### PCT

## WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



# INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5:		(11) International Publication Number:	WO 93/24586
C09K 5/04, 3/30, C08J 9/14	A1	(43) International Publication Date:	9 December 1993 (09.12.93)

(21) International Application Number:	PCT/US93/04614	(74) Agents: WALKER, P., Michael et al.; E.I. du Pont de Ne-
(22) International Filing Date:	20 May 1993 (20.05.93)	mours and Company, Legal/Patent Records Center,

30) Priority data:  07/890,508 28 May 1992 (28.05.92) 07/954,999 1 October 1992 (01.10.92) 08/026,714 5 March 1993 (05.03.93)	US	(81) Designated States: AU, BB, BG, BR, BY, CA, CZ, FI, HU, JP, KP, KR, KZ, LK, MG, MN, MW, NO, NZ, PL, RO, RU, SD, SK, UA, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

(71) Applicant: E.I. DU	PONT DE NEMOURS AND COM.	
PANY [US/US];	1007 Market Street, Wilmington, DE	
19898 (US).		

(72) Inventors: KLUG, Diana, Lynn; 614 Northside Drive, Wilmington, DE 19809 (US). MINOR, Barbara, Haviland; 233 Green Haven Drive, Elkton, MD 21921 (US). PATRON, Donna, Marie; 211 West Silver Fox Road, Newark, DE 19702 (US). CHISOLM, Tuncen, E., C.; 1601 Stonebridge Boulevard, New Castle, DE 19720 (US). SIEVERT, Allen, Capron; 215 Rhett Lane, Elkton, MD 21921 (US).

Published

With international search report.

(54) Title: COMPOSITIONS OF A FLUOROETHER AND A HYDROFLUOROCARBON

#### (57) Abstract

This invention relates to compositions that include at least one fluoroether and at least one hydrofluorocarbon. Included in this invention are compositions of a cyclic or acyclic hydrofluoroether of the formula  $C_aF_bH_{2a+2-b}O_c$  wherein a=2 or 3 and  $3 \le b \le 8$  and c=1 or 2 and a hydrofluorocarbon of the formula  $C_nF_mH_{2n+2-m}$  wherein  $1 \le n \le 4$  and  $1 \le m \le 8$ . Such compositions may be used as refrigerants, cleaning agents, expansion agents for polyolefins and polyurethanes, aerosol propellants, heat transfer media, gaseous dielectrics, fire extinguishing agents, power cycle working fluids, polymerization media, particulate removal fluids, carrier fluids, buffing abrasive agents, and displacement drying agents.

#### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

•					Manufacula :
AT	- Austria	FR	France	MR	Mauritania
ΑU	Australia	GA	Gabon	MW	Malawi
BB	Burbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	· · GN	Guinca	Ю	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BÇ.	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	· IE	treland	PT	Portugal :
BR	Brazil	· IT	Italy	RO	Romania
CA .	Canada	<b>9L</b>	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic	SD	Sudan
	Congo		of Korea	SE	Sweden
CG CH	Switzerland	KR	Republic of Korea	SK	Slovak Republic
	Côte d'Ivoire	ΚZ	Kazakhstan	SN	Senegal
CI :	<del></del> -	1.1	Liechtenstein	SU	Soviet Union
CM	Canteroon	LK	Sri Lanka	TD	Chad
cs	Czechoslovakia	1.U	i.uxembourg	TG	Tugo
CZ	Czech Republic	MC	Munaco	UA	Ukraine
DE	Germany		•	US	United States of America
DK	Denmark	MG	Madagascar	VN	Viet Nam
ES	Spain	MI.	Mali	VII.	7 ICI 144111
FI	Finland	MN	Mongolia		

10

15

20

25

30

35

#### TITLE

#### COMPOSITIONS OF A FLUOROETHER AND A HYDROFLUOROCARBON

#### FIELD OF THE INVENTION

This invention relates to compositions that include at least one fluoroether and at least one hydrofluorocarbon. Such compositions may be used as refrigerants, cleaning agents, expansion agents for polyolefins and polyurethanes, aerosol propellants, heat transfer media, gaseous dielectrics, fire extinguishing agents, power cycle working fluids, polymerization media, particulate removal fluids, carrier fluids, buffing abrasive agents, displacement drying agents and as carriers for sterilant gases.

Included in this invention are compositions which include a fluoroether and a hydrofluorocarbon in which the halocarbon global warming potential (HGWP) of the hydrofluorocarbon is lowered by adding the fluoroether to the hydrofluorocarbon. Also included in this invention are compositions a fluoroether and a hydrofluorocarbon that are azeotropic or azeotrope-like.

#### **BACKGROUND OF THE INVENTION**

Fluorinated hydrocarbons have many uses, one of which is as a refrigerant. Such refrigerants include dichlorodifluoromethane (CFC-12) and chlorodifluoromethane (HCFC-22).

In recent years it has been suggested that certain chlorofluorocarbon (CFC) and hydrochlorofluorocarbon (HCFC) refrigerants released into the atmosphere may adversely affect the ozone layer. Although this proposition has not yet been completely established, there is a movement toward the control of the use and the production of certain CFCs and HCFCs under an international agreement.

In order to address the potential problem of ozone depletion, it has been suggested that chlorofluorocarbon refrigerants and hydrochlorofluorocarbon refrigerants be replaced with hydrofluorocarbon refrigerants. Since the hydrofluorocarbon (HFC) refrigerants contain no chlorine, they have zero ozone depletion potential.

Another environmental concern is the role of CFCs in the "greenhouse effect". The greenhouse effect refers to the warming of the Earth's climate that takes place when atmospheric gases, which are relatively transparent to visible light and allow sunshine to reach the Earth, trap heat by absorbing infrared radiation released by the Earth.

10

15

20

25

35

There is presently no universally accepted methodology for combining all relevant factors into a singe global warming potential for emissions of gases such as CFCs. One approach is to define the greenhouse effect of a compound in terms of a potential to enhance global warming relative to a known standard. One such definition is known as a halocarbon global warming potential (HGWP), which is the ratio of incremental radiative warming resulting from an emission of a gas, over the lifetime of the gas in the atmosphere, to the calculated warming that would result from a release of the same mass of reference gas CFC-11.

While HFCs may have a zero ozone depletion potential, some HFCs may have an HGWP that may be undesirable and subject to governmental regulation. Accordingly, there is also a demand for the development of refrigerants that have a low ozone depletion potential while at the same time having a low HGWP.

It is preferred that refrigerants that include more than one component be azeotropic or azeotrope-like so that the composition of the refrigerant does not change when leaked or discharged to the atmosphere from refrigeration equipment. A change in composition of a refrigerant may affect its properties, such as performance or flammability.

It is also desirable to use compositions that have a low ozone depletion potential and/or a low HGWP and/or that are azeotropic or azeotropelike as cleaning agents, blowing agents in the manufacture of closed-cell polyurethane, phenolic and thermoplastic foams, as propellants in aerosols, as heat transfer media, gaseous dielectrics, fire extinguishing agents, power cycle working fluids, such as for heat pumps, inert media for polymerization reactions, fluids for removing particulates from metal surfaces, as carrier fluids that may be used, for example, to place a fine film of lubricant on metal parts, or as buffing abrasive agents to remove buffing abrasive compounds from surfaces such as metal, as displacement drying agents for removing water, such as from jewelry or metal parts, as resist developers in conventional circuit manufacturing techniques including chlorine-type developing agents, and as strippers for photoresists when used with, for example, a chlorohydrocarbon, such as 1,1,1-trichloroethane or trichloroethylene.

10

15

#### **SUMMARY OF THE INVENTION**

This invention relates to compositions that include a fluoroether and a hydrofluorocarbon. Included in this invention are compositions of a cyclic or acyclic hydrofluoroether of the formula  $C_aF_bH_{2a+2-b}O_c$  wherein a=2 or 3 and  $3 \le b \le 8$  and c=1 or 2 and a hydrofluorocarbon of the formula  $C_nF_mH_{2n+2-m}$  wherein  $1 \le n \le 4$  and  $1 \le m \le 8$ . Such compositions may be used as refrigerants, cleaning agents, expansion agents for polyolefins and polyurethanes, aerosol propellants, heat transfer media, gaseous dielectrics, fire extinguishing agents, power cycle working fluids, polymerization media, particulate removal fluids, carrier fluids, buffing abrasive agents, and displacement drying agents.

Another aspect of this invention relates to the discovery that the HGWP of a hydrofluorocarbon can be lowered by adding to the hydrofluorocarbon a fluoroether having a lower HGWP than the HGWP of the hydrofluorocarbon. Accordingly, the present invention relates to a composition of a first component that includes a hydrofluorocarbon and a second component that includes a fluoroether that has an HGWP less than the HGWP of the first component, such that the HGWP of the composition is less than the HGWP of the first component.

Also included in this invention are compositions which include a fluoroether and a hydrofluorocarbon that are azeotropic or azeotrope-like.

#### 25

30

35 -

40

20

#### **DETAILED DESCRIPTION**

The present invention relates to compositions that include a fluoroether and a hydrofluorocarbon (HFC). Included in this invention are compositions of a cyclic or acyclic hydrofluoroether of the formula  $C_aF_bH_{2a+2-b}O_c$  wherein a=2 or 3 and  $3 \le b \le 8$  and c=1 or 2 and a hydrofluorocarbon of the formula  $C_nF_mH_{2n+2-m}$  wherein  $1 \le n \le 4$  and  $1 \le m \le 8$ . These compositions may be used as refrigerants, cleaning agents, expansion agents for polyolefins and polyurethanes, aerosol propellants, heat transfer media, gaseous dielectrics, fire extinguishing agents, power cycle working fluids, polymerization media, particulate removal fluids, carrier fluids, buffing abrasive agents, and displacement drying agents.

The fluoroethers that are included in this invention have two or three carbon atoms. Examples of such fluoroethers include the following.

- 1. Hexafluorodimethyl ether (116E, or CF3OCF3, boiling point = 59.0°C),
- Pentafluorodimethyl ether (125E, or CHF<sub>2</sub>OCF<sub>3</sub>, boiling point = -36.2°C),

Bis(difluoromethyl) ether (134E, or CHF<sub>2</sub>OCHF<sub>2</sub>, boiling point = 5 3. 5°C), Fluoromethyl trifluoromethyl ether (134aE, or CH<sub>2</sub>FOCF<sub>3</sub>, boiling 4. point =  $-20.0^{\circ}$ C), Trifluoromethyl methyl ether (143aE, or CH3OCF3, boiling point = 5. -24.2°C), 10 Perfluorooxetane (C-216E or CF<sub>2</sub>O 6. CF2CF2, boiling point = -29.2°C), 2,2,4,4,5,5-hexafluoro-1,3-dioxolane (C-216E2 or C<sub>3</sub>F<sub>6</sub>O<sub>2</sub>, having a 15 7. structure of CF<sub>2</sub> 20 CF<sub>2</sub>-CF<sub>2</sub> boiling point = -22.1°C), Perfluoromethyl ethyl ether (218E, or CF<sub>3</sub>OCF<sub>2</sub>CF<sub>3</sub>, boiling point = -23.3°C), Perfluorodimethoxymethane (218E2, or CF<sub>3</sub>OCF<sub>2</sub>OCF<sub>3</sub>, boiling point 25 = -10.2°C), 10. 2,2,3,4,4-pentafluorooxetane (C-225e $E\alpha\beta$ , or C3HF5O, having a structure of  $O-CF_2$ F<sub>2</sub>C-CHF boiling point = 3.4°C), 11. 1-trifluoromethoxy-1,1,2,2-tetrafluoroethane (227ca $E\alpha\beta$ , or CF<sub>3</sub>OCF<sub>2</sub>CHF<sub>2</sub>, boiling point = about -3°C), 12. Difluoromethoxy pentafluoroethane (227caEβγ, or CHF2OCF2CF3, 35 boiling point =  $-8.0^{\circ}$ C), 1-trifluoromethoxy-1,2,2,2-tetrafluoroethane (227eaE, or 13. CF<sub>3</sub>OCHFCF<sub>3</sub>, boiling point = -9.4°C), 2,2,4,4-tetrafluorooxetane (C-234fE $\alpha\beta$ , or C<sub>3</sub>H<sub>2</sub>F<sub>4</sub>O, having a structure 40

O-CF<sub>2</sub> | | F<sub>2</sub>C-CH<sub>2</sub>

boiling point = 21.2°C),

10

15. 2,2,3,3-tetrafluorooxetane (C-234fE $\beta\gamma$ , or C<sub>3</sub>H<sub>2</sub>F<sub>4</sub>O, having a structure of

O-CH<sub>2</sub> | | F<sub>2</sub>C-CF<sub>2</sub>

15

boiling point =28°C),

16. 1-difluoromethoxy-1,1,2,2-tetrafluoroethane (236caE, or CHF<sub>2</sub>OCF<sub>2</sub>CHF<sub>2</sub>, boiling point = 28.5°C),

20

- 17. 1-difluoromethoxy-1,2,2,2-tetrafluoroethane (236eaE $\beta\gamma$ , or CHF2OCHFCF3, boiling point = 23.2°C),
- 18. 1-trifluoromethoxy-2,2,2-trifluoroethane (236faE, or CF<sub>3</sub>OCH<sub>2</sub>CF<sub>3</sub>, boiling point = 5.6°C),
- 19. 1-difluoromethoxy-2,2,2-trifluoroethane (245faE $\beta\gamma$ , or CHF2OCH2CF3, boiling point = 29°C).

25

116E (CAS Reg. No. 1479-49-8) has been prepared by electrochemical fluorination of dimethyl ether as disclosed by Simons in U. S. Patent 2,519,983.

30

125E (CAS Reg. No. 3822-68-2) has been prepared by electrochemical fluorination of dimethyl ether (CH<sub>3</sub>OCH<sub>3</sub>) as disclosed by Fox, et. al. in U. S. Patent 3,511,760 and by Hutchinson in U. S. Patent 3,887,439.

134E (CAS Reg. No. 1691-17-4) can be prepared by reaction of antimony trifluoride with CHF<sub>2</sub>OCHCl<sub>2</sub> as disclosed by O'Neill in GB 2,248,617.

35

134aE (CAS Reg. No. 2261-01-0) has been made by the electrochemical fluorination of methyl 2-methoxypropionate as reported by Berenblit, et. al. Zh. Org. Khim., Vol. 12, pp. 767-770 (1976).

143aE (CAS Reg. No. 421-14-7) has been made by the reaction of methyl fluoroformate with sulfur tetrafluoride as reported by Aldrich and Sheppard,

40 J. Am. Chem. Soc., Vol. 29, 11-15 (1964).

C-216E (CAS Reg. No. 425-82-1) can be made by electrochemical

20

30

35

40

fluorination of trimethylene oxide (oxetane) in anhydrous hydrogen fluoride as disclosed by Kauck and Simons in U. S. Patent 2,594,272.

C-216E2 (CAS Reg. No. 21297-65-4) has been prepared by UV irradiation of perfluoro-b-oxa-d-valerolactone in the vapor or liquid phase as reported by Throckmorton in <u>J. Org. Chem.</u>, Vol. 34, pp. 3438-3440 (1969). The lactone was prepared by the reaction of KF with perfluorooxydiacetyl chloride.

218E (CAS Reg. No. 665-16-7) has been made by direct fluorination of CF<sub>3</sub>OCH<sub>2</sub>CF<sub>3</sub> (prepared by reaction of CF<sub>3</sub>OF with vinylidene fluoride) as reported by Sekiya and Ueda in Chemistry Letters, pp. 609-612 (1990).

218E2 (CAS Reg. No. 53772-78-4) was made in the electrochemical fluorination of methyl 2-methoxypropionate as reported by Berenblit, et. al. Zh. Org. Khim., Vol. 12, pp. 767-770 (1976).

C-225eEαβ (CAS Reg. No. 144109-03-5) may be prepared by direct fluorination of trimethylene oxide (cyclo-CH<sub>2</sub>CH<sub>2</sub>CH<sub>2</sub>CH<sub>2</sub>O-) using techniques described by Lagow and Margrave in Progress in Inorganic Chemistry, Vol. 26, pp. 161-210 (1979) or by Adcock and Cherry in Ind. Eng. Chem. Res., Vol. 26, pp. 208-215 (1987). The direct fluorination is carried out to the desired level of fluorine incorporation into the starting material, and products receovered by fractional distillation.

227caΕαβ (CAS Reg. No. 2356-61-8) has been prepared by reacting difluoroacetyl fluoride with cesium fluoride and carbonyl fluoride followed by treatment with sulfur tetrafluoride as disclosed by Eisemann in U. S. Patent 3,362,190.

 $227caE\beta\gamma$  (CAS Reg. No. 53997-64-1) has been made by electrochemical fluorination of CHCl<sub>2</sub>OCF<sub>2</sub>CHClF as reported by Okazaki, et. al. J. Fluorine Chem., Vol. 4, pp. 387-397 (1974).

227eaE (CAS Reg. No. 2356-62-9) was prepared by reacting 2-trifluoromethoxy-tetrafluoropropionyl fluoride (CF<sub>3</sub>CF(OCF<sub>3</sub>)COF) with aqueous potassium hydroxide at 230°C as disclosed by Eisemann in U. S. Patent 3,362,190.

C-234fEαβ may be prepared by direct fluorination of trimethylene oxide (cyclo-CH<sub>2</sub>CH<sub>2</sub>CH<sub>2</sub>O-) using techniques described by Lagow and Margrave in Progress in Inorganic Chemistry, Vol. 26, pp. 161-210 (1979) or by Adcock and Cherry in Ind. Eng. Chem. Res., Vol. 26, pp. 208-215 (1987). The direct fluorination is carried out to the desired level of fluorine incorporation into the starting material, and products receovered by fractional distillation.

C-234fEβγ (CAS Reg. No. 765-63-9) has been prepared by Weinmayr (J. Org. Chem., Vol. 28, pp. 492-494 (1963)) as a by-product from the reaction of

15

20

25

30

35

5 TFE with formaldehyde in HF.

236caE (CAS Reg. No. 32778-11-3) has been prepared by fluorination of CHCl<sub>2</sub>OCF<sub>2</sub>CHF<sub>2</sub> (prepared in turn by chlorination of CH<sub>3</sub>OCF<sub>2</sub>CHF<sub>2</sub>) using anhydrous hydrogen fluoride with antimony pentachloride catalyst as reported by Terrell, et. al. in J. Medicinal Chem., Vol. 15, pp. 604-606 (1972).

236eaEβγ (CAS Reg. No. 57041-67-5) has been prepared by chlorination of methoxy acetyl chloride to give the intermediate, CHCl<sub>2</sub>OCHClCOCl, which was isolated and reacted with sulfur tetrafluoride at 150C to give the product as disclosed by Halpern and Robin in U. S. Patent 4,888,139.

236faE (CAS Reg. No. 20193-67-3) has been prepared by reaction of 2,2,2-trifluoroethanol with carbonyl fluoride to give the intermediate, CF<sub>3</sub>CH<sub>2</sub>OCOF, which was in turn reacted with sulfur tetrafluoride at 150-200°C to give the product as disclosed by Eisemann in U. S. Patent 3,394,878.

245faE $\beta\gamma$  (CAS Reg. No. 1885-48-9) has been prepared by the reaction of chlorodifluoromethane with trifluoroethanol in the presence of potassium hydroxide as disclosed by Croix in US Patent No. 3,637,477.

The HFCs that may be combined with the fluoroethers include one or more of the following: difluoromethane (HFC-32), fluoromethane (HFC-41), pentafluoroethane (HFC-125), 1,1,2,2-tetrafluoroethane (HFC-134), 1,1,1,2-tetrafluoroethane (HFC-134a), 1,1,2-trifluoroethane (HFC-143), 1,1,1-trifluoroethane (HFC-143a), 1,1-difluoroethane (HFC-152a), fluoroethane (HFC-161), 1,1,1,2,2,3,3-heptafluoropropane (HFC-227ca), 1,1,1,2,3,3,3-hexafluoropropane (HFC-226ca), 1,1,1,2,2,3-hexafluoropropane (HFC-236ca), 1,1,1,2,2,3-hexafluoropropane (HFC-236cb), 1,1,2,2,3-pentafluoropropane (HFC-245ca), 1,1,1,2,2-pentafluoropropane (HFC-245cb), 1,1,2,3,3-pentafluoropropane (HFC-245ca), 1,1,1,3,3-

pentafluoropropane (HFC-245fa), 1,2,2,3-tetrafluoropropane (HFC-254ca), 1,1,2,2-tetrafluoropropane (HFC-254cb), 1,1,1,2-tetrafluoropropane (HFC-254eb), 1,2,2-trifluoropropane (HFC-263ca), 1,1,1-trifluoropropane (HFC-263fb), 2,2-difluoropropane (HFC-272ca), 1,2-difluoropropane (HFC-272ea), 1,1-difluoropropane (HFC-272fb), 2-fluoropropane (HFC-281ea), 1-fluoropropane (HFC-281fa), 1,1,1,3,3,4,4,4-octafluorobutane (HFC-338mf), 1,1,1,4,4,4-

The following can be used as refrigerants: compositions of a cyclic or acyclic hydrofluoroether of the formula  $C_aF_bH_{2a+2-b}O_c$  wherein a=2 or 3 and  $3 \le b \le 8$  and c=1 or 2 and a hydrofluorocarbon of the formula  $C_nF_mH_{2n+2-m}$ 

hexafluorobutane (HFC-356mff), or (CF<sub>3</sub>)<sub>2</sub>CHCH<sub>3</sub>, (HFC-356mmz).

20

5 wherein  $1 \le n \le 4$  and  $1 \le m \le 8$ . Examples of such compositions include the following.

1-99 weight percent 116E and 1-99 weight percent HFC-32, HFC-41, HFC-125, HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a, HFC-161, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236ea, HFC-236fa, HFC-245ca, HFC-245cb, HFC-245ca, HFC-245ca, HFC-254cb, HFC-254cb, HFC-254cb, HFC-254cb, HFC-254cb, HFC-263ca, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281ea, or HFC-281fa.

1-99 weight percent 125E and 1-99 weight percent HFC-32, HFC-125, HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a, HFC-161, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236fa, HFC-245ca, HFC-245cb, HFC-245ea, HFC-254ca, HFC-254cb, HFC-254eb, HFC-263ca, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281ea, or HFC-281fa.

1-99 weight percent 134E and 1-99 weight percent HFC-32, HFC-125, HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a, HFC-161, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236ea, HFC-236fa, HFC-245ca, HFC-245ca, HFC-245ca, HFC-254cb, HFC-254cb, HFC-254cb, HFC-263ca, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281ea, HFC-281fa, HFC-338mf or 356mff.

1-99 weight percent 134aE and 1-99 weight percent HFC-32, HFC-125, HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152, HFC-152a, HFC-161, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236fa, HFC-245ca, HFC-245ca, HFC-245ca, HFC-254cb, HFC-254cb, HFC-254cb, HFC-263ca, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281ea, or HFC-281fa.

1-99 weight percent 143aE and 1-99 weight percent HFC-32, HFC-30 125, HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a, HFC-161, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236fa, HFC-245ca, HFC-245cb, HFC-245ca, HFC-254cb, HFC-254cb, HFC-254cb, HFC-263ca, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281ea, or HFC-281fa.

1-99 weight percent C216E, and 1-99 weight percent HFC-32, HFC-35, HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a, HFC-161, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236fa, HFC-245ca, HFC-245cb, HFC-245ea, HFC-254ca, HFC-254cb, HFC-254eb, HFC-263ca, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281ea, or HFC-281fa.

1-99 weight percent C-216E2 and 1-99 weight percent HFC-32, HFC-40 134, HFC-134a, HFC-143, HFC-152a, HFC-161, or HFC-245cb.
1-99 weight percent 218E and 1-99 weight percent HFC-32, HFC-125,

25

30

35

5 HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a, HFC-161, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236fa, HFC-245ca, HFC-245cb, HFC-245ca, HFC-254ca, HFC-254cb, HFC-254cb, HFC-254cb, HFC-263ca, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281ea, or HFC-281fa.

1-99 weight percent 218E2 and 1-99 weight percent HFC-32, HFC-10 125, HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a, HFC-161, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236fa, HFC-245ca, HFC-245cb, HFC-245ca, HFC-254cb, HFC-254cb, HFC-254cb, HFC-263fa, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281ea, or HFC-281fa.

1-99 weight percent C-225e $E\alpha\beta$  and 1-99 weight percent HFC-143,

15 HFC-236cb, HFC-236ea, or HFC-245cb.

1-99 weight percent 227caEαβ and 1-99 weight percent HFC-32, HFC-125, HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a, HFC-161, HFC-227ca, HFC-227ca, HFC-236ca, HFC-236cb, HFC-236fa, HFC-245ca, HFC-245cb, HFC-245fa, HFC-254ca, HFC-254cb, HFC-254cb, HFC-263ca, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281ea, or HFC-281fa.

1-99 weight percent 227caEβγ and 1-99 weight percent HFC-32, HFC-125, HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a, HFC-161, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236fa, HFC-245ca, HFC-245cb, HFC-245ea, HFC-245fa, HFC-254ca, HFC-254cb, HFC-254cb, HFC-263ca, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281fa.

1-99 weight percent 227eaE and 1-99 weight percent HFC-32, HFC-125, HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a, HFC-161, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236fa, HFC-245ca, HFC-245cb, HFC-245ca, HFC-254ca, HFC-254cb, HFC-254cb, HFC-263ca, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281ea, or HFC-281fa.

1-99 weight percent C-234fEaß and 1-99 weight percent HFC-245cb, HFC-356mff or HFC-356mmz.

1-99 weight percent C-234fE $\beta\gamma$  and 1-99 weight percent HFC-245ca, HFC-245cb, HFC-245ea, HFC-254ca, HFC-356mff or HFC-356mmz.

1-99 weight percent 236caE and 1-99 weight percent HFC-125, HFC-134, HFC-134a, HFC-143a, HFC-152a, HFC-161, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236fa, HFC-245ca, HFC-245cb, HFC-245ea, HFC-245fa, HFC-254ca, HFC-254cb, HFC-254cb, HFC-263ca, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281ea, or HFC-281fa.

1-99 weight percent 236eaEβγ and 1-99 weight percent HFC-125, HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a, HFC-161, HFC-227ca,

- 5 HFC-227ea, HFC-236ca, HFC-236cb, HFC-236fa, HFC-245ca, HFC-245cb, HFC-245ea, HFC-245fa, HFC-254ca, HFC-254cb, HFC-254eb, HFC-263ca, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281ea, HFC-281fa, HFC-338mf, HFC-356mff or HFC-356mmz.
- 1-99 weight percent 236faE and 1-99 weight percent HFC-32, HFC-10 125, HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a, HFC-161, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236fa, HFC-245ca, HFC-245cb, HFC-245ea, HFC-245fa, HFC-254ca, HFC-254cb, HFC-254cb, HFC-263ca, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281ea, or HFC-281fa.

15

20

25

1-99 weight percent 245faE $\beta\gamma$  and 1-99 weight percent HFC-125, 5 HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a, HFC-161, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236fa, HFC-245ca, HFC-245cb, HFC-245ea, HFC-245fa, HFC-254ca, HFC-254cb, HFC-263ca, HFC-263fb, HFC-272ca, HFC-272ea, HFC-272fb, HFC-281ea, HFC-281fa, or HFC-356mff.

The present invention also relates to the discovery of azeotropic or azeotrope-like compositions of effective amounts of the following compounds to form an azeotropic or azeotrope-like composition at a specific temperature or pressure:

116E and HFC-32, HFC-41, HFC-125, HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a or HFC-161; 125E and HFC-32, HFC-134, HFC-134a. HFC-143, HFC-152a or HFC-161; 134E and HFC-143, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236ea, HFC-236fa, HFC-245cb, HFC-254cb, HFC-254eb, HFC-338mf, or HFC-356mff; 134aE and HFC-32, HFC-134, HFC-143, HFC-152a, HFC-227ca, HFC-227ea or HFC-245cb; 143aE and HFC-32, HFC-134. HFC-143a, HFC-152a, HFC-227ca, HFC-227ea or HFC-245cb; C216E and HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161 or HFC-245cb; C216E2 and HFC-32, HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161 or HFC-245cb; 218E and HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161 or HFC-263fb; 218E2 and HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161, HFC-236fa or HFC-263fb; C-225eE $\alpha\beta$  and HFC-143, HFC-236cb, HFC-236ea or HFC-245cb; 227caE $\alpha\beta$  and HFC-32, HFC-143, HFC-245cb, HFC-272ca, HFC-281ea or HFC-281fa; 227caΕβγ and HFC-32, HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161, HFC-263fb, HFC-272ca, HFC-281ea or HFC-281fa; 227eaE and HFC-32, HFC-134, HFC-134a. HFC-143, HFC-152a, HFC-161, HFC-263fb, HFC-272ca, HFC-281ea or HFC-281fa; C-234fEαβ and HFC-245cb, HFC-245eb, HFC-356mff or HFC-356mmz; C-30 234fE $\beta\gamma$  and HFC-245ca, HFC-245cb, HFC-254ca, HFC-356mff or HFC-356mmz; 236caE and HFC-143, HFC-245ca, or HFC-254ca; 236eaE $\beta\gamma$  and HFC-143, HFC-245ca, HFC-263ca, HFC-338mf, HFC-356mff or HFC-356mmz; or 236faE and HFC-32, HFC-143, HFC-272ca, HFC-272fb or HFC-281fa; 245faE8~ 35 and HFC-356mff.

10

15

20

25

**30** ...

35

By "azeotropic" composition is meant a constant boiling liquid admixture of two or more substances that behaves as a single substance. One way to characterize an azeotropic composition is that the vapor produced by partial evaporation or distillation of the liquid has the same composition as the liquid from which it was evaporated or distilled, that is, the admixture distills/refluxes without compositional change. Constant boiling compositions are characterized as azeotropic because they exhibit either a maximum or minimum boiling point, as compared with that of the non-azeotropic mixtures of the same components.

By "azeotrope-like" composition is meant a constant boiling, or substantially constant boiling, liquid admixture of two or more substances that behaves as a single substance. One way to characterize an azeotrope-like composition is that the vapor produced by partial evaporation or distillation of the liquid has substantially the same composition as the liquid from which it was evaporated or distilled, that is, the admixture distills/refluxes without substantial compositional change.

It is recognized in the art that a composition is azeotrope-like if, after 50 weight percent of the composition is removed such as by evaporation or boiling off, the difference in vapor pressure between the original composition and the composition remaining after 50 weight percent of the original composition has been removed is less than 10 percent, when measured in absolute units. By absolute units, it is meant measurements of pressure and, for example, psia, atmospheres, bars, torr, dynes per square centimeter, millimeters of mercury, inches of water and other equivalent terms well known in the art. If an azeotrope is present, there is no difference in vapor pressure between the original composition and composition remaining after 50 weight percent of the original composition has been removed.

Therefore, included in this invention are compositions of effective amounts of a fluoroether and an HFC such that after 50 weight percent of an original composition is evaporated or boiled off to produce a remaining composition, the difference in the vapor pressure between the original composition and the remaining composition is about 10 percent or less. Examples of such compositions include the following:

116E and HFC-32, HFC-41, HFC-125, HFC-134, HFC-134a, HFC-5 143, HFC-143a, HFC-152a or HFC-161; 125E and HFC-32, HFC-134, HFC-134a, HFC-143, HFC-152a or HFC-161; 134E and HFC-143, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236ea, HFC-236fa, HFC-245cb, HFC-254cb, HFC-254eb, HFC-338mf or HFC-356mff; 134aE and HFC-32, HFC-134, HFC-143, HFC-152a, HFC-227ca, HFC-227ea or HFC-245cb; 143aE and HFC-32, HFC-134, HFC-10 143a, HFC-152a, HFC-227ca, HFC-227ea or HFC-245cb; C216E and HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161 or HFC-245cb; C-216E2 and HFC-32, HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161 or HFC-245cb; 218E and HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161 or HFC-263fb; 218E2 and HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161, HFC-236fa or HFC-263fb; 15 C-225eE $\alpha\beta$  and HFC-143, HFC-236cb, HFC-236ea or HFC-245cb; 227caE $\alpha\beta$  and HFC-32, HFC-143, HFC-245cb, HFC-272ca, HFC-281ea or HFC-281fa; 227caEβγ and HFC-32, HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161, HFC-263fb, HFC-272ca, HFC-281ea or HFC-281fa; 227eaE and HFC-32, HFC-134, HFC-134a. HFC-143, HFC-152a, HFC-161, HFC-263fb, HFC-272ca, HFC-281ea or HFC-20 281fa; C-234fEαβ and HFC-245cb, HFC-245eb, HFC-356mff or HFC-356mmz; C-234fE\(\beta\) and HFC-245ca, HFC-245cb, HFC-245ea, HFC-254ca, HFC-356mff or HFC-356mmz; 236caE and HFC-143, HFC-245ca or HFC-254ca; 236eaE $\beta\gamma$  and HFC-143, HFC-245ca, HFC-263ca, HFC-338mf, HFC-356mff or HFC-356mmz; 236faE and HFC-32, HFC-143, HFC-272ca, HFC-272fb or HFC-281fa; or 245faE $\beta\gamma$ 25 and HFC-356mff.

Substantially constant boiling, azeotropic or azeotrope-like compositions of this invention comprise the following (all at 25°C):

30		TABLE 1	
	<b>COMPONENTS</b>	<b>WEIGHT RANGES</b>	PREFERRED
	116E/HFC-32	50.0-88.0/12.0-50.0	50.0-88.0/12.0-50.0
	116E/HFC-41	5.0-84.0/16.0-95.0	40.0-84.0/16.0-60.0
•	116E/HFC-125	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0
35	116E/HFC-134	52.0-99.0/1.0-48.0	70.0-99.0/1.0-30.0
	116E/HFC-134a	53.0-99.0/1.0-47.0	53.0-99.0/1.0-47.0
	116E/HFC-143	60.0-99.0/1.0-40.0	60.0-99.0/1.0-40.0
	116E/HFC-143a	1.0-99.0/1.0-99.0	30.0-99.0/1.0-70.0
	116E/HFC-152a	60.0-99.0/1.0-40.0	60.0-99.0/1.0-40.0
40	116E/HFC-161	60.0-99.0/1.0-40.0	60.0-99.0/1.0-40.0
	125E/HFC-32	25.0-73.0/27.0-75.0	30.0-70.0/30.0-70.0
			•
•	•		

5	125E/HFC-134	37.0-99.0/1.0-63.0	70.0-99.0/1.0-30.0
	125E/HFC-134a	1.0-99.0/1.0-99.0	1.0-50.0/50.0-99.0
	125E/HFC-143	1.0-43.0/57.0-99.0	1.0-30.0/70.0-99.0
	125E/HFC-152a	1.0-61.0/39.0-99,0	1.0-40.0/60.0-99.0
	125E/HFC-161	1.0-71.0/29.0-99.0	30.0-50.0/50.0-70.0
10	134E/HFC-143	1.0-99.0/1.0-99.0	1.0-50.0/50.0-99.0
	134E/HFC-227ca	1.0-51.0/49.0-99.0	1.0-40.0/60.0-99.0
	134E/HFC-227ea	1.0-49.0/51.0-99.0	1.0-40.0/60.0-99.0
	134E/HFC-236ca	1.0-99.0/1.0-99.0	30.0-99.0/1.0-70.0
	134E/HFC-236cb	1.0-99.0/1.0-99.0	1.0-70.0/30.0-99.0
15	134E/HFC-236ea	1.0-99.0/1.0-99.0	30.0-70.0/30.0-70.0
	134E/HFC-236fa	1.0-99.0/1.0-99.0	1.0-80.0/20.0-99.0
	134E/HFC-245cb	1.0-62.0/38.0-99.0	1.0-50.0/50.0-99.0
	134E/HFC-254cb	1.0-99.0/1.0-99.0	1.0-70.0/30.0-99.0
	134E/HFC-254eb	1.0-99.0/1.0-99.0	1.0-99.0/1.0-99.0
20	134E/HFC-338mf	27.0-99.0/1.0-73.0	40.0-80.0/20.0-60.0
٠	134E/HFC-356mff	40.0-99.0/1.0-60.0	40.0-99.0/1.0-60.0
	134aE/HFC-32	1.0-55.0/45.0-99.0	1.0-55.0/45.0-99.0
	134aE/HFC-134	1.0-99.0/1.0-99.0	20.0-60.0/40.0-80.0
	134aE/HFC-143	52.0-99.0/1.0-48.0	52.0-99.0/1.0-48.0
25	134aE/HFC-152a	1.0-99.0/1.0-99.0	1.0-99.0/1.0-99.0
	134aE/HFC-227ca	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0
	134aE/HFC-227ea	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0
	134aE/HFC-245cb	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0
	143aE/HFC-32	1.0-54.0/46.0-99.0	1.0-54.0/46.0-99.0
30	143aE/HFC-134	1.0-99.0/1.0-99.0	30.0-99.0/1.0-70.0
· · · · ·	143aE/HFC-143a	1.0-53.0/47.0-99.0	1.0-53.0/47.0-99.0
	143aE/HFC-152a	1.0-99.0/1.0-99.0	20.0-80.0/20.0-80.0
	143aE/HFC-227ca	1.0-99.0/1.0-99.0	1.0-80.0/20.0-99.0
	143aE/HFC-227ea	1.0-99.0/1.0-99.0	1.0-90.0/10.0-99.0
35	143aE/HFC-245cb	20.0-99.0/1.0-80.0	20.0-80.0/20.0-80.0
	C216E/HFC-134	1.0-99.0/1.0-99.0	50.0-99.0/1.0-50.0
	C216E/HFC-134a	1.0-99.0/1.0-99.0	20.0-80.0/20.0-80.0
	C216E/HFC-143	61.0-99.0/1.0-39.0	61.0-99.0/1.0-39.0
	C216E/HFC-152a	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0
40	C216E/HFC-161	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0
	C216E/HFC-245cb	1.0-99.0/1.0-99.0	30.0-99.0/1.0-70.0

5	C216E2/HFC-32	1.0-70.0/30.0-99.0	30.0-70.0/30.0-70.0
	C216E2/HFC-134	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0
	C216E2/HFC-134a	1.0-99.0/1.0-99.0	1.0-80.0/20.0-99.0
	C216E2/HFC-143	58.0/99.0/1.0-42.0	58.0-99.0/1.0-42.0
	C216E2/HFC-152a	1.0-99.0/1.0-99.0	40.0-99.0/1.0-60.0
10	C216E2/HFC-161	1.0-84.0/16.0-99.0	20.0-84.0/16.0-80.0
	C216E2/HFC-245cb	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0
	218E/HFC-134	35.0-99.0/1.0-65.0	50.0-80.0/20.0-50.0
	218E/HFC-134a	1.0-99.0/1.0-99.0	20.0-80.0/20.0-80.0
	218E/HFC-143	57.0-99.0/1.0-43.0	57.0-99.0/1.0-43.0
15	218E/HFC-152a	41.0-99.0/1.0-59.0	41.0-99.0/1.0-59.0
	218E/HFC-161	39.0-84.0/16.0-61.0	39.0-84.0/16.0-61.0
	218E/HFC-263fb	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0
	218E2/HFC-134	1.0-79.0/21.0-99.0	20.0-70.0/30.0-80.0
	218E2/HFC-134a	1.0-72.0/28.0-99.0	1.0-60.0/40.0-99.0
20	218E2/HFC-143	52.0-91.0/9.0-48.0	52.0-91.0/9.0-48.0
	218E2/HFC-152a	1.0-81.0/19.0-99.0	20.0-70.0/30.0-80.0
	218E2/HFC-161	1.0-77.0/23.0-99.0	20.0-77.0/23.0-80.0
	218E2/HFC-236fa	1.0-99.0/1.0-99.0	30.0-99.0/1.0-70.0
	218E2/HFC-263fb	1.0-99.0/1.0-99.0	20.0-90.0/10.0-80.0
25	C225eEαβ/HFC-143	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0
	C225eEαβ/HFC-236cb	1.0-99.0/1.0-99.0	1.0-80.0/20.0-99.0
	C225eE $\alpha\beta$ /HFC-236ea	1.0-99.0/1.0-99.0	30.0-99.0/1.0-70.0
	C225eEαβ/HFC-245cb	1.0-65.0/35.0-99.0	1.0-65.0/35.0-99.0
	$227caE\alpha\beta/HFC-32$	1.0-61.0/39.0-99.0	1.0-61.0/39.0-99.0
30	$227caE\alpha\beta/HFC-143$	42.0-99.0/1.0-58.0	42.0-95.0/5.0-58.0
• • •	$227caE\alpha\beta/HFC-245cb$	1.0-82.0/18.0-99.0	1.0-80.0/20.0-99.0
· · · · ·	227caEαβ/HFC-272ca	1.0-99.0/1.0-99.0	30.0-99.0/1.0-70.0
	$227caE\alpha\beta/HFC-281ea$	1.0-99.0/1.0-99.0	40.0-99.0/1.0-60.0
	$227 \text{caE} \alpha \beta / \text{HFC-} 281 \text{fa}$	1.0-99.0/1.0-99.0	40.0-99.0/1.0-60.0
35	$227caE\beta\gamma/HFC-32$	1.0-67.0/33.0-99.0	1.0-67.0/33.0-99.0
	$227$ caE $\beta\gamma$ /HFC-134	1.0-76.0/24.0-99.0	10.0-50.0/50.0-90.0
	$227caE\beta\gamma/HFC-134a$	1.0-67.0/33.0-99.0	1.0-67.0/33.0-99.0
	227caE $β\gamma$ /HFC-143	46.0-91.0/9.0-54.0	46-91.0/9.0-54.0
	$227caE\beta\gamma/HFC-152a$	1.0-78.0/22.0-99.0	10.0-78.0/22.0-90.0
40	227caE $\beta\gamma$ /HFC-161	1.0-72.0/28.0-99.0	10.0-72.0/28.0-90.0
	227caE $\beta\gamma$ /HFC-263fb	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0

5	227caEβγ/HFC-272ca	1.0-99.0/1.0-99.0	30.0-99.0/1.0-70.0
	227caEβγ/HFC-281ea	1.0-99.0/1.0-99.0	40.0-99.0/1.0-60.0
	227caEβγ/HFC-281fa	1.0-99.0/1.0-99.0	40.0-99.0/1.0-60.0
	227eaE/HFC-32	1.0-68.0/32.0-99.0	10.0-68.0/32.0-90.0
	227eaE/HFC-134	1.0-78.0/22.0-99.0	10.0-60.0/40.0-90.0
10	227eaE/HFC-134a	1.0-70.0/30.0-99.0	1.0-60.0/40.0-99.0
	227eaE/HFC-143	47.0-92.0/8.0-53.0	47.0-92.0/8.0-53.0
	227eaE/HFC-152a	1.0-80.0/20.0-99.0	10.0-80.0/20.0-90.0
	227eaE/HFC-161	1.0-73.0/27.0-99.0	20.0-73.0/27.0-80.0
	227eaE/HFC-263fb	1.0-99.0/1.0-99.0	30.0-99.0/1.0-70.0
15	227eaE/HFC-272ca	30.0-99.0/1.0-70.0	30.0-99.0/1.0-70.0
	227eaE/HFC-281ea	1.0-99.0/1.0-99.0	40.0-99.0/1.0-60.0
	227eaE/HFC-281fa	1.0-99.0/1.0-99.0	40.0-99.0/1.0-60.0
	C234fEαβ/HFC-245cb	1.0-58.0/42.0-99.0	1.0-58.0/42.0-99.0
	C234fEαβ/HFC-245eb	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0
20	C234fEαβ/HFC-356mff	1.0-99.0/1.0-99.0	20.0-80.0/20.0-80.0
	C234fEαβ/HFC-356mmz	1.0-99.0/1.0-99.0	20.0-80.0/20.0-80.0
•	C-234fE $\beta\gamma$ /HFC-245ca	1.0-99.0/1.0-99.0	10.0-80.0/20.0-90.0
	C-234fE $\beta\gamma$ /HFC-245cb	1.0-56.0/46.0-99.0	1.0-40.0/60.0-99.0
	C-234fE $\beta\gamma$ /HFC-245ea	1.0-99.0/1.0-99.0	10.0-89.0/21.0-90.0
25	C-234fE $\beta\gamma$ /HFC-254ca	1.0-99.0/1.0-99.0	10.0-99.0/1.0-90.0
	C-234fE $\beta\gamma$ /HFC-356mff	1.0-99.0/1.0-99.0	20.0-80.0/20.0-80.0
	C-234fE $\beta\gamma$ /HFC-356mmz	1.0-82.0/18.0-99.0	1.0-60.0/40.0-99.0
	236caE/HFC-143	1.0-60.0/40.0-99.0	10.0-60.0/40.0-90.0
	236caE/HFC-254ca	1.0-99.0/1.0-99.0	1.0-80.0/20.0-99.0
30	236caE/HFC-245ca	1.0-99.0/1.0-99.0	1.0-80.0/20.0-99.0
•	236eaE $\beta\gamma$ /HFC-143	1.0-66.0/34.0-99.0	10.0-66.0/34.0-90.0
	236eaEβγ/HFC-245ca	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0
	236eaEβγ/HFC-263ca	1.0-99.0/1.0-99.0	1.0-99.0/1.0-99.0
	$236eaE\beta\gamma/HFC-338mf$	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0
35	236eaE $\beta\gamma$ /HFC-356mff	1.0-99.0/1.0-99.0	20.0-99.0/1.0-80.0
	236eaEβγ/HFC-356mmz	1.0-99.0/1.0-99.0	1.0-80.0/20.0-99.0
	236faE/HFC-32	1.0-55.0/45.0-99.0	1.0-55.0/45.0-99.0
	236faE/HFC-143	28.0-84.0/16.0-72.0	30.0-84.0/16.0-70.0
	236faE/HFC-272ca	1.0-99.0/1.0-99.0	10.0-99.0/1.0-90.0
40	236faE/HFC-272fb	1.0-99.0/1.0-99.0	40.0-99.0/1.0-60.0
	236faE/HFC-281fa	1.0-99.0/1.0-99.0	1.0-99.0/1.0-99.0

15

20

25

5  $245 \text{fa} E \beta \gamma / \text{HFC-356mff}$  1.0-99.0/1.0-99.0 1.0-70.0/30.0-99.0

For purposes of this invention, "effective amount" is defined as the amount of each component of the inventive compositions which, when combined, results in the formation of an azeotropic or azeotrope-like composition. This definition includes the amounts of each component, which amounts may vary depending on the pressure applied to the composition so long as the azeotropic or azeotrope-like compositions continue to exist at the different pressures, but with possible different boiling points.

Therefore, effective amount includes the amounts, such as may be expressed in weight percentages, of each component of the compositions of the instant invention which form azeotropic or azeotrope-like compositions at temperatures or pressures other than as described herein.

For the purposes of this discussion, azeotropic or constant-boiling is intended to mean also essentially azeotropic or essentially-constant boiling. In other words, included within the meaning of these terms are not only the true azeotropes described above, but also other compositions containing the same components in different proportions, which are true azeotropes at other temperatures and pressures, as well as those equivalent compositions which are part of the same azeotropic system and are azeotrope-like in their properties. As is well recognized in this art, there is a range of compositions which contain the same components as the azeotrope, which will not only exhibit essentially equivalent properties for refrigeration and other applications, but which will also exhibit essentially equivalent properties to the true azeotropic composition in terms of constant boiling characteristics or tendency not to segregate or fractionate on boiling.

It is possible to characterize, in effect, a constant boiling admixture which may appear under many guises, depending upon the conditions chosen, by any of several criteria:

<sup>2</sup> The composition can be defined as an azeotrope of A, B, C (and D...) since the very term "azeotrope" is at once both definitive and limitative, and requires that effective amounts of A, B, C (and D...) for this unique composition of matter which is a constant boiling composition.

\* It is well known by those skilled in the art, that, at different pressures, the composition of a given azeotrope will vary at least to some degree, and changes in pressure will also change, at least to some degree, the boiling point temperature. Thus, an azeotrope of A, B, C (and D...) represents a unique type of relationship but with a

35

30

variable composition which depends on temperature and/or pressure. Therefore, compositional ranges, rather than fixed compositions, are often used to define azeotropes.

10

\* The composition can be defined as a particular weight percent relationship or mole percent relationship of A, B, C (and D...), while recognizing that such specific values point out only one particular relationship and that in actuality, a series of such relationships, represented by A, B, C (and D...) actually exist for a given azeotrope, varied by the influence of pressure.

15

\* An azeotrope of A, B, C (and D...) can be characterized by defining the compositions as an azeotrope characterized by a boiling point at a given pressure, thus giving identifying characteristics without unduly limiting the scope of the invention by a specific numerical composition, which is limited by and is only as accurate as the analytical equipment available.

20

The azeotrope or azeotrope-like compositions of the present invention can be prepared by any convenient method including mixing or combining the desired amounts. A preferred method is to weigh the desired component amounts and thereafter combine them in an appropriate container.

25

There is no universally accepted methodology for combining all relevant factors into a single global warming potential for greenhouse gas emissions. One way to define the greenhouse effect of a compound is to determine its potential to enhance global warming relative to a known standard. In the present invention, the halocarbon global warming potential (HGWP) of several fluoroethers and HFCs were determined using known estimating techniques.

30

35

HGWP is defined as the ratio of incremental radiative warming resulting from an emission of a gas, over the lifetime of the gas in the atmosphere, to the calculated warming that would result from a release of the same mass of reference gas CFC-11, which has an HGWP of 1.0. The calculation of HGWP is discussed in Fisher et. al., Model Calculations on the Relative Effects of CFCs and their Replacements on Global Warming, Nature, Volume 344, pp. 513-516 (1990), the text of which is incorporated herein by reference.

It has been discovered that the HGWP of an HFC can be lowered by adding to the HFC a fluoroether having a lower HGWP than the HGWP of the HFC such that the combination of the HFC and the fluoroether has an HGWP

lower than the HGWP of the HFC. Therefore, the present invention relates to a composition of a first component that includes a hydrofluorocarbon and a second

15

20

25

component that includes a fluoroether that has an HGWP less than the HGWP of the first component, such that the HGWP of the composition is less than the HGWP of the first component.

The scope of this invention includes a single fluoroether compound added to a single HFC, as well as a single fluoroether added to mixtures of two or more HFCs. Further, the invention includes mixtures of one or more fluoroethers added to a single HFC, as well as mixtures of one or more fluoroethers added to mixtures of two or more HFCs.

The HGWP of a composition of components A and B is equal to [fractional composition of A] x [HGWP of A] + [fractional composition of B] x [HGWP of B]. The HGWP of a composition of more than two components is determined in the same way, that is, by multiplying the fractional composition of a component by its HGWP, and then adding together the fractional HGWPs of all the components.

Specific examples illustrating the invention are given below. Unless otherwise stated therein, all percentages are by weight. It is to be understood that these examples are merely illustrative and in no way are to be interpreted as limiting the scope of the invention. All values given in the Examples are +/- 5 percent.

#### EXAMPLE 1

Phase Study

A phase study on the following compositions, wherein the composition is varied and the vapor pressures are measured, at a constant temperature of 25°C, shows that the following compositions are azeotropic.

30

#### TABLE 2

			Vapor Press.
	Weight % Fluoroether	Weight % HFC	psia (kPa)
	75.2 wt.% 116E	24.8 wt.% HFC-32	490.5 (3382)
35	58.6 wt.% 116E	41.4 wt.% HFC-41	575.6 (3969)
•	86.0 wt.% 116E	14.0 wt.% HFC-125	295.6 (2038)
	90.2 wt.% 116E	9.8 wt.% HFC-134	302.7 (2087)
	90.0 wt.% 116E	10.0 wt.% HFC-134a	299.5 (2065)
	94.9 wt.% 116E	5.1 wt.% HFC-143	305.9 (2109)
40	94.8 wt.% 116E	5.2 wt.% HFC-143a	293.1 (2021)
	92.1 wt.% 116E	7.9 wt.% HFC-152a	305.4 (2106)
٠	87.3 wt.% 116E	12.7 wt.% HFC-161	344.3 (2374)

5	86.5 wt.% 125E	13.5 wt.% HFC-134	130.7 (901)
J	92.0 wt% 125E	8.0 wt% HFC-143	132.0 (910)
	84.4 wt% 125E	15.6 wt% HFC-152a	134.1 (925)
	66.5 wt% 125E	33.5 wt% HFC-161	171.1 (1179)
	00.5 W (70 1252	00.0 11170 12 0 101	
10	37.9 wt% 134E	62.1 wt% HFC-143	34.0 (235)
10	13.6 wt% 134E	86.4 wt% HFC-227ca	65.9 (454)
	7.3 wt% 134E	92.7 wt.% HFC-227ea	67.2 (463)
•	78.0 wt% 134E	22.0 wt% HFC-236ca	63.8 (440)
	36.3 wt% 134E	63.7 wt% HFC-236cb	36.3 (250)
10		47.2 wt% HFC-236ea	33.3 (229)
15	52.8 wt% 134E	85.8 wt.% HFC-236fa	39.8 (274)
	14.2 wt.% 134E		80.0 (551)
	28.5 wt% 134E	71.5 wt% HFC-245cb	34.9 (241)
	29.7 wt% 134E	70.3 wt% HFC-254cb	
	28.6 wt.% 134E	71.4 wt.% HFC-254eb	35.5 (245)
20	97.1 wt.% 134E	2.9 wt.% HFC-356mff	30.4 (210)
	65.5 wt% 134E	34.5 wt% HFC-338mf	33.2 (229)
	11.5 wt.% 134aE	88.5 wt.% HFC-32	249.2 (1718)
	42.6 wt.% 134aE	57.4 wt.% HFC-134	78.3 (540)
25	98.1 wt.% 134aE	1.9 wt.% HFC-143	73.9 (510)
23	19.1 wt.% 134aE	80.9 wt.% HFC-152a	86.0 (593)
	65.5 wt% 134aE	34.5 wt% HFC-227ca	76.3 (526)
	65.4 wt.% 134aE	34.6 wt.% HFC-227ea	75.4 (520)
	57.7 wt.% 134aE	42.3 wt.% HFC-245cb	91.7 (632)
30	37.7 Wt.70 134aL	12.5 Willyo 121 O 2 1500	, and (4)
30	6.2 wt.% 143aE	93.8 wt.% HFC-32	247.4 (1706)
	92.4 wt.% 143aE	7.6 wt. % HFC-134	127.6 (880)
	8.7 wt.% 143aE	91.3 wt.% HFC-143a	182.2 (125 <del>6</del> )
•	48.6 wt.% 143aE	51.4 wt.% HFC-152a	87.3 (602)
25	71.5 wt% 143aE	28.5 wt% HFC-227ca	85.9 (592)
. 35		24.4 wt.% HFC-227ea	84.8 (585)
	75.6 wt.% 143aE	40.4 wt.% HFC-245cb	102.8 (709)
	59.6 wt.% 143aE	40.4 WI.70 III C-243CD	102.0 (107)
	79.8 wt.% C216E	20.2 wt.% HFC-134	104.4 (720)
40	61.7 wt.% C216E	38.3 wt.% HFC-134a	108.0 (744)
	91.9 wt.% C216E	8.1 wt.% HFC-143	103.5 (714)
	77.6 wt.% C216E	22.4 wt.% HFC-152a	109.1 (752)
•	58.8 wt.% C216E	41.2 wt.% HFC-161	148.3 (1022)
	95.1 wt.% C216E	4.9 wt.% HFC-245cb	100.6 (693)
45	)3.1 Wi. / 0 C21C2	ways 255 5 5	
	36.0 wt.% C216E2	64.0 wt.% HFC-32	272.4 (1878)
	60.5 wt.% C216E2	39.5 wt.% HFC-134	88.6 (611)
	20.6 wt.% C216E2	79.4 wt.% HFC-134a	99.0 (683)
	87.1 wt.% C216E2	12.9 wt.% HFC-143	82.9 (572)
<b>CO</b>		39.5 wt.% HFC-152a	95.6 (659)
50	60.5 wt.% C216E2	54.3 wt.% HFC-161	138.3 (954)
	45.7 wt.% C216E2	34.3 WI.70 III C-101	130.3 (334)

5	74.7 wt.% C216E2	25.3 wt.% HFC-245cb	81.3 (561)
	63.3 wt. %218E	36.7 wt. % HFC-134	116.6 (804)
	53.0 wt.% 218E	47.J wt.% HFC-134a	122.3 (843)
	85.3 wt.% 218E	14.7 wt.% HFC-143	103.7 (715)
. 10	68.2 wt.% 218E	31.8 wt.% HFC-152a	•
10	62.6 wt.% 218E		124.0 (855)
		37.4 wt.% HFC-161	170.9 (1178)
•	96.3 wt.% 218E	3.7 wt.% HFC-263fb	84.0 (579)
	46.1 wt.% 218E2	53.9 wt.% HFC-134	89.6 (617)
15	24.7 wt.% 218E2	75.3 wt.% HFC-134a	101.1 (697)
•	78.3 wt.% 218E2	21.7 wt.% HFC-143	72.6 (501)
	51.0 wt.% 218E2	49.0 wt.% HFC-152a	98.1 (676)
	46.4 wt.% 218E2	53.6 wt.% HFC-161	145.1 (1000)
	89.8 wt.% 218E2	10.2 wt.% HFC-236fa	52.6 (363)
20	60.5 wt.% 218E2	39.5 wt.% HFC-263fb	57.9 (399)
	55.9 wt.% C225eEαβ	44.1 wt.% HFC-143	38.0 (2626)
	16.7 wt.% C225eEαβ	83.3 wt.% HFC-236cb	33.7 (232)
·	91.5 wt.% C225eEαβ	8.5 wt.% HFC-236ea	
25	22.4 wt.% C225eEαβ	77.6 wt.% HFC-245cb	31.1 (214)
25	17.9 wt.% 227ca $E\alpha\beta$	82.1 wt.% HFC-32	70.1 (483)
	70.9 wt.% 227caEαβ	29.1 wt.% HFC-143	253.4 (1747)
	$8.1 \text{ wt.} \% 227 \text{ca} \text{E} \alpha \beta$	91.9 wt.% HFC-245cb	53.7 (370)
	94.3 wt.% 227caEαβ	5.7 wt.% HFC-272ca	67.4 (465)
30	31.5 wt. % 227 caE $\alpha\beta$	68.5 wt.% HFC-281ea	41.5 (286)
30	84.3 wt.% 227caE $\alpha\beta$		47.3 (326)
	64.5 W1.70 221 Carαρ	15.7 wt.% HFC-281fa	42.5 (293)
•	28.4 wt.% 227caE $\beta\gamma$	71.6 wt.% HFC-32	269.7 (1859)
	34.8 wt.% 227caE $\beta\gamma$	65.2 wt.% HFC-134	82.7 (570)
35	1.9 wt.% 227caE $\beta\gamma$	98.1 wt.% HFC-134a	98.3 (678)
:	73.8 wt.% 227caE $\beta\gamma$	26.2 wt.% HFC-143	66.2 (456)
	38.3 wt.% 227caE $\beta\gamma$	61.7 wt.% HFC-152a	91.4 (630)
	34.4 wt.% 227caEβγ	65.6 wt.% HFC-161	137.5 (948)
	32.9 wt.% 227caE $\beta\gamma$	67.1 wt.% HFC-263fb	54.6 (376)
40	89.0 wt.% 227caE $\beta\gamma$	11.0 wt.% HFC-272ca	49.6 (342)
	73.1 wt.% 227caΕβγ	26.9 wt.% HFC-281ea	54.0 (372)
	85.9 wt.% 227caE $\beta\gamma$	14.1 wt.% HFC-281fa	51.1 (352)
	30.0 wt.% 227eaE	70.0 wt.% HFC-32	272.2 (1877)
45	38.2 wt.% 227eaE	61.8 wt. % HFC-134	84.7 (584)
	9.3 wt.% 227eaE	90.7 wt.% HFC-134a	98.6 (680)
•	74.9 wt.% 227eaE	25.1 wt.% HFC-143	68.9 (475)
•	42.1 wt.% 227eaE	57.9 wt.% HFC-152a	93.3 (643)
•	37.5 wt.% 227eaE	62.5 wt.% HFC-161	, ,
50	49.3 wt.% 227eaE	50.7 wt.% HFC-263fb	139.5 (962) 55.7 (384)
50	90.7 wt.% 227eaE	9.3 wt.% HFC-272ca	55.7 (384) 52.1 (359)
	,		J4.1 (JJ9)
	·		
·. ···			

_	76.8 wt.% 227eaE	23.2 wt.% HFC-281ea	56.0 (386)
5	87.6 wt.% 227eaE	12.4 wt.% HFC-281fa	53.4 (368)
	87.0 Wt. 70 ZZ / Cal	22.1 W 6.70 2 22 C 20 2 2 2	•
	13.5 wt.% C-234fEαβ	86.5 wt.% HFC-245cb	69.9 (482)
	49.1 wt.% C-234fEαβ	50.9 wt.% HFC-245eb	17.6 (121)
10	59.0 wt.% C-234fEαβ	41.0 wt.% HFC-356mff	18.8 (130)
10	50.1 wt.% C-234fEαβ	49.9 wt.% HFC-356mmz	20.1 (139)
	30.1 Wt.70 C-2341EMP	1717 11170 121 0 00 00	• •
	33.6 wt.% C-234fEβγ	66.4 wt.% HFC-245ca	14.5 (100)
	10.2 wt.% C-234fEβγ	89.8 wt.% HFC-245cb	69.1 (476)
15	36.0 wt.% C-234fEβγ	64.0 wt.% HFC-245ea	14.5 (100)
13	36.0 wt.% C-234fEβγ	64.0 wt.% HFC-254ca	13.8 (95)
	43.1 wt.% C-234fEβγ	56.9 wt.% HFC-356mff	17.1 (118)
	35.8 wt.% C-234fEβγ	64.2 wt.% HFC-356mmz	18.6 (128)
	55.6 Wayo 6 20 1247		
20	12.0 wt.% 236caE	88.0 wt.% HFC-143	33.4 (230)
20	17.6 wt.% 236caE	82.4 wt.% HFC-254ca	13.8 (95)
	17.0 11.70 2550		
	25.9 wt.% 236eaE $\beta\gamma$	74.1 wt.% HFC-143	34.7(239)
	69.1 wt.% 236eaE $\beta\gamma$	30.9 wt.% HFC-245ca	16.1 (111)
25	4.1 wt.% 236eaEβγ	95.9 wt.% HFC-263ca	18.3 (126)
	92.6 wt.% 236eaΕβγ	7.49 wt.% HFC-338mf	18.9 (130)
	96.9 wt.% 236ea $E\beta\gamma$	3.1 wt.% HFC-356mff	15.7 (108)
	15.1 wt.% 236ea $E\beta\gamma$	84.9 wt.% HFC-356mmz	16.7 (115)
30	8.5 wt.% 236faE	91.5 wt.% HFC-32	248.6 (1714)
	56.9 wt.% 236faE	43.1 wt.% HFC-143	45.1 (311)
	27.8 wt.% 236faE	72.2 wt.% HFC-272ca	34.8 (240)
	82.3 wt.% 236faE	17.7 wt.% HFC-272fb	30.2 (208)
	9.3 wt.% 236faE	90.7 wt.% HFC-281fa	37.7 (260)
35	· .		
- <del>-</del>	4.4 wt.% 245faΕβγ	95.6 wt.% HFC-356mff	14.9 (103)
•			

#### **EXAMPLE 2**

## Impact of Vapor Leakage on Vapor Pressure at 25°C

A vessel is charged with an initial composition at 25°C, and the vapor pressure of the composition is measured. The composition is allowed to leak from the vessel, while the temperature is held constant at 25°C, until 50 weight percent of the initial composition is removed, at which time the vapor pressure of the composition remaining in the vessel is measured. The results are summarized below.

15

#### TABLE 3

	Refrigerant	0 wt% evaporated	50 wt% evaporated	% change in
	Composition	psia (kPa)	psia (kPa)	vapor pressure
20	116E/HFC-32			<u></u>
	75.2/24.8	490.6(3385)	490.6(3385)	0.0
	89/11	484.3(3341)	434.4(2297)	10.3
	88/12	485.8(3352)	451.4(3114)	7.1
	70/30	490.4(3383)	490.0(3381)	0.6
25	60/40	489.6(3378)	488.0(3367)	0.3
	50/50	488.8(3372)	486.1(3354)	0.6
	80/20	490.2(3382)	489.1(3374)	0.2
	116E/HFC-41			
30	58.6/41.4	575.6(3971)	575.6(3971)	0.0
	70/30	572.4(3949)	566.7(3910)	1.0
	85/15	540.4(3728)	483.1(3333)	10.6
	84/16	544.9(3759)	493.7(3406)	9.3
	40/60	571.3(3942)	558.5(3853)	2.2
35	30/70	565.7(3903)	515.9(3559)	8.8
	28/72	564.1(3892)	505.8(3490)	10.3
	29/71	- 564.9(3897)	510.7(3523)	9.6
• •	5/95	512.9(3539)	477.9(3297)	6.6
40	116E/HFC-125			
•	86.0/14.0	295.6(2039)	295.6(2039)	0.0
	99/1	292.7(2019)	292.6(2018)	0.0
•	70/30	292.2(2016)	291.1(2008)	0.4
	60/40	297.3(2051)	284.0(1959)	4.5
45	50/50	280.6(1936)	273.9(1889)	2.4
	40/60	272.0(1876)	260.5(1797)	4.4
	30/70	261.0(1800)	244.0(1683)	6.5

				5.0
5	10/90	227.3(1568)	209.5(1445)	7.2
	1/99	202.5(1397)	199.8(1378)	1.3
	116E/HFC-134			0.2
	99.0/1.0	294.8 (2033)	294.0 (2027)	0.3
10	90.2/9.8	302.7 (2087)	302.7 (2087)	0.0
	70.0/30.0	293.5 (2024)	285.2 (1967)	2.8
	52.0/48.0	283.9 (1957)	258.0 (1779)	9.1
	•			
	116E/HFC-134a			
15	90.0/10.0	299.5(2066)	299.5(2066)	0.0
	99/1	293.8(2027)	293.5(2025)	0.0
	52/48	276.8(1909)	248.6(1715)	10.2
	53/47	277.5(1914)	251.8(1737)	9.3
	60/40	282.6(1949)	267.0(1842)	5.5
20	70/30	289.7(1998)	281.6(1943)	2.8
	80/20	296.2(2043)	293.7(2026)	8.0
	•			
	116E/HFC-143			
	94.9/5.1	305.9(2110)	305.9(2110)	0.0
25	99/1	300.2(2071)	295.6(2039)	1.5
	80/20	299.2(2064)	295.9(2041)	1.1
	70/30	293.5(2025)	285.2(1967)	2.8
	65/35	290.6(2005)	280.2(1933)	3.5
	61/39	300.6(2074)	298.3(2058)	0.8
30	60/40	300.6(2074)	283.6(1956)	5.6
	116E/HFC-143a		200 4 (2022)	0.0
	94.8/5.2	293.1(2022)	293.1(2022)	0.0
	70/30	281.6(1943)	277.4(1914)	1.5
35	60/40	273.6(1887)	265.0(1828)	3.1
	50/50	264.3(1823)	250.0(1725)	5.4
	40/60	253.7(1750)	232.3(1602)	8.4
	10/90	206.8(1426)	186.0(1283)	10.1
	1/99	183.6(1266)	180.9(1248)	1.5
40	99/1	292.5(2018)	292.5(2018)	0.0
•				
	116E/HFC-152a		205 5/2100\	0.0
	92.1/7.9	305.5(2108)	305.5(2108)	0.0
	99/1	296.4(2045)	295.1(2036)	0.4
45	•	292.3(2016)	280.4(1934)	4.1
	60/40	286.6(1977)	259.3(1789)	9.5
	11 <i>CD /</i> ITEO 161			
	116E/HFC-161	244 4(2276)	244.4(2376)	0.0
	87.3/12.7	344.4(2376)	297.5(2052)	3.2
50	•	307.4(2121)		2.3
	70/30	337.9(2331)	330.2(2278)	2.3

5	60/40	334.1(2305)	308.4(2128)	7.7
-	95/5	335.6(2315)	324.8(2241)	3.2
		,	,	
	125E/HFC-32			
	1.0/99.0	246.2 (1697)	245.9 (1695)	0.1
10	10.0/90.0	241.2 (1663)	238.8 (1646)	1.0
	20.0/80.0	235.0 (1620)	230.0 (1586)	2.1
	30.0/70.0	227.8 (1571)	220.1 (1518)	3.4
	40.0/60.0	219.4 (1513)	209.3 (1443)	4.6
	50.0/50.0	209.5 (1444)	197.4 (1361)	5.8
15	60.0/40.0	197.9 (1364)	184.7 (1273)	6.7
	70.0/30.0	184.4 (1271)	171.2 (1180)	7.2
	80.0/20.0	168.5 (1162)	157.2 (1084)	6.7
	90.0/10.0	149.9 (1034)	142.8 (985)	4.7
	99.0/1.0	130.8 (902)	129.9 (896)	0.7
20	•			
	• .			
	125E/HFC-134			
	37.0/63.0	116.3 (802)	105.1 (725)	· <b>9.6</b>
25	70.0/30.0	128.6 (887)	127.6 (880)	0.8
	86.5/13.5	130.7 (901)	130.7 (901)	0.0
	99.0/1.0	128.9 (889)	128.8 (888)	0.1
	125E/HFC-134a			
30	1.0/99.0	98.5 (679)	98.5 (679)	0.0
	10.0/90.0	100.9 (696)	100.4 (692)	0.5
	20.0/80.0	103.5 (714)	102.6 (707)	0.9
	30.0/70.0	106.2 (732)	105.0 (724)	1.1
	40.0/60.0	108.9 (751)	107.6 (742)	1.2
35	50.0/50.0	111.8 (771)	110.4 (761)	1.3
	60.0/40.0	114.8 (792)	113.4 (782)	1.2
	70.0/30.0	117.9 (813)	116.7 (805)	1.0
	80.0/20.0	121.3 (836)	120.3 (829)	0.8
	90.0/10.0	124.8 (860)	124.2 (856)	0.5
- 40	99.0/1.0	128.1 (883)	128.1 (883)	0.0
•	125E/HFC-143			
•	57.0/43.0	123.5 (852)	112.1 (773)	9.2
2	60.0/40.0	124.2 (856)	115.9 (799)	6.7
45		126.9 (875)	122.4 (844)	3.6
	92.0/ 8.0	132.0 (910)	132.0 (190)	0.0
	99.0/ 1.0	129.5 (893)	129.3 (892)	0.2
	•			

WO 93/24586 PCT/US93/04614

. 5	125E/HFC-152a			
	39.0/61.0	120.3 (829)	108.6 (747)	9.7
	50.0/50.0	125.3 (864)	118.5 (817)	5.4
	60.0/40.0	129.0 (889)	125.6 (866)	2.7
	84.4/15.6	134.1 (925)	134.1 (925)	0.0
10	•	129.4 (892)	129.2 (891)	0.2
10	99.0/ 1.0	129.4 (092)	123.2 (031)	0.2
	125E/HFC-161			
	29.0/71.0	161.6 (1114)	145.8 (1006)	9.8
•	50.0/50.0	169.0 (1165)	166.3 (1146)	1.6
15	66.5/33.5	171.1 (1179)	171.1 (1179)	0.0
	70.0/30.0	170.9 (1179)	170.8 (1177)	0.1
	99.0/ 1.0	133.2 (919)	130.5 (900)	2.1
	134E/HFC-143			
20	1.0/99.0	33.1 (228)	33.1 (228)	0.0
	37.9/62.1	34.0 (235)	34.0 (235)	0.0
	50.0/50.0	33.9 (234)	33.9 (234)	0.0
	70.0/30.0	33.2 (229)	33.1 (228)	0.4
	99.0/1.0	30.6 (211)	30.5 (210)	0.1
25	77.0/ 1.0	20.0 (211)	30.5 (210)	<b>0.1</b>
23	134E/HFC-227ca	L		
	1.0/99.0	64.2 (443)	64.1 (442)	0.1
	13.6/86.4	65.9 (454)	65.9 (454)	0.0
•	30.0/70.0	64.6 (445)	63.5 (438)	1.6
30	40.0/60.0	63.0 (434)	60.4 (416)	4.1
	51.0/49.0	60.9 (420)	55.0 (379)	9.6
	- '	` ,	,	
	134E/HFC-227e	a		
•	7.3/92.7	67.2 (463)	67.2 (463)	0.0
35	1.0/99.0	66.8 (461)	66.8 (461)	0.0
	40.0/60.0	62.6 (432)	59.3 (409)	5.3
-	50.0/50.0	60.3 (416)	54.0 (372)	10.4
	49.0/51.0	60.6 (418)	54.6 (376)	9.9
40	134E/HFC-236c	a		
•• • •	78.0/22.0	29.5(203)	29.5(203)	0.0
	90/10	29.4(202)	29.4(202)	0.0
	99/1	29.2(201)	29.2(201)	0.0
•	70/30	29.4(202)	29.4(202)	<b>0.0</b> .
45	60/40	29.3(202)	29.2(201)	0.3
	50/50	29.0(200)	29.0(200)	0.0
•	30/70	28.0(193)	27.7(191)	1.1
	10/90	26.2(180)	26.0(179)	0.8
	1/99	25.1(173)	25.0(172)	0.4
50	•	()		2

	5	134E/HFC-236cb			
	3	1.0/99.0	33.8 (233)	33.8 (233)	0.0
		36.3/63.7	36.3 (250)	• •	0.0
		40.0/60.0		36.3 (250)	
		•	36.3 (250)	36.3 (250)	0.0
		70.0/30.0	34.8 (240)	34.3 (236)	1.6
1	10	99.0/1.0	30.6 (211)	30.5 (210)	0.3
		134E/HFC-236ea		·	
		1.0/99.0	28.9 (199)	28.9 (199)	0.0
		30.0/70.0	32.6 (225)	32.4 (223)	0.7
1	l5	52.8/47.2	33.3 (229)	33.3 (229)	0.0
		70.0/30.0	32.9 (227)	32.8 (226)	0.3
		99.0/1.0	30.6 (211)	30.5 (210)	0.3
	•	134E/HFC-236fa			
	20	14.2/85.8	39.8 (274)	20.9 (274)	
4	20	1.0/99.0	•	39.8 (274)	0.0
		•	39.4 (272)	39.4 (272)	0.0
		40.0/60.0	38.8 (268) 37.1 (256)	38.6 (266) 36.3 (250)	0.5
		60.0/40.0	37.1 (256)	36.3 (250)	2.2
	25	80.0/20.0	34.4 (237)	33.3 (230)	3.2
4	25	99.0/ 1.0	30.7 (212)	30.5 (210)	0.7
		134E/HFC-245cb			
		1.0/99.0	69.0 (476)	67.8 (467)	1.7
		28.5/71.5	80.0 (551)	80.0 (551)	0.0
	30	40.0/60.0	79.6 (549)	79.0 (545)	0.7
		50.0/50.0	78.9 (544)	77.4 (534)	1.9
		62.0/38.0	77.9 (537)	71.4 (492)	8.4
		134E/HFC-254cb		·	
. :	35	1.0/99.0	34.2 (236)	34.2 (236)	0.0
,		29.7/70.3	34.9 (241)	34.9 (241)	0.0
		40.0/60.0	34.8 (240)	34.8 (240)	0.0
	٠.	70.0/30.0	33.6 (232)	33.4 (230)	0.7
		99.0/1.0	30.6 (211)	30.5 (210)	0.7
	40	<i>55.</i> 107 2.10	0010 (211)	30.3 (210)	0.1
		134E/HFC-254eb		·	
		28.6/71.4	35.5 (245)	35.5 (245)	0.0
		15.0/85.0	35.3 (243)	35.3 (243)	0.0
		1.0/99.0	34.8 (240)	34.8 (240)	0.0
· ·	45 -	60.0/40.0	34.7 (239)	34.5 (238)	0.6
•		80.0/20.0	33.1 (228)	32.7 (225)	1.2
		99.0/ 1.0	30.6 (211)	30.5 (210)	0.3
		134E/HFC-338mf			
	50	27.0/73.0	30.5 (210)	27.6 (190)	0.4
	30	40.0/60.0	32.2 (222)	31.1 (214)	9.4 3.4
	_	•	()	()	
	•				
		·	•		•

5	65.5/34.5	33.2 (229)	33.2 (229)	0.0
•	80.0/20.0	32.9 (227)	32.6 (225)	0.8
	99.0/1.0	30.6 (211)	30.5 (210)	0.4
	134E/HFC-356	mff		
10	97.1/2.9	30.4 (210)	30.4 (210)	. 0.0
10	99.0/1.0	30.4 (210)	30.4 (210)	0.0
	60.0/40.0	28.7 (198)	27.8 (192)	3.1
	40.0/60.0	26.4 (182)	23.9 (165)	9.5
	39.0/61.0	26.3 (181)	23.6 (163)	10.3
15	37.0/01.0	2010 (40-5)		
	134aE/HFC-32	2.		
	11.5/88.5	249.1(1718)	249.1(1718)	0.0
	1/99	247.2(1705)	247.1(1705)	0.0
	20/80	248.3(1713)	247.7(1709)	0.2
20	30/70	245.8(1695)	243.0(1676)	1.1
	56/44	231.1(1594)	207.6(1432)	10.2
	55/45	232.0(1600)	210.0(1449)	9.5
	40/60	241.9(1669)	234.5(1618)	3.0
25	134aE/HFC-1	34		
23	99.0/1.0	74.0 (510)	74.0 (510)	0
	60.0/40.0	77.9 (537)	77.9 (537)	0
	42.6/57.4	78.3 (540)	78.3 (540)	0
	20.0/80.0	77.7 (536)	77.7 (536)	0
30	1.0/99.0	76.2 (525)	76.2 (525)	0
	134aE/HFC-1	1/13		
	•	73.8 (509)	73.8 (509)	0
	99.0/1.0 98.1/1.9	73.9 (510)	73.9 (510)	0
35	52.0/48.0	65.0 (448)	58.7 (405)	9.7
		150-		
	134aE/HFC-		06 1/504\	0.0
: ::···	19.1/80.9	86.1(594)	86.1(594)	0.0
	10/90	86.0(593)	86.0(593)	0.0
40	1/99	85.8(592)	85.8(592)	
	30/70	86.0(593)	86.0(593)	0.0
	50/50	85.0(586)	84.9(585)	0.1
	70/30	82.7(570)	82.2(567)	0.6
•	80/20	80.7(556)	80.0(552)	0.9
45	99/1	74.3(512)	74.2(512)	0.1
	134aE/HFC	-227ca		
	65.5/34.5	76.2(525)	76.2(525)	0.0
	80/20	75.8(523)	75.8(523)	0.0
50	•	75.0(517)	74.9(516)	0.1
	99/1	74.0(510)	73.9(510)	0.1
	•			

		₩.		
5	50/50	75.7(522)	75.6(521)	0.1
	40/60	74.8(516)	74.4(513)	0.5
	30/70	73.4(506)	72.7(501)	1.0
	20/90	71.2(491)	70.2(484)	1.4
	1/99	64.2(443)	64.1(442)	0.3
10	,		011(442)	0.5
	134aE/HFC-227ea			
•	65.4/34.6	75.5(521)	75.5(521)	0.0
	80/20	75.2(518)	75.1(518)	0.0
	90/10	74.6(514)	74.6(514)	0.1
15	99/1	73.9(509)	73.9(509)	
	50/50	75.1(518)	75.0(517)	0.0
	30/70	73.4(506)	73.0(517)	0.1
	10/90	69.6(480)	69.2(4 <b>7</b> 7)	0.5
	1/99	67.0(462)	67.0(462)	0.6
20	- <b>/</b>	57.0(10 <i>2</i> )	07.0(402)	0.0
<del> v</del>	134aE/HFC-245cb	1		
	57.7/42.3	91.6(632)	91.6(632)	ΛΛ
	70/30	90.9(627)	90.1(621)	0.0
	80/20	89.0(614)	85.9(592)	0.9
25	92/8	83.3(574)	77.4(534)	3.5
	99/1	75.5(521)	74.1(511)	7.1
•	30/70	87.6(604)	84.3(581)	1.8
	20/80	83.4(575)	78.4(541)	3.8
	10.90	76.9(530)	i i i i i i i i i i i i i i i i i i	6
30	1/99	67.7(467)	72.3(498) 67.8(467)	6
		• • • • • • • • • • • • • • • • • • • •	07.0(407)	0.1
	143aE/HFC-32			
	6.2/98.8	247.4(1707)	247.4(1707)	Λ Λ
•	1/99	246.9(1703)	247.4(1707) 246.9(1703)	0.0
. 35	20/80	245.1(1691)	243.9(1682)	0.0 0.5
	30/70	241.4(1665)	237.3(1637)	
	40/60	236.1(1629)	226.9(1565)	1.7 3.0
	50/50	228.8(1578)	210.9(1455)	3.9
	55/45	224(1545)	200.1(1380)	7.8 10.6
40	54/46	225(1552)	202(1393)	10.6
			202(1333)	10.0
	143aE/HFC-134	•		
	99.0/1.0	127.5 (879)	127.5 (879)	0
	92.4/7.6	127.6 (880)	127.6 (880)	0
45	30.0/70.0	123.4 (851)	123.1 (849)	
,	1.0/99.0	118.3 (815)	118.2 (815)	0.2
•	•		110.2 (013)	0.
	143aE/HFC-143a			
	8.7/91.3	182.1(1256)	182.1(1256)	0.0
50	1/99	181.0(1248)	181.0(1248)	0.0
<del>-</del> -	20/80	180.5(1245)	179.7(1239)	0.0
	,	100.5(1275)	113.1(1239)	0.4
		. •		
	· ·	•		

5	40/50	172.4(1189)	165.0(1138)	4.3
3	55/45	161.8(1116)	144.7(998)	10.6
	54/46	162.7(1122)	146.3(1009)	10.1
	53/47	163.5(1128)	147.9(1020)	9.5
	ודןכנ	100.0(11-0)		
10	143aE/HFC	-152a		
10	48.6/51.4	87.4(603)	87.4(603)	0.0
	40/60	87.3(602)	87.3(602)	0.0
	30/70	87.2(601)	87.1(601)	0.1
	10/90	86.3(595)	86.3(595)	0.0
15	1/99	85.8(592)	85.8(592)	0.0
	60/40	87.2(601)	87.2(601)	0.0
	70/30	86.9(599)	86.8(598)	0.1
	90/10	85.2(587)	85.2(587)	0.0
	99/1	84.0(579)	84.0(579)	0.0
20	•			
	143aE/HF0	C-227ca	25.0(500)	0.0
	71.5/28.5	85.9(592)	85.9(592)	0.0
	80/20	85.7(591)	85.7(591)	0.0
	99/1	84.0(579)	84.0(579)	0.0
25	60/40	85.6(590)	85.4(589)	0.2
	40/60	83.2(574)	82.1(566)	1.3
	30/70	80.8(557)	78.9(544)	2.3 3.5
	20/80	77.2(532)	74.5(514)	0.6
	1/99	64.7(446)	64.3(443)	0.0
30	4 40 TO /TTT	20.007		
	143aE/HF	C-227ea 84.9(585)	84.9(585)	0.0
,	75.6/24.4	84.5(583)	84.5(583)	0.0
	90/10	83.9(578)	83.9(578)	0.0
0.5	99/1	84.8(585)	84.8(585)	0.0
35	70/30	84.4(582)	84.3(581)	0.1
	60/40	83.6(576)	83.2(574)	0.5
	50/50 30/70	80.1(552)	78.9(544)	1.5
	30/70	72.8(502)	71.3(492)	2.1
. 40	10/90	67.3(464)	67.1(463)	0.3
40	1/99	07.5(404)	• • • • • • • • • • • • • • • • • • • •	•
	143aE/H	FC-245cb		
	59.6/40.4		102.8(709)	0.0
	70/30	102.2(705)	101.5(700)	0.7
45		100.5(693)	96.9(668)	3.6
7⊷	99/1	85.8(592)	84.0(579)	2.1
	40/60	100.7(694)	98.2(677)	2.5
	30/70	97.4(672)	91.6(632)	6.0
•	20/80	91.8(633)	82.7(570)	9.9
5	0 19/81	91.0(627)	81.7(563)	10.2
J	0 17/01	()	•	

	5	C-216E/HFC-13	84		•	•
	J	1.0/99.0	76.9 (530)	76.3 (526)	0.8	
				98.0 (676)	2.1	
		50.0/50.0	100.1 (690)		0	
		79.8/20.2	104.4 (720)	104.4 (720)		
		99.0/1.0	100.8 (695)	100.7 (694)	0.1	
	10		·	•		
		C216E/HFC-13	4a			
		61.7/38.3	108.0(745)	108.0(745)	0.0	
		80/20	106.6(735)	106.4(734)	0.2	•
		90/10	104.4(720)	105.0(724)	0.6	
	15	99/1	100.8(695)	100.7(694)	0.1	
	1.5	50/50	107.6(742)	107.4(741)	0.1	
		•	105.2(725)	104.6(721)	0.2	
		30/70	101.0(696)	100.4(692)	0.5	
		10/90	* *	· ·	0.1	
		1/99	98.6(680)	98.5(679)	0.1	
	20		10			
		C216E/HFC-14		101.0 ((0))	0.0	
		99.0/1.0	101.2 (698)	101.0 (696)	0.2	
		91.9/8.1	103.5 (714)	103.5 (714)	0	
		61.0/39.0	96.6 (666)	87.3 (602)	9.6	
	25					
		C216E/HFC-1:	52a			
		77.6/22.4	109.1(752)	109.1(752)	0.0	
	-	90/10	107.2(739)	106.7(736)	0.5	
		99/1	101.4(699)	101.1(697)	0.3	
	30	70/30	108.7(759)	108.5(748)	0.2	
		60/40	107.2( <b>7</b> 39)	106.2(732)	0.9	
		30/70	99.2(684)	94.8(654)	4.4	
		20/80	95.4(658)	91.0(627)	4.6	
•		10/90	91.0(627)	87.9(606)	3.4	
	35	1/99	86.3(595)	86.0(593)	0.3	
•	. 33	1/99	00.5(555)	00.0(373)	0.0	
		C216E/HFC-1	61	·		
. •		58.8/41.2	148.3(1023)	148.3(1023)	0.0	
.,	•	•	147.2(1015)	146.3(1009)	0.6	
•	40	70/30		139.1(959)	2.9	
	40	•	143.3(988)	= "		
	•	99/1	105.4(727)	102.2(705)	3.0	
		50/50	147.8(1019)	147.4(1017)	0.3	
		40/60	146.4(1010)	144.7(998)	1.2	
		30/70	144.1(994)	140.6(970)	2.4	
	45	20/80	140.8(971)	136.3(940)	3.2	
		1/99	130.9(903)	130.4(899)	0.4	
•				•		
		C216E/HFC-	245cb			
•		95.1/4.9	100.6(694)	100.6(694)	0.0	
	50	99/1	100.4(692)	100.4(692)	0.0	
		70/30	96.9(668)	95.6(659)	1.3	
		•	` ,	, ,		•
•						
•	•		· · · · · · · · · · · · · · · · · · ·			-
					•	
- Andrew - A	- and sy mindiplying for	The area will have a successful to the successfu				11 17 9 mm - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1

			•		
	5	60/40	94.1(694)	91.8(633)	2.4
		50/50	90.8(626)	87.4(603)	3.7
		40/60	87.0(600)	87.9(606)	1.0
		30/70	82.8(571)	78.3(540)	5.4
		20/80	78.0(538)	74.1(511)	5.0
	10	•	•		0.0
	10	1/99	68.0(469)	68.0(469)	0.0
		C-216E2/HFC	2-32		
		36.0/64.0	272.4 (1878)	272.4 (1878)	0.0
		15.0/85.0	269.3 (1857)	256.1 (1766)	4.9
	15	1.0/99.0	250.4 (1726)	246.8 (1702)	1.4
	10	60.0/40.0	269.3 (1857)	261.3 (1802)	3.0
		80.0/20.0	250.6 (1728)	179.7 (1239)	28.3
		70.0/30.0	263.9 (1820)	238.7 (1646)	9.5
		71.0/29.0	263.0 (1813)	235.0 (1620)	10.6
	20	/1.0/23.0	205.0 (1815)	255.0 (1020)	10.0
	20	C-216E2/HFC	C-134		
		60.5/39.5	88.6 (611)	88.6 (611)	0.0
		80.0/20.0	86.7 <b>(5</b> 98)	85.9 (592)	0.9
		99.0/1.0	77.6 (535)	77.3 (533)	0.4
	25	40.0/60.0	87.2 (601)	86.4 (596)	0.9
		20.0/80.0	83.2 (574)	81.4 (561)	2.2
		1.0/99.0	76.5 (527)	76.3 (526)	0.3
		C-216E2/HF0			
	30	20.6/79.4	99.0 (683)	99.0 (683)	0.0
		1.0/99.0	98.3 (678)	98.3 (678)	0.0
		50.0/50.0	97.2 (670)	96.8 (667)	0.4
•		80.0/20.0	89.6 (618)	87.6 (604)	2.2
		99.0/1.0	77.6 (535)	77.3 (533)	0.4
	35	G 01 (TO /IT			•
		C-216E2/HF		02.0 (572)	0.0
		87.1/12.9	82.9 (572)	82.9 (572)	0.0
		99.0/1.0	78.1 (538)	77.5 (534)	0.8
		50.0/50.0	77.2 (532)	55.6 (383)	28.0
	40	70.0/30.0	80.8 (557)	78.5 (541)	2.8
		60.0/40.0	79.0 (545)	73.1 (504)	7.5
		58.0/42.0	78.7 (543)	71.2 (491)	9.5
		57.0/43.0	78.5 (541)	70.1 (483)	10.7
	45	C-216E2/HF	C-152a		
	73	60.5/39.5	95.6 (659)	95.6 (659)	0.0
		80.0/20.0	93.2 (643)	92.1 (635)	1.2
		99.0/1.0	78.4 (541)	77.7 (536)	0.9
		•		• •	
	50	40.0/60.0	94.2 (649)	93.5 (645)	0.7
	50	20.0/80.0	90.9 (627)	89.5 (617)	1.5
		1.0/99.0	86.1 (594)	85.9 (592)	0.2
:		• .			
•					
	٠.				
	. ,		·		

	5				
	J	C-216E2/HFC-161			· ·
		45.7/54.3	138.3 (954)	138.3 (954)	0.0
		20.0/80.0	135.8 (936)	134.6 (928)	0.9
		<b>▼</b>	•		
	10	1.0/99.0	130.6 (900)	130.4 (899)	0.2
	10	60.0/40.0	137.3 (947)	136.4 (940)	0.7
		80.0/20.0	129.0 (889)	120.3 (829)	6.7
•		85.0/15.0	123.7 (853)	111.0 (765)	10.3
		84.0/16.0	124.9 (861)	113.1 (780)	9.4
	15	C-216E2/HFC-245	cb		
		74.7/25.3	81.3 (561)	81.3 (561)	0.0
		99.0/1.0	77.2 (532)	77.1 (̀532)́	0.1
		50.0/50.0	79.3 (547)	78.6 (542)	0.9
		20.0/80.0	73.1 (504)	71.8 (495)	1.8
	20	1.0/99.0	67.7 (467)	67.6 (466)	0.1
		2.0,77.0	(,,,,	(100)	
		218E/HFC-134			
		99.0/1.0	87.3 (602)	84.7 (584)	3.0
		80.0/20.0	113.8 (785)	109.9 (758)	3.4
	25	63.3/36.7	116.6 (804)	116.6 (804)	0
		50.0/50.0	115.8 (798)	114.5 (789)	1.1
		35.0/65.0	113.5 (783)	102.7 (708)	9.5
		218E/HFC-134a			
	30	53.0/47.0	122.3(843)	122.3(843)	0.0
	50	70/30	120.2(829)	117.8(812)	2.0
		80/20	115.6(797)	109.1(752)	5.6
		99/1	86.8(598)	84.7(584)	2.4
		40/60	121.5(838)	120.3(830)	1.0
	35	30/70	119.6(825)	115.6(797)	3.3
		20/80	116.3(802)	108.0(745)	7.1
		1/99	99.9(689)	98.4 <u>(</u> 679)	1.5
		1/77	33.3(003)	JO.4(0 <i>1</i> J)	1.5
		218E/HFC-143			
	40	99.0/1.0	90.6 (625)	84.5 (583)	<b>6.7</b>
	٠	85.3/14.7	103.7 (715)	103.7 (715)	0
•		57.0/43.0	102.4 (706)	99.0 (683)	3.3
		218E/HFC-152a			
•	45	68.2/31.8	124.0(855)	124.0(855)	0.0
	75	80/20	112.4(775)	120.0(828)	6.8
•		•	89.5(617)	85.1(587)	· ·
		99/1 60/40	123.6(852)	123.0(848)	4.9
		•	•		0.5
	50	50/50 40/60	122.6(845)	119.5(824)	2.5
	٥٢	40/60 41/59	121.0(834) 121.2(836)	108.5(748) 110.3(761)	10.3 9.0
			121.2(050)	110.0(701)	). <del>U</del>
		· ·		·	
•					
			•		

			·	
5				
	218E/HFC-161	170 0/1170)	170.9(1179)	0.0
	62.6/37.4	170.9(1179) 167.8(1157)	160.2(1105)	4.5
	80/20	, ,	146.4(1010)	10.6
4.0	85/15	163.8(1130)	149.9(1034)	9.1
10	84/16	164.9(1137)		0.5
	60/40	170.9(1179)	170.8(1178)	10.1
	38/62	169.4(1168)	152.3(1050)	7.7
	39/61	169.5(1169)	156.5(1079)	1.1
15	218E/HFC-263	fb		
	96.3/3.7	84.0(579)	84.0(579)	0.0
	99/1	83.9(578)	83.9(578)	0.0
	70/30	80.0(552)	78.5(541)	1.9
	40/60	71.6(494)	66.1(456)	7.7
20	23/77	65.4(451)	59.1(407)	9.6
	24/76	65.8(454)	59.4(409)	9.7
	25/75	66.2(456)	60.2(415)	9.6
	10/90	59.5(410)	55.5(383)	6.7
	1/99	54.6(376)	54.1(373)	0.9
25	-40VIO /TVVIO 40			
30	218E2/HFC-13		76.2 (525)	1.2
	1.0/99.0	77.1 (532)	76.2 (525)	4.4
	20.0/80.0	86.9 (599)	83.1 (573) 89.6 (618)	0
	36.1/53.9	89.6 (618)	83.0 (572)	4.4
	70.0/30.0	86.8 (598)	74.8 (516)	9.9
	79.0/21.0	83.0 (572)	74.6 (310)	7.7
	218E2/HFC-134a			
	24.7/75.3	101.1(697)	101.1(697)	0.0
<b>35 40</b>	10/90	100.2(691)	99.9(689)	0.3
	1/99	98.5(679)	98.4(679)	0.1
	40/60	100.2(691)	99.6(687)	0.6
	50/50	98.7(681)	96.8(667)	1.9
	70/30	92.0(634)	84.1(580)	8.6
	73/27	90.2(622)	81.1(559)	10.1
	72/28	90.8(626)	82.1(566)	9.6
	218E2/HFC-1	L <b>43</b>	·	
•	91.0/9.0	70.7 (487)	65.0 (448)	8.1
45		72.6 (501)	72.6 (501)	0
	52.0/48.0	71.8 (495)	67.5 (465)	6.0
	218E2/HFC-	150a		
	51.0/49.0	98.1(676)	98.1(676)	0.0
Er	•	96.4(665)	93.9(647)	2.6
50	•	91.3(630)	82.0(565)	10.2
	82/18	7 1.3(030)	02.0(303)	10.2

	5	81/19	92.0(634)	83.5(576)	9.2
	J	40/60	97.7(674)	97.1(670)	0.6
		30/70	96.7(667)		
		•		94.5(652)	2.3
		20/80	94.8(654)	90.5(624)	4.5
-	4.0	10/90	91.5(631)	87.3(602)	4.6
	10	1/99	86.5(596)	85.9(592)	0.7
4		218E2/HFC-161			
		46.4/53.6	145.1(1001)	145.1(1001)	0.0
		60/40	144.4(996)	143.2(988)	0.8
	15	77 /23	139.4(961)	126.7(874)	9.1
	•	78/22	138.8(957)	124.5(859)	10.3
•		40/60	145.0(1000)	144.7(998)	0.2
		30/70	144.3(995)	142.0(979)	1.6
		20/80	142.7(984)	135.6(935)	5.0
	20	10/90	139.1(959)	131.3(906)	5.6
		1/99	131.5(907)	130.2(898)	1.0
				•	
		218E2/HFC-236fa	50 ((2(2)	50 ((0.50)	
	۰.	89.8/10.2	52.6(362)	52.6(362)	0.0
	25	99/1	52.3(360)	52.4(361)	0.2
		70/30	51.8(357)	51.6(356)	0.4
		60/40	50.8(350)	50.3(347)	1.0
		50/50	49.7(342)	48.8(336)	1.8
	••	30/70	46.6(321)	44.9(309)	3.6
	30	20/80	44.6(307)	42.9(296)	3.8
		10/90	42.2(291)	41.0(282)	2.8
		1/99	39.7(273)	39.5(272)	0.5
		218E2/HFC-263fb			
	35	60.5/39.5	57.9(399)	57.9(399)	0.0
	•	70/30	57.7(398)	57.7(398)	0.0
•		90/10	55.4(382)	55.1(380)	0.5
•		99/1	52.7(363)	52.6(362)	0.2
		50/50	57.7(398)	57.7(398)	0.0
	40	30/70	56.7(391)	56.5(389)	0.4
	:	20/80	56.0(386)	56.0(386)	0.0
		10/90	55.0(379)	54.8(378)	0.4
·		1/99	54.1(373)	54.1(373)	0.0
	45	C-225eEαβ/HFC-	1/12		
	73	55.9/44.1	38.0 (262)	29 N (262)	0.0
		80.0/20.0		38.0 (262)	0.0
•		•	36.7 (253)	36.1 (249)	1.6
		99.0/1.0	31.6 (218)	31.4 (216)	0.6
	50	20.0/80.0	36.1 (249)	35.4 (244)	1.9
	<b>50</b> .	1.0/99.0	33.3 (230)	33.2 (229(	0.3
	•				•
	•			•	
•					

5	C-225eEαβ/HF0	C-236cb		
J	16.7/83.3	33.7 (232)	33.7 (232)	0.0
	1.0/99.0	33.6 (232)	33.6 (232)	0.0
	•	33.3 (230)	33.3 (230)	0.0
	50.0/50.0			
	80.0/20.0	32.3 (223)	32.2 (222)	0.3
10	99.0/1.0	31.2 (215)	31.2 (215)	0.0
	C-225eEαβ/HF	C-236ea		
	91.5/8.5	31.1 (214)	31.1 (214)	0.0
	99.0/1.0	31.1 (214)	31.1 (214)	0.0
15	•	30.8 (212)	30.8 (212)	0.0
15	60.0/40.0	•	*	
	40.0/60.0	30.4 (210)	30.3 (209)	0.3
	20.0/80.0	29.7 (205)	29.6 (204)	0.3
	1.0/99.0	28.8 (199)	28.8 (199)	0.0
20	C-225eEαβ/HF	C-245cb		
	22.4/77.6	70.1 (483)	70.1 (483)	0.0
•	1.0/99.0	67.7 (467)	67.6 (466)	0.1
	50.0/50.0	67.7 (467)	65.7 (453)	3.0
	60.0/40.0	66.0 (455)	61.7 (425)	6.5
25	65.0/35.0	65.0 (448)	58.5 (403)	10.0
. 25	05.0/55.0	05.0 (448)	30.3 (403)	10.0
	227caEαβ/HFC			
	17.9/82.1	253.4(1748)	253.4(1748)	0.0
	10/90	252.8(1744)	251.8(1737)	0.4
30	1/99	247.9(1710)	247.1(1705)	0.3
	40/60	251.3(1734)	248.0(1711)	1.3
	60/40	244.7(1688)	223.4(1541)	8.7
	61/39	244.0(1683)	221.0(1524)	9.4
	62/38	243.4(1679)	218.2(1505)	10.4
35		213.1(1013)	210.2(1303)	10
	227caΕαβ/ΗΓ	C-143		
٠.	99.0/1.0	43.0 (296)	41.8 (288)	2.8
•	95.0/5.0	47.6 (328)	44.4 (306)	6.7
	70.9/29.1	53.7 (370)	53.7 (370)	0
40	42.0/58.0	52.0 (359)	46.9 (323)	9.8
	42.0/50.0	52.6 (55)		
	227caEαβ/HF			
	8.1/91.9	67.5(465)	67.5(465)	0.0
	1/99	67.4(465)	67.4(465)	0.0
45	30/70	66.7(460)	66.5(458)	0.3
_	50/50	64.5(445)	63.4(437)	1.7
	70/30	60.2(415)	56.8(391)	5.6
	77/23	57.9(399)	53.2(367)	8.1
	80/20	56.6(390)	51.5(355)	9.0
50	•		•	
50	•	55.8(385) 55.2(381)	50.3(347)	9.8
	83/17	55.3(381)	49.7(342)	10.1

5		•			
<b>5</b>	227caEαβ/HFC-272	2ca			
	94.3/5.7	41.4(285)	41.4(285)	0.0	
	99/1	41.4(285)	41.4(285)	0.0	
	80/20	41.0(282)	41.0(282)	0.0	
10	•	•	39.4(271)	0.8	
10		39.7(273)	•		
	40/60	38.1(262)	37.6(259)	1.3	
	20/80	36.4(251)	35.9(247)	1.4	•
	10/90	35.5(245)	35.2(242)	0.8	
	1/99	34.6(238)	34.6(238)	0.0	
15				·	
	227caEαβ/HFC-28				
	31.5/68.5	47.4(327)	47.4(327)	0.0	
	20/80	47.3(326)	47.3(326)	0.0	
	10/90	47.2(325)	47.2(325)	0.0	
20	1/99	47.1(325)	47.1(325)	0.0	
	50/50	47.2(325)	47.2(325)	0.0	
	70/30	46.5(320)	46.4(320)	0.2	
	90/10	44.2(305)	43.9(302)	0.7	
	99/1	41.7(287)	41.6(287)	0.2	
25	•	720 (2017)	(==+,		
	227caΕαβ/HFC-28	1fa			
	84.3/15.7	42.4(292)	42.4(292)	0.0	
	90/10	42.3(291)	42.3(291)	0.0	
	99/1	41.5(286)	41.5(286)	0.0	
30		41.6(287)	41.4(285)	0.5	
30	40/60	40.3(278)	40.0(276)	0.7	
	•			0.8	
	20/80	39.0(269)	38.7(267)		•
	10/90	38.4(265)	38.2(263)	0.5	
	1/99	37.8(260)	37.8(260)	0.0	
. 3		•			
	227caEβγ/HFC-32			0.0	
· · .	28.4/71.6	269.7(1860)	269.7(1860)	0.0	
	10/90	268.6(1853)	247.0(1704)	8.0	
	1/99	255.3(1761)	246.7(1702)	3.4	
4	0 40/60	269.4(1858)	268.8(1854)	0.2	
	60/40	266.6(1839)	255.3(1761)	4.2	
	67/33	263.7(1819)	238.6(1646)	9.5	
	68/32	263.1(1815)	235.0(1621)	10.6	
• 4	15 $227 \text{ca} \text{E} \beta \gamma / \text{HFC-1}$	34	·		
, .	34.8/65.2	82.7 (571)	82.7 (571)	0.0	
	10/90	80.0 (552)	78.7 (543)	1.6	
	5/95	78.4 (541)	77.3 (533)	1.4	
	1/99	76.6 (529)	76.3 (527)	0.0	
4	50 50/50	81.9 (565)	81.1 (560)	1.0	
•	60/40	80.3 (554)	77.8 (537)	3.1	
	30) <del>1</del> 0	00.0 (001)	,,,,,	<b></b>	
• •					
		•			
• • • • • • • • • • • • • • • • • • • •	•				
• • • •				. •	

5	70/30	77.3 (533)	72.2 (498)	6.6
J	77/23	74.1 (511)	66.7 (460)	10.0
	76/24	74.6 (515)	67.6 (466)	9.4
	10,21			
	227caΕβγ/ΗΕ	FC-134a		
10	1.9/98.1	98.3(678)	98.3(678)	0.0
	1/99	98.3(678)	98.3(678)	0.0
	20/80	97.2(670)	96.9(668)	0.3
	30/70	95.8(661)	94.8(654)	1.0
	50/50	91.0(627)	87.1(601)	4.3
15	68/32	83.3(574)	74.8(516)	10.2
	67/33	83.8(578)	75.6(521)	9.8
		Da 440		
	227caΕβγ/H	FC-143	57.4 (396)	9.0
	91.0/9.0	63.1 (435)	66.2 (456)	0
20	73.8/26.2	66.2 (456)	59.1 (407)	9.2
	46.0/54.0	65.1 (449)	39.1 (407)	7,2
	227caΕβγ/H	FC-152a		
	38.3/61.7	91.4(630)	91.4(630)	0.0
25	20/80	90.4(623)	89.6(618)	0.9
	10/90	88.7(612)	87.6(604)	1.2
•	1/99	86.1(594)	85.9(592)	0.2
	60/40	89.8(619)	88.0(607)	• 2.0
	70/30	87.2(601)	82.7(570)	5.2
30	80/20	82.1(566)	73.1(504)	11
	78/22	83.4(575)	75.4(520)	9.6
	79/21	82.8(571)	74.3(512)	10.2
	227caΕβγ/Ι	JEC-161		
25	34.4/65.6	137.5(948)	137.5(948)	0.0
35	20/80	136.7(943)	135.6(935)	0.8
	10/90	134.7(929)	132.6(914)	1.6
	1/99	130.8(902)	130.4(899)	0.3
	40/60	134.4(927)	137.3(947)	2.2
40		135.0(931)	131.0(903)	3.0
	72/28	130.2(898)	117.8(812)	9.5
	73/27	129.6(894)	116.0(800)	10.4
	227caΕβγ/	HFC-263fb	F1 (1051)	0.0
45	•	54.6(376)	54.6(376)	0.0
	20/80	54.5(376)	54.5(376)	0.0
	10/90	54.3(374)	54.3(374)	0.0
	1/99	54.0(372)	54.0(372)	0.0
	50/50	54.4(375)	54.4(375)	0.0
5	•	53.4(368)	53.2(367)	0.4
,	90/10	50.9(351)	50.7(349)	0.4

5	99/1	49.0(338)	48.9(337)	0.2
	227caEβγ/HFC	C-272ca		
	89.0/11.0	49.6(342)	49.6(342)	0.0
	99/1	48.9(337)	48.9(337)	0.0
10	60/40	47.1(325)		
10	40/60	44.1(304)	46.0(317)	2.3
	30/70	• •	41.3(285)	6.3
	•	42.2(291)	38.9(268)	7.8
	20/80	40.1(276)	36.9(254)	8.0
	10/90	37.6(259)	35.4(244)	5.9
15	1/99	34.8(240)	34.6(238)	0.6
	80/20	49.3(340)	49.2(339)	0.2
	227caΕβγ/HFC			
	73.1/26.9	54.0(372)	54.0(372)	_ 0.0
20	80/20	53.8(371)	53.8(371)	0.0
	90/10 ·	52.6(362)	52.3(360)	0.0
	99/1	49.3(340)	49.2(339)	0.6
	60/40	53.4(368)	53.4(368)	0.2
	40/60	52.0(358)	51.4(354)	0.0
.25	30 <sup>′</sup> /70	51.0(351)	50.1(345)	1.8
	10/90	48.6(335)	48.0(331)	1.2
	1/99	47.3(326)	47.2(325)	0.2
	227caΕβγ/HF0	C-281fa	·	
30	85.9/14.1	51.0(351)	51.0(351)	0.0
	90/10	50.9(351)	50.9(351)	0.0
	99/1	49.1(338)	49.1(338)	0.0
	70/30	50.0(345)	49.5(341)	1.0
	40/60	45.9(316)	43.3(298)	5.7
35	30/70	44.2(305)	41.2(284)	6.8
	20/80	42.3(291)	39.6(273)	6.4
	10/90	40.1(276)	38.5(265)	
-	1/99	38.0(262)		4.0
	1/77	36.0(202)	37.8(260)	0.5
40	227eaE/HFC-3	32		
	30.0/70.0	272.3(1878)	272.3(1878)	0.0
	20/80	272.1(1877)	270.9(1869)	0.4
	10/90	271.2(1871)	246.7(1702)	9.0
	1/99	257.1(1774)	246.7(1702)	4.0
45	50/50	271.4(1872)	268.6(1853)	1.0
	60/40	269.6(1860)	259.6(1791)	
	68/32	266.4(1838)	240.8(1661)	3.7
	69/31		•	9.6
	07/31	265.8(1834)	237.1(1636)	10.8
50	227eaE/HFC-	134		
	1.0/99.0	76.7 (529)	76.3 (526)	0.5
	<del>-</del>		(= -34)	<del>0.</del>

			-0.0 (F.(1))	0.5
5	10.0/90.0	80.9 (558)	78.9 (544)	2.5
	38.2/61.8	84.7 (584)	84.7 (584)	0
	60.0/40.0	82.7 (570)	80.7 (556)	2.4
	78.0/22.0	76.4 (527)	69.1 (476)	9.6
	•			
10	227eaE/HFC-1	34a		
	9.3/90.7	98.6(680)	98.6(680)	0.0
	1/99	98.3(678)	98.3(678)	0.0
	30/70	97.2(670)	96.5(665)	0.7
	40/60	95.5(659)	93.8(647)	1.8
15	60/40	89.6(618)	83.9(578)	6.4
	70/30	84.6(583)	76.2(525)	9.0
	71/29	84.0(579)	75.3(519)	10.4
	, = / = -	,	•	
	227eaE/HFC-1	143		
20	92.0/8.0	65.4 (451)	<b>59.1 (408)</b>	9.6
	74.9/25.1	68.9 (475)	68.9 (475)	0.0
	47.0/53.0	67.7 (469)	61.7 (426)	8.9
	80.0/20.0	68.8 (475)	68.4 (472)	0.6
	93.0/7.0	64.6 (451)	57.7 (398)	<b>10.7</b>
25	60.0/40.0	68.4 (446)	67.6 (466)	1.2
	50.0/50.0	67.9 (472)	65.2 (450)	4.0
	46.0/54.0	67.7 (474)	59.0 (407)	12.8
	·	•		
	227eaE/HFC-	152a		
30	42.1/57.9	93.2(643)	93.2(643)	0.0
•	20/80	91.6(632)	90.3(623)	1.4
	10/90	89.4(616)	87.8(605)	1.8
	1/99	86.2(594)	85.9(592)	0.3
•	60/40	92.0(634)	90.7(625)	1.4
35	70/30	89.7(618)	85.8(592)	4.3
	80/20	84.9(585)	76.5(527)	9.9
	81/19	84.2(581)	75.2(518)	10.7
	30/70	92.8(640)	92.3(636)	0.5
		•		•
40	•	2-161		0.0
٠.	37.5/62.5	139.5(962)	139.5(962)	0.0
	20/80	138.3(954)	136.4(941)	1.4
	10/90	135.8(937)	132.6(914)	2.4
•	1/99	131.0(903)	130.3(899)	0.5
45	60/40	137.5(948)	134.2(926)	2.4
	70/30	134.2(926)	124.8(866)	7.0
	73/27	132.6(914)	120.1(828)	9.4
	74/26	131.9(910)	118.3(816)	10.3
	30/70	139.3(961)	139.0(959)	0.2
50	•			
	227eaE/HF0	C-263fb		
	•			

-	10.0/50.7	557/201	55.7(384)	0.0
5	49.3/50.7	55.7(384)	•	0.2
	30/70	55.4(382)	55.3(381) 55.0(370)	0.0
	20/80	55.0(379)	55.0(379)	
	10/90	54.6(376)	54.5(376)	0.2
	1/99	54.1(373)	54.0(372)	0.2
10	70/30	55.2(380)	55.1(380)	0.2
	80/20	54.4(375)	54.3(374)	0.2
•	90/10	53.2(367)	53.0(365)	0.4
	99/1	51.5(355)	51.5(355)	0.0
		•	· · · · · · · · · · · · · · · · · · ·	*·· -
15	227eaE/HFC-272ca			
	90.7/9.3	52.0(358)	52.0(358)	0.0
	99/1	51.4(354)	51.4(354)	0.0
	70/30	50.3(347)	49.6(342)	1.4
	50/50	47.3(326)	44.7(308)	5.5
20	35/65	44.5(307)	40.4(278)	<b>9.2</b>
	30/70	43.4(299)	39.1(269)	9.9
• • •	29/71	43.2(298)	38.8(267)	10.2
	80/20	51.4(354)	51.2(353)	0.4
	80/20	31.4(334)	31.2(000)	
25	227eaE/HFC-281ea			
	76.8/23.2	55.9(385)	55.9(385)	0.0
	•	54.9(378)	54.7(377)	0.4
	90/10	51.8(357)	51.7(356)	0.2
	99/1		54.8(378)	0.7
20	60/40	55.2(380) 53.2(367)	52.1(359)	2.1
30	40/60	53.2(367) 51.0(358)	50.6(349)	2.5
	30/70	51.9(358) 50.4(347)	• -	2.4
	20/80	50.4(347)	49.2(339) 48.1(331)	1.6
	10/90	48.9(337)		0.2
25	1/99	47.3(326)	47.2(325)	0.2
. 35	007 F /TTC 2015-			
·	227eaE/HFC-281fa		52 2/267)	0.0
	87.6/12.4	53.3(367)	53.3(367)	
	99/1	51.7(356)	51.6(356)	0.2
	60/40	50.5(348)	48.9(337)	3.2
40	40/60	47.2(325)	43.7(301)	7.4
	30/70	45.2(311)	41.4(285)	8.4
	20/80	43.0(296)	39.6(273)	7.9
	10/90	40.5(279)	38.4(265)	5.2
	1/99	38.0(262)	37.8(260)	0.5
45	70/30	51.9(358)	51.2(353)	1.3
•	$C-234fE\alpha\beta/HFC-2$			
	13.5/86.5	69.9 (482)	69.9 (482)	0.0
	1.0/99.0	67.9 (468)	67.7 (467)	0.3
50	40.0/60.0	67.6 (466)	65.6 (452)	3.0
	50.0/50.0	66.4 (458)	63.6 (439)	4.2
			•	
				•
•				
· ·				
			•	

MA	03	12	400	7
WO	7.3	I Z	477	۲n

## PCT/US93/04614

Α	2
4	L

5	55.0/45.0	65.9 (454)	62.0 (427)	5.9
	57.0/43.0	65.7 (453)	60.7 (419)	7.6
	58.0/42.0	65.6 (452)	59.5 (410)	9.3
	59.0/41.0	65.5 (452)	57.5 (396)	12.2
	•	,	( )	
10	C-234fE $\alpha\beta$ /HI	FC-245eb		
	49.1/50.9	17.6 (121)	17.6 (121)	0.0
	20.0/80.0	17.3 (119)	17.3 (119)	0.0
	1.0/99.0	16.9 (117)	16.9 (117)	0.0
	80.0/20.0	17.3 (119)	17.3 (119)	0.0
15	99.0/1.0	16.8 (116)	16.8 (116)	0.0
10	7710/ 210	2010 (220)	10.0 (110)	0.0
	C-234fE $\alpha\beta$ /HI	FC-356mff		
	59.0/41.0	18.8 (130)	18.8 (130)	0.0
	80.0/20.0	18.4 (127)	18.2 (125)	1.1
20	99.0/1.0	16.9 (117)	16.8 (116)	0.6
~	40.0/60.0	18.5 (128)	18.3 (126)	1.1
	20.0/80.0	17.3 (119)	16.8 (116)	2.9
	10.0/90.0	16.2 (112)	15.7 (108)	3.1
	1.0/99.0	14.8 (102)	14.8 (102)	0.0
25	2.07 55.0	11.0 (102)	11.0 (102)	0.0
	C-234fEαβ/H	FC-356mmz		
	50.1/49.9	20.1 (139)	20.1 (139)	0.0
	20.0/80.0	19.1 (132)	18.7 (129)	2.1
	1.0/99.0	16.8 (116)	16.7 (115)	0.6
30	80.0/20.0	19.2 (132)	18.7 (129)	2.6
	990/1.0	16.9 (117)	16.8 (116)	0.6
	•			
	C-234fE $\beta\gamma$ /H	FC-245cb		
	10.2/89.8	69.1 (476)	69.1 (476)	0.0
35	1.0/99.0	67.8 (467)	67.7 (467)	0.1
	40.0/60.0	66.4 (458)	64.4 (444)	3.0
	50.0/50.0	65.4 (451)	62.7 (432)	4.1
	55.0/45.0	65.0 (448)	61.0 (421)	6.2
	58.0/42.0	64.7 (446)	52.6 (363)	18.7
40	57.0/43.0	64.8 (447)	57.9 (399)	10.6
	56.0/44.0	64.9 (447)	60.0 (414)	7.6
	•		,	,
	C-234fE $\beta\gamma$ /H	IFC-245ca		
	33.6/66.4	14.5 (100)	14.5 (100)	0.0
45	15.0/85.0	14.4 (99)	14.4 (99)	0.0
-	1.0/99.0	14.2 (98)	14.2 (98)	0.0
	60.0/40.0	14.3 (99)	14.3 (99)	0.0
	80.0/20.0	13.9 (96)	13.9 (96)	0.0
	99.0/ 1.0	13.3 (92)	13.3 (92)	0.0
50		·- \ <i>-</i> /-/		3.0
	C-234 $fE\beta\gamma/H$	IFC-245ea		

5	36.0/64.0	14.5 (100)	14.5 (100)	0.0
	15.0/85.0	14.4 (99)	14.4 (99)	0.0
	1.0/99.0	14.2 (98)	14.2 (98)	0.0
	•			
	60.0/40.0	14.4 (99)	14.3 (99)	0.7
	80.0/20.0	14.0 (97)	13.9 (96)	0.7
10	99.0/ 1.0	13.3 (92)	13.3 (92)	0.0
	•	` ,		
	C-234 $fE\beta\gamma/HI$	FC-254ca		
	36.0/64.0	13.8 (95)	13.8 (95)	0.0
	15.0/85.0	13.8 (95)	13.8 (95)	0.0
15	1.0/99.0	13.7 (94)		
13	•	• •	13.7 (94)	0.0
	60.0/40.0	13.8 (95)	13.8 (95)	0.0
	80.0/20.0	13.6 (94)	13.6 (94)	0.0
	99.0/ 1.0	13.3 (92)	13.3 (92)	0.0
20	C-234fEβγ/H	FC-356mff		
	43.1/56.9	17.1 (118)	17.1 (118)	0.0
	20.0/80.0	16.5 (114)		
	•		16.3 (112)	1.2
	1.0/99.0	14.8 (102)	14.8 (102)	0.0
	70.0/30.0	16.5 (114)	16.0 (110)	3.0
25	90.0/10.0	15.0 (103)	14.0 (97)	6.7
•	99.0/1.0	13.5 (93)	13.3 (92)	1.5
	C-234fEβγ/H	FC-356mmz		·
-	35.8/64.2	18.6 (128)	10 6 /120\	0.0
20	•		18.6 (128)	0.0
30	15.0/85.0	18.0 (124)	17.8 (123)	1.1
	1.0/99.0	16.7 (115)	16.7 (115)	0.0
	60.0/40.0	18.1 (125)	17.6 (121)	2.8
	80.0/20.0	16.8 (116)	15.3 (105)	8.9
	85.0/15.0	16.2 (112)	14.5 (100)	10.5
35	83.0/17.0	16.5 (114)	14.8 (102)	10.3
	82.0/18.0	16.6 (114)	15.0 (103)	9.6
	236caE/HFC		15.0 (105)	7.0
	60.0/40.0	30.4 (210)	27.4 (190)	0.0
		•	27.4 (189)	9.9
	12.0/88.0	33.4 (230)	33.4 (231)	0.0
40	10.0/90.0	33.4 (230)	33.4 (230)	0.0
•	1.0/99.0	33.1 (228)	33.1 (228)	0.0
	5.0/95.0	33.3 (230)	33.3 (230)	0.0
	30.0/70.0	33.0 (228)	33.0 (228)	0.0
•	40.0/60.0	32.4 (224)	31.7 (219)	2.2
15		•		2.2
45	61.0/39.0	30.3 (209)	27.1 (187)10.6	
	236caE/HFC	-245ca		
	1.0/99.0	14.2 (98)	14.2 (98)	0.0
	10.0/90.0	14.1 (97)	14.1 (97)	0.0
50	20.0/80.0	14.0 (97)	14.0 (97)	
50	7	` ,	7 7	0.0
•	30.0/70.0	13.9 (96)	13.9 (96)	0.0

	5	40.0/60.0	13.8 (95)	13.7 (94)	0.7	•
		50.0/50.0	13.6 (94)	13.6 (94)	0.0	
		60.0/40.0	13.5 (93)	13.4 (92)	0.7	
		70.0/30.0	13.3 (92)	13.3 (92)	0.0	
		80.0/20.0	13.2 (91)	13.2 (91)	0.0	
,	10	90.0/10.0	13.1 (90)	13.0 (90)	0.8	•
	10	99.0/1.0	12.9 (89)	12.9 (89)	0.0	
		99.0/1.0	12.5 (65)	12.5 (65)		
		236caE/HFC-2	54ca			•
	15	17.6/82.4	<b>13.7(94)</b> .	13.7(94)	0.0	
		10/90	13.7(94)	13.7(94)	0.0	
		1/99	13.7(94)	13.7(94)	0.0	
		30/70	13.7(94)	13.7(94)	0.0	
		50/50	13.6(93)	13.6(93)	0.0	
	20	70/30	13.4(92)	13.4(92)	0.0	
		90/10	13.1(90)	13.1(90)	0.0	:
		99/1	13.0(89)	13.0(89)	0.0	
		40/60	13.7(94)	13.7(94)	0.0	
	25	236eaEβγ/HF	C-143	00.4 (00.4)	0.2	
		66.0/34.0	32.1 (221)	29.1 (201)	9.3	
		25.9/74.1	34.6 (239)	34.6 (239)	0	
		10.0/90.0	34.1 (235)	33.9 (234)	0.6	
		1.0/99.0	33.2 (229)	33.2 (229)	0	
	30					
		236eaEβγ/HF	C-245ca	147/101\	0.0	
		1.0/99.0	14.7 (101)	14.7 (101)	0.0	
		10.0/90.0	15.0 (103)	15.0 (103) 15.3 (105)	0.6	,
		20.0/80.0	15.4 (106)	15.3 (105) 15.6 (108)	0.0	. :
,	35	30.0/70.0	15.6 (108)	15.8 (109)	0.0	
		40.0/60.0	15.8 (109)	16.0 (110)	0.0	
		50.0/50.0	16.0 (110) 16.1 (111)	16.1 (111)	0.0	
. •		60.0/40.0	16.1 (111)	16.1 (111)	0.0	
	40	69.1/30.9	16.1 (111)	16.1 (111)	0.0	
···:	40	80.0/20.0	15.9 (110)	15.9 (110)	0.0	
		90.0/10.0	15.7 (108)	15.7 (108)	0.0	
		99.0/1.0	, ,	15.7 (100)		,
		236eaΕβγ/H	FC-263ca	40.0/405)	^ ^	•
	45	4.1/95.9	18.2(125)	18.2(125)	0.0	
		1/99	18.2(125)	18.2(125)	0.0	
		30/70	18.1(124)	18.1(124)	0.0	-
		50/50	17.9(123)	17.8(122)	0.6	
		70/30	17.3(119)	17.2(118)	0.6	
	50	•	16.4(113)	16.3(112)	0.6	
		99/1	15.8(109)	15.8(109)	0.0	
				· .		,
				•		
•						
		· .		·		

5				
	236eaEβγ/HFC	C-338mf		
	92.6/7.4	16.2(111)	16.1(111)	0.6
	99/1	15.8(109)	15.7(108)	0.6
	70/30	17.4(120)	17.2(118)	1.1
10	50/50	18.1(124)	18.0(124)	0.6
	40/60	18.4(127)	18.4(127)	0.0
	30/70	18.6(128)	18.6(128)	0.0
	10/90	18.8(129)	18.8(129)	0.0
	1/99	18.8(129)	18.8(129)	0.0
15	•	•		
	236eaEβγ/HF	C-356mff -		
	1.0/99.0	14.9 (103)	14.9 (103)	0.0
	10.0/90.0	15.1 (104)	15.1 (104)	0.0
	20.0/80.0	15.2 (105)	15.2 (105)	0.0
20	30.0/70.0	15.3 (106)	15.3 (106)	0.0
	40.0/60.0	15.4 (106)	15.4 (106)	0.0
	50.0/50.0	15.5 (107)	15.5 (107)	0.0
	60.0/40.0	15.6 (108)	15.6 (108)	0.0
	70.0/30.0	15.6 (108)	<b>15.6</b> (108)	0.0
25	80.0/20.0	15.7 (108)	15.7 (108)	0.0
	90.0/10.0	15.7 (108)	15.7 (108)	0.0
	96.9/3.1	15.7 (108)	15.7 (108)	0.0
	99.0/1.0	15.7 (108)	15.7 (108)	0.0
30	236eaΕβγ/HF	C-356mmz		
	15.1/84.9	16.6(114)	16.6(114)	0.0
	1/99	16.6(114)	16.6(114)	0.0
	30/70	16.6(114)	16.6(114)	0.0
	50/50	16.5(113)	16.5(113)	0.0
35	70/30	16.2(111)	16.2(111)	0.0
•	90/10	15.9(109)	15.9(109)	0.0
· · · · · · · · · · · · · · · · · · ·	99/1	15.7(108)	15.7(108)	0.0
	236faE/HFC	-32		
40	8.5/91.5	248.6(1715)	248.6(1715)	0.0
	1/99	247.2(1705)	247.0(1704)	0.1
	20/80	247.5(1707)	246.5(1700)	0.4
	40/60	243.5(1680)	236.4(1631)	2.9
•	50/50	240.0(1656)	224.0(1545)	6.7
45	55/45	237.3(1637)	213.8(1475)	9.9
٠	56/44	236.7(1633)	211.3(1458)	10.7

5	236faE/HFC-1	43		
	84.0/16.0	42.2 (291)	38.2 (264)	9.5
	56.9/43.1	45.1 (311)	45.1 (311)	0.0
	30.0/70.0	43.8 (302)	40.4 (279)	<b>7.</b> 8
	28.0/72.0	43.6 (301)	39.5 (272)	9.4
10	40.0/60.0	44.6 (308)	43.6 (301)	2.2
10	27.0/73.0	43.5 (300)	39.0 (269)	10.3
	70.0/30.0	44.6 (308)	43.9 (303)	1.6
	80.0/20.0	43.2 (298)	40.5 (280)	6.3
	•	41.4 (286)	37.0 (255)	10.6
15	86.0/14.0	41.8 (288)	37.6 (259)	10.0
15	85.0/15.0	41.0 (200)	37.0 (237)	10.0
	236faE/HFC-2			
	27.8/72.2	34.8(240)	34.8(240)	0.0
	10/90	34.7(239)	34.7(239)	0.0
20	1/99	34.5(238)	34.5(238)	0.0
	40/60	34.7(239)	34.7(239)	0.0
	60/40	34.2(236)	34.1(235)	0.3
	70/30	33.7(232)	33.5(231)	0.6
	90/10	31.6(218)	31.3(216)	0.9
25	99/1	29.8(205)	29.8(205)	0.0
	236faE/HFC-	272fb		
	82.3/17.7	30.2(208)	30.2(208)	0.0
	▼	29.7(204)	29.7(204)	0.0
20	99/1 70/30	30.0(207)	30.0(207)	0.0
30	50/50	29.3(202)	29.2(201)	0.3
	40/60	28.9(199)	28.6(197)	1.0
•	•	28.3(195)	28.0(197)	1.1
	30/70	27.7(191)	27.5(189)	0.7
25	20/80		26.9(185)	0.7
35	10/90	27.1(187)	26.5(182)	0.0
	1/99	26.5(182)	20.3(162)	<b>0.0</b>
·.:	236faE/HFC			
	9.3/90.7	37.7(260)	37.7(260)	0.0
40	1/99	37.7(260)	37.7(260)	0.0
-	20/80	37.7(260)	37.7(260)	0.0
•	40/60	37.4(258)	37.4(258)	0.0
	60/40	36.6(252)	36.4(251)	0.5
. •	70/30	35.9(247)	35.6(245)	0.8
45	80/20	34.8(240)	34.2(236)	1.7
	90/10	32.9(227)	32.3(222)	1.8
	99/1	30.0(207)	29.9(206)	0.3
	245faΕβγ/H	FC-356mff		
50		14.9 (103)	14.9 (103)	0.0
ΣŲ	4.4/95.6	14.9 (103)	14.9 (103)	0.0
	4.4/33.0	14.5 (103)	14.7 (103)	, 0.0

WO 9	2 <i>/</i> 7	45	26

P	CT	/1	150	3/	'n.	lK1	1
4	$\sim$ 1 $^{\circ}$		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	J,	U٦	PV I	**

4	-
Λ	•
7	•

5	10.0/90.0	14.9 (103)	14.9 (103)	0.0
	20.0/80.0	14.8 (102)	14.8 (102)	0.0
	30.0/70.0	14.7 (101)	14.7 (101)	0.0
	40.0/60.0	14.6 (100)	14.6 (100)	0.0
	50.0/50.0	14.4 (99)	14.3 (99)	0.7
10	60.0/40.0	14.2 (98)	14.1 (97)	0.7
	70.0/30.0	13.9 (96)	13.8 (95)	0.7
	80.0/20.0	13.6 (93)	13.4 (93)	1.5
	90.0/10.0	13.2 (91)	13.1 (90)	0.8
	99.0/1.0	12.8 (88)	12.7 (88)	·· 0.8
15				

## EXAMPLE 3

20

## Refrigerant Performance

The following table shows the refrigerant performance of various compositions. Except where indicated, the data are based on the following conditions.

•	Evaporator temperature	45.0°F (7.2°C)
25	Condenser temperature	130.0°F (54.4°C)
	Subcool temperature	15°F
	Return gas temperature	65.0°F (18.3°C)
	Compressor efficiency is 75%.	

30

## TABLE 4

· · · · · · · · · · · · · · · · · · ·	Refrig.	Evap. Press.	Cond. Press.	Comp. Dis	<b>5.</b>	Capaci BTU/i	•
	Comp.	Psia (kPa)	<u>Psia (kPa</u>	Temp. °F (°	<u>°C)</u> (	COP (kw	<u>/)_</u>
35	HCFC-22	90.6 (625)	312.6 (2155)	212.8 (100.4)	3.41	351.3 (6.2)	
	125E/HFC-32	2					
	5.0/95.0	146.3 (1009)	502.6 (3465)	250.5 (121.0)	3.14	544.0 (9.6)	
40	40.0/60.0	134.4 (927)	,	217.3 (102.9)	3.11	474.9 (8.3)	•
	95.0/5.0	82.4 (568)	298.2 (2056)	162.0 (72.2)	3.04	272.7 (4.8)	
	125E/HFC-12	25					
	5.0/95.0	16.2 (112)	70.8 (488)	166.3 (74.6)	3.99	85.8 (1.5)	
45	95.0/5.0*	49.8 (343)	236.8 (1633)	120.5 (49.2)	3.14	209.6 (3.7)	

5	* = Condenser temp. is 80°F, evaporator temp. is 0°F, subcool temp. is 25°F and
	return gas is 20°F

	125E/HFC-13		071 0 (1075)	156 4 (60 1)	2.00	241 6 (4 2)
	99.0/1.0	74.1 (511)	,	156.4 (69.1)	2.98	241.6 (4.2)
10	86.5/13.5	72.3 (498)	,	158.1 (70.1)	3.06	244.5 (4.3)
	37.0/63.0	56.2 (387)	218.2 (1504)		3.43	228.4 (4.0)
	5.0/95.0	44.5 (307)	179.4 (1237)	1/3.1 (/8.4)	3.58	197.6 (3.5)
	125E /UEC 12	Ma				
15	125E/HFC-13 5.0/95.0	56.1 (387)	215.9 (1489)	172.0 (77.8)	3.44	228.7 (4.0)
13	50.0/50.0	63.6 (439)	240.2 (1655)	1	3.27	238.6 (4.2)
	95.0/5.0	73.0 (503)	268.9 (1854)	` '	3.00	241.2 (4.2)
	33.073.0	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		•		
	125E/HFC-14	43				
20	5.0/95.0	17.7 (122)	77.8 (536)	190.0 (87.8)	3.87	93.0 (1.6)
	92.0/8.0	64.7 (446)	248.4 (1713)		3.12	231.3 (4.1)
	99.0/1.0	76.3 (526)	280.3 (1933)	160.3 (71.3)	3.05	254.9 (4.5)
	105E /IEC 1	42.0				
05	125E/HFC-1	43a 110.8 (764)	367.1 (2531)	216.7 (102.6)	3.18	384.5 (6.8)
25	5.0/95.0* 95.0/5.0+	33.1 (228)	143.5 (989)	119.4 (48.6)	3.40	145.9 (2.6)
	93.0/3.0+	33.1 (220)	113.3 (303)	11311 (1010)		
	* = Subcool	temp. is 20°F				
	+ = Conden	ser temp. is 80°	F, evaporator	temp. is 0°F and	l return g	gas temp. is 20°F
30						
	125E/HFC-1					005 5 (4.0)
	5.0/95.0	52.1 (359)	197.2 (1360)		3.60	227.5 (4.0)
	84.4/15.6	75.4 (520)	274.4 (1892)		3.17	264.0 (4.6)
	95.0/ 5.0	77.6 (535)	282.9 (1951)	163.9 (73.3)	3.07	260.2 (4.6)
35	105T2 /UTCC	161		•		•
	125E/HFC- 5.0/95.0	80.4 (554)	282.6 (1948)	200.3 (93.5)	3.47	317.4 (5.6)
,	66.5/35.5	89.6 (618)	311.9 (2150)	· •	3.23	314.7 (5.5)
	99.0/ 1.0	78.9 (544)	288.0 (1986	•	3.02	259.3 (4.6)
40	•	70.5 (2 . 1)				,
	125E/HFC-	227ca		••		
	5.0/95.0	38.2 (263)	149.4 (1030	) 143.7 (62.1)	3.22	141.4 (2.5)
	95.0/5.0	75.4 (520)	277.1 (1911	) 160.9 (71.6)	3.04	250.5 (4.4)
	•					
45	•		100 ( (000)	4400 (60.5)	2.24	101 0 (0 1)
	5.0/95.0	30.4 (210)	130.4 (899)	· · · · · · · · · · · · · · · · · · ·	3.24	121.2 (2.1)
	95.0/5.0	74.6 (514)	276.0 (1903	3) 161.0 (71.7)	3.04	249.2 (4.4)
	125E/HFC	-236ch				
50		20.0 (138)	86.2 (594)	146.1 (63.4)	3.57	90.8 (1.6)
3(	95.0/5.0	71.1 (490)				
	33.0/3.0	7 1.1 (100)		, ===: ()		, , , , ,

	5						•	•
		125E/HFC-2	36fa					
		5.0/95.0	21.9 (151)	93.2 (643)	145.9 (63.3)	3.53	97.1 (1.7)	j
		95.0/5.0	71.8 (495)	268.8 (1853)		3.08	245.9 (4.3)	!
1	0	125E/HFC-2	45ca					
•		5.0/95.0	8.46 (58)	42.6 (294)	156.8 (69.3)	3.97	48.7 (0.9)	
		95.0/5.0	61.2 (422)	250.5 (1727)	•	3.08	226.2 (4.0)	
		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	( )		(, , ,			
		125E/HFC-2	45 <b>c</b> b					
1	15	5.0/95.0	37.9 (261)	143.0 (986)		3.33	143.0 (2.5)	
		95.0/5.0	74.2 (512)	276.8 (1908)	161.5 (71.9)	3.00	246.0 (4.3)	
		125E/HFC-2	245ea					
		5.0/95.0	8.41 (58)	43.2 (298)	161.4 (71.9)	4.00	49.6 (0.9)	
2	20	95.0/5.0	61.2 (422)	251.0 (1731)	•	3.08	226.6 (4.0)	*.
			N456					
		125E/HFC-2		50.7 (410)	154 4 (60.0)	2.00	(( 1 (1 0)	•
		5.0/95.0	12.7 ((88)	59.7 (412)	154.4 (68.0)	3.80	66.4 (1.2)	٠
,	25	95.0/5.0	61.9 (427)	258.4 (1782)	167.6 (75.3)	2.88	216.9 (3.8)	
•	25	125E/HFC-2	25402		·			•
	•	5.0/95.0	8.05 (56)	40.5 (279)	160.0 (71.1)	3.99	46.8 (0.8)	
		95.0/5.0	59.0 (407)	245.6 (1693)	•	3.09	222.0 (3.9)	
		·	, ,		` '		,	
	30	125E/HFC-		05.0 (506)	154 ( /(0 1)	2.67	02.0 (1.6)	
		5.0/95.0	20.0 (138)	•	154.6 (68.1)	3.67	93.8 (1.6)	
		95.0/5.0	69.7 (481)	263.2 (1815)	162.1 (72.3)	3.11	243.4 (4.3)	
		125E/HFC-	254eb					
	35	5.0/95.0	69.3 (478)	263.5 (1817	) 162.5 (72.5)	3.08	241.1 (4.2)	
		95.0/5.0	67.1 (463)	270.3 (1864	) 166.6 (74.8)	2.87	226.9 (4.0)	•
•		125E/HFC	263ca					
		5.0/95.0	10.6 (73)	49.5 (341)	161.5 (71.9)	3.90	57.3 (1.0)	
	<i>4</i> 0	95.0/5.0	61.4 (423)	` '	) 164.9 (73.8)		228.5 (4.0)	
	טּּּ	75.075.0	01 (120)	:	, 10.15 (15.6)			
		125E/HFC	-263fb					
		5.0/95.0	31.7 (219)	124.2 (856)	155.0 (68.3)	3.54	134.2 (2.4)	
	,	95.0/5.0	72.6 (501)	268.6 (1852	2) 161.3 (71.8)	3.10	248.1 (4.4)	
	45						•	
		125E/HFC				:		· ;•
		5.0/95.0	20.1 (139)	82.4 (568)	· · · · · · · · · · · · · · · · · · ·		• •	1.
		95.0/5.0	67.4 (465)	255.6 (1762	2) 162.3 (72.4)	3.16	240.8 (4.2)	ļ.
•	50	125E/HFC	2-272ea			. •		!
		5.0/95.0	11.8 (81)	54.9 (379)	) 170.0 (76.7)	3.90	64.1 (1.1)	1
								•
· .			•	·	•		·	
								i
	·. ·· .			•				;
								1

5	95.0/5.0	61.1 (421)	244.5 (1686)	165.1 (73.9)	3.17	229.2 (4.0)
	125E/HFC-27	2fb				
	5.0/95.0	15.0 (103)	67.4 (465)	168.1 (75.6)	3.83	78.0 (1.4)
	95.0/5.0	64.3 (443)	250.4 (1726)	163.8 (73.2)	3.17	235.5 (4.1)
10	105E /UEC 28	140				
	125E/HFC-28 5.0/95.0	27.4 (189)	107.9 (744)	167.8 (75.4)	3.71	124.5 (2.2)
	95.0/5.0	69.1 (476)	258.2 (1780)	162.3 (72.4)	3.16	244.6 (4.3)
	•	•	, ,			
15	125E/HFC-28		00.0 (610)	160 0 /76 1)	3.75	103.6 (1.8)
	5.0/95.0	21.5 (148)	89.8 (619) 252.4 (1740)	169.0 (76.1) 162.9 (72.7)	3.19	240.1 (4.2)
	95.0/5.0	66.4 (458)	232.4 (1740)	102.9 (72.7)	3.19	240.1 (4.2)
	134E/HFC-22					1045(04)
20	5.0/95.0	35.9 (248)	141.5 (976)	143.9 (62.2)	3.23	134.7 (2.4)
	7.3/92.7	36.0 (248)	141.7 (977)	144.5 (62.5)	3.24	135.5 (2.4)
	95.0/5.0	16.7 (115)	79.1 (545)	173.0 (78.3)	3.82	89.3 (1.6)
•	134E/HFC-2	36fa				
25	14.2/85.8	21.2 (146)	91.1 (628)	148.6 (64.8)	3.50	94.3 (1.7)
	5.0/95.0	20.6 (142)	88.6 (611)	146.3 (63.5)	3.48	91.1 (1.6)
	95.0/5.0	15.7 (108)	75.9 (523)	174.0 (78.9)	3.74	83.5 (1.5)
	134E/HFC-2	54eb				
30	28.6/71.4	19.0 (131)	82.9 (572)	159.2 (70.7)	3.64	90.4 (1.6)
	5.0/95.0	19.0 (131)	81.6 (563)	155.2 (68.4)	3.62	88.7 (1.6)
	95.0/5.0	15.5 (107)	74.9 (516)	174.5 (79.2)	3.73	82.2 (1.4)
•	134E/HFC-3	356mff				
35	97.1/2.9	15.1 (104)	73.5 (507)	174.4 (79.1)	3.73	80.6 (1.4)
	5.0/95.0	8.0 (55)	41.6 (287)	139.4 (59.7)	3.60	41.8 (0.7)
	95.0/5.0	15.1 (104)	73.4 (506)	173.4 (78.6)	3.72	80.4 (1.4)
	134aE/HFC	-32				
40		148.4 (1023)	506.8 (3494	) 199.1 (92.8)	3.15	511.8 (9.0)
	95.0/5.0	51.1 (352)	201.2 (1387	7) 167.8 (75.4)	3.56	216.6 (3.8)
•	55/45*	55.4(382)	227.7(1571)	153.7(67.6)	3.50	247.5(4.4)
	11.5/88.5*	77.6(535)	293.8(2027)	) 163.5(73.1)	3.48	328.8(5.8)
•	1/99*	78.9(544)	299.8(2068)	) 166.8(74.9)	3.49	337.2(5.9)
45						
	* Condense:	r temp. 90°F, e	vaporator tem	p. 10°F, and retu	ırn gas te	emp. 30°F
	134aE/HFC	C-125				
	5.0/95.0	113.6 (783)	382.2 (263	•	2.80	325.1 (5.7)
50		44.6 (308)	1	9) 164.7 (73.7)	3.45	185.2 (3.3)

	5	134aE/HFC-	134				-	•	1
		99.0/1.0	41.8 (288)	167.7 (1156)	164.1 (73.4)	3.45	174.7 (3.1)		:
		42.6/57.4	42.9 (296)	•	174.1 (78.9)	3.53	185.8 (3.3)		î
		1.0/99.0	42.2 (291)	169.6 (1169)	•	3.59	188.7 (3.3)		٠,
			,	(/	(2227)				i I.
	10	134aE/HFC	-134a						
		5.0/95.0	53.9 (372)	212.0 (1462)	170.8 (77.1)	3.42	221.2 (3.9)		
		95.0/5.0	42.4 (292)	170.1 (1173)	164.5 (73.6)	3.44	176.8 (3.1)		•
		•			- ,			•	
		134aE/HFC			·-····································		*		
	15	5.0/95.0	16.7 (115)	• •	192.5 (89.2)	3.81	87.9 (1.5)		
		95.0/5.0	38.9 (268)	158.7 (1094)	166.0 (74.4)	3.48	166.8 (2.9)		
		101 7 17770							
		134aE/HFC		2(1.2 (0.404)	0160 (100 5)		201.0 (6.5)		
	20	5.0/95.0	108.7 (749)	, ,	216.8 (102.7)	3.20	381.9 (6.7)	•	
	20	95.0/5.0	45.2 (312)	179.7 (1239)	166.9 (74.9)	3.46	188.3 (3.3)		
		134aE/HFC	-152		•				
		99/1	41.9(289)	168.2(1160)	164.5(73.6)	3.45	175.3(3.1)		
		19.1/80.9	50.0(345)	191.4(1160)	197.6(73.6)	3.59	218.2(3.1)		
	25	1/99	50.8(350)	193.2(1320)	•	3.61	223.3(2.8)		•
							(332)		
		134aE/HFC	-152a						
		5.0/95.0	50.6 (349)	192.8 (1329)	202.5 (94.7)	3.60	222.3 (3.9)		
		95.0/5.0	42.7 (294)		166.4 (74.7)	3.46	178.8 (3.1)		
	30	99/1	41.9 (289)		164.5 (73.6)	3.45	175.3 (3.1)		
		19.1/80.9	50.0 (345)		197.6 (73.6)	<b>3.5</b> 9	218.2 (3.1)		•.
		1/99	50.8 (351)	193.2 (1321)	203.8 (92.0)	3.61	223.3 (2.8)		
		12/oF/UE/	7 161						
•	35	134aE/HFC 5.0/95.0	79.0 (545)	277 9 (1015)	200.1 (93.4)	2.40	2127 (55)		
	33	95.0/5.0	45.5 (314)	•	167.6 (75.3)	3.49 3.45	313.7 (5.5) 189.2 (3.3)		•
		22.0/2.0	13.3 (311)	100.0 (1245)	107.0 (75.5)	J.7J	107.2 (3.3)		
	*.	134aE/HFC	C-227 <b>c</b> a						
		5.0/95.0	37.8 (261)	148.1 (1021)	143.9 (62.2)	3.21	140.0 (2.5)		
	40	95.0/5.0	42.4 (292)	•	163.1 (72.8)	3.42	175.0 (3.1)		
•	•	99/1	41.9(289)	167.9(1158)	•	3.44	174.5(3.1)		
	•	65.5/34.5	44.7(308)	174.0(1200)		3.33	173.9(3.1)		
		1/99	36.8(253)	143.8(992)	142.8(61.6)	3.21	136.1(2.4)		
		10 mg - 10 mg	·				•		Ī
	45	134aE/HF0							1
		5.0/95.0	36.9 (254)	145.3 (1002		3.22	137.7 (2.4)		i
•		95.0/5.0	42.2 (291)	169.3 (1167	, , ,	3.42	174.5 (3.1)		; ;.
		99/1	41.7 (288)		(i) 163.7 (73.2)	3.45	174.2 (3.1)		
	. <b>E</b> O	65.4/34.6	39.7 (274)	•	130 8 (50.0)	3.37	161.3 (2.8)		:
	50	1/99	28.6 (198)	123.6 (853)	139.8 (59.9)	3.22	114.2 (2.0)		!
	•	-	•					•	
							.•		į
	•	•							·  -
			:			_			<b>.</b> :
						•			;
		·							1

5	134aE/HFC-	-236ca	-			
	5.0/95.0	14.2 (98)	66.5 (459)	152.1 (66.7)	3.65	70.6 (1.2)
	95.0/5.0	39.7 (274)	161.4 (1113)	163.9 (73.3)	3.45	167.8 (3.0)
	134aE/HFC	-236cb				
10	5.0/95.0	19.5 (134)	84.6 (583)	146.6 (63.7)	3.52	87.9 (1.5)
	95.0/5.0	40.7 (281)	164.0 (1131)	163.2 (72.9)	3.45	170.5 (3.0)
	134aE/HFC	-236fa				
	5.0/95.0	21.4 (148)	91.6 (632)	146.3 (63.5)	3.49	94.4 (1.7)
15	95.0/5.0	41.0 (283)	165.1 (1138)	163.3 (72.9)	3.43	170.8 (3.0)
	134aE/HFC	-245ca				
	5.0/95.0	7.9 (54)	40.9 (282)	158.2 (70.1)	3.84	45.0 (0.8)
	95.0/5.0	36.8 (254)	154.9 (1068)	165.7 (74.3)	3.45	159.8 (2.8)
20						
	134aE/HFC					
	5.0/95.0	36.6 (252)	139.3 (960)	140.1 (60.1)	3.31	138.5 (2.4)
	95.0/5.0	41.7 (288)	166.7 (1149)	` '	3.44	173.1 (3.0)
	99/1	41.8 (288)	167.4 (1155)	•	3.45	174.2 (3.1)
25	57.7/42.3	40.4 (279)	157.8 (1089)	•	3.39	161.0 (2.8)
	1/99	36.3 (251)	137.6 (949)	139.2 (59.6)	3.31	136.6 (2.4)
	134aE/HFC					
	5.0/95.0	7.9 (54)	41.5 (286)	163.0 (72.8)	3.86	45.6 (0.8)
30	95.0/5.0	36.7 (253)	155.2 (1070)	166.1 (74.5)	3.44	159.4 (2.8)
	134aE/HF0	C-245fa				
	5.0/95.0	12.1 (83)	57.8 (399)	155.4 (68.6)	3.71	62.4 (1.1)
	95.0/5.0	38.7 (267)	158.9 (1096)	164.3 (73.5)	3.46	165.4 (2.9)
35	404.17/1977	0.054				
	134aE/HF0		20.0 (260)	161 4 /71 0\	2 06	42.2 (0.9)
	5.0/95.0	7.6 (52)	39.0 (269)	•	3.86	•
	95.0/5.0	35.9 (248)	152.6 (1052)	166.3 (74.6)	3.45	157.1 (2.8)
40	134aE/HF	C-254cb				
	5.0/95.0	19.4 (134)	83.1 (573)	155.0 (68.3)	3.63	90.6 (1.6)
	95.0/5.0	39.9 (275)	161.5 (1114	) 163.8 (73.2)	3.46	168.3 (3.0)
•	134aE/HF	C-254eb	•			
45	5.0/95.0	19.7 (136)	84.3 (581)	154.9 (68.3)	3.63	91.9 (1.6)
	95.0/5.0	39.9 (275)	161.6 (1114	) 163.7 (73.2)	3.46	168.6 (3.0)
	134aE/HF	C-263ca				
	5.0/95.0	10.1 (70)	48.0 (331)	162.5 (72.5)	3.81	54.1 (1.0)
50	95.0/5.0	36.8 (254)	153.7 (1060	) 165.4 (74.1)	3.47	160.0 (2.8)

5	134aE/HFC	-263fb				
	5.0/95.0		121.9 (840)	155.2 (68.4)	3.53	131.3 (2.3)
	95.0/5.0	41.0 (283)	164.5 (1134)	163.4 (73.0)	3.45	171.7 (3.0)
	134aE/HFC	-272ca				
10	5.0/95.0		80.7 (556)	160.8 (71.6)	3.71	91.9 (1.6)
	95.0/5.0	39.1 (270)	158.4 (1092)	164.0 (73.3)	3.48	166.7 (2.9)
	134aE/HFC					
	5.0/95.0	11.3 (78)	53.6 (370)	171.0 (77.2)	3.82	•
15	95.0/5.0	36.7 (253)	153.2 (1056)	165.8 (74.3)	3.48	160.0 (2.8)
	134aE/HFC					
	5.0/95.0	14.6 (101)	66.0 (455)	` . <i>*</i>	3.77	75.0 (1.3)
	95.0/5.0	38.0 (262)	155.9 (1075)	165.0 (73.9)	3.49	163.7 (2.9)
20	134aE/HFC	281ea				
	5.0/95.0	26.9 (185)	106.3 (733)	168.0 (75.6)	3.69	122.1 (2.1)
	95.0/5.0	39.9 (275)	160.4 (1106)	•	3.49	169.2 (3.0)
	·		• •	, ,		
25	134aE/HF0		. 00 4 (610)	160 5 (76 1)	2 77	101 0 (1 9)
	5.0/95.0	21.1 (145)	88.4 (610)	169.5 (76.4)	3.72	101.0 (1.8)
	95.0/5.0	38.9 (268)	157.8 (1088)	164.7 (73.7)	3.49	166.1 (2.9)
	143aE/HF0		5045 (0400)	400 4 (00 0)	2.16	
30	5.0/95.0	147.8 (1019)	504.7 (3480)	•	3.16	510.9 (9.0)
	95.0/5.0	55.7 (384)	211.3 (1457)		3.55	230.2 (4.1)
	54/46	106.8(736)	385.7(2661)		3.25	391.0(6.9)
	6.2/93.8	147.5(1017)	502.7(3468)	•	3.17	509.9(9.0)
	1/99	149.2(1029)	509.7(3516)	200.0(93.3)	3.16	518.0(9.1)
35	143aE/HF	C-125				
	5.0/95.0	115.3 (795)	385.6 (2659)	170.2 (76.8)	2.80	328.3 (5.8)
	95.0/5.0	50.6 (349)	193.4 (1333)		3.47	205.8 (3.6)
40	143aE/HF	C-134		·. · · · · · · · · · · · · · · · · · ·		
	99.0/1.0	47.9 (33)	183.8 (1267	) 167.2 (75.1)	3.48	196.1 (3.4)
	92.4/7.6	47.6 (328)	183.3 (1264		3.48	196.1 (3.4)
	1.0/99.0	42.2 (291)	169.8 (1171	•	3.59	188.9 (3.3)
45	143aE/HF	C-134a				
	5.0/95.0	54.1 (373)	212.3 (1464	170.8 (77.1)	3.43	222.0 (3.9)
	95.0/5.0	48.2 (332)	185.2 (1277		3.47	197.2 (3.5)
		•	•			

5	143aE/HFC	-143				
	5.0/95.0	16.9 (117)	75.7 (522)	192.3 (89.1)	3.83	89.1 (1.6)
	95.0/5.0	44.4 (306)	174.1 (1200)	168.9 (76.1)	3.50	186.8 (3.3)
	143aE/HFC	-143a				
10	5.0/95.0	108.8 (750)	361.8 (2495)	216.8 (102.7)	3.20	380.8 (6.7)
10	95.0/5.0	50.5 (348)	194.6 (1342)	170.2 (76.8)	3.44	205.2 (3.6)
	53/47	77.4(534)	275.0(1897)	189.0(87.2)	3.37	292.4(5.1)
	•		•			• •
	8.7/91.3*	106.8(736)	355.5(2453)	214.0(101.1)	3.23	376.8(6.6)
	1/99*	111.7(770)	368.5(2542)	219.1(103.9)	3.19	388.4(6.8)
15	*subcool ten	np. 20°F	,			
	143aE/HFC	2-152a				
	5.0/95.0	50.6 (349)	192.7 (1329)	202.5 (94.7)	3.60	222.4 (3.9)
20	95.0/5.0	48.0 (331)	184.2 (1270)	169.1 (76.2)	3.49	197.7 (3.5)
	99/1	47.9(330)	183.9(1268)	167.5(75.3)	3.47	196.4(3.5)
•	48.6/51.4	49.2(339)	188.3(1299)	186.9(86.1)	3.57	211.2(3.7)
	1/99	50.8(350)	193.2(1333)	203.8(95.4)	3.61	223.3(3.9)
	1/33	30.0(330)	175.2(1555)	203.8(33.4)	. 5.01	223.3(3.3)
25	143aE/HFC	C-161				
	5.0/95.0	78.9 (544)	277.6 (1914)	200.3 (93.5)	3.48	313.1 (5.5)
	95.0/5.0	50.7 (350)	193.7 (1336)	170.0 (76.7)	3.47	206.7 (3.6)
	143aE/HFC	C-227ca				
30	5.0/95.0	38.6 (266)	150.9 (1040)	144.4 (62.4)	3,22	143.0 (2.5)
	95.0/5.0	48.5 (334)	186.0 (1282)		3.45	196.5 (3.5)
	99/1	48.0(331)	184.3(1271)	` '	3.47	196.1(3.5)
	71.5/28.5	50.6(349)	190.7(1315)	•	3.37	195.4(3.4)
	1/99	36.9(254)	144.6(997)	142.9(161)	3.21	136.7(2.4)
35	-1/5	2013 (2017)	21110(227)	1.20(101)	0.21	10017 (21.1)
	143aE/HF0	C-227ea				
•	5.0/95.0	37.8 (261)	148.3 (1022)	144.4 (62.4)	3.23	141.0 (2.5)
	95.0/5.0	48.5 (334)	185.9 (1282)	•	3.45	196.5 (3.5)
	99/1	48.0(331)	184.3(1271)	` '	3.47	196.1(3.5)
40	•	50.5(348)	190.4(1313)	• •		` '
40	•		•	•	3.39	196.3(3.5)
	1/99	36.9(254)	144.6(997)	142.6(61.4)	3.21	136.7(2.4)
	143aE/HF					
	5.0/95.0	14.6 (101)	•	,	3.67	73.2 (1.3)
45	95.0/5.0	45.7 (315)	178.3 (1229)	) 167.1 (75.1)	3.47	188.9 (3.3)
	143aE/HF	C-236cb				
	5.0/95.0	19.9 (137)	86.2 (594)	146.9 (63.8)	3.54	90.2 (1.6)
	95.0/5.0	46.7 (322)	180.6 (1245	•	3.46	191.2 (3.4)
50	143aE/HF	C-236fa				
	143aE/TI	C-2501a				

	5	5.0/95.0	22.0 (152)		146.6 (63.7)	3.51	97.2 (1.7)
		95.0/5.0	47.1 (325)	181.6 (1252)	166.3 (74.6)	3.46	192.4 (3.4)
		143aE/HFC-2	245ca				
		•		42.2 (202)	158.4 (70.2)	3.88	47.0 (0.8)
•		5.0/95.0	8.3 (57)	42.3 (292)	•		• •
	10	95.0/5.0	42.6 (294)	171.3 (1181)	168.8 (76.0)	3.46	180.3 (3.2)
•		143aE/HFC-2	245cb				
		5.0/95.0	37.2 (256)	140.9 (971)	140.3 (60.2)	3.32	140.7 (2.5)
		95.0/5.0	47.7 (329)	182.8 (1260)	165.7 (74.3)	3.47	194.2 (3.4)
	15	99/1	48.0(331)	184.3(1271)	166.9(73.3)	3.47	196.1(3.5)
•	13	•	50.9(351)	190.6(1315)	157.7(69.8)	3.33	192.1(3.4)
		59.6/40.4		169.4(1168)	148.5(64.7)	3.25	163.3(2.9)
		20/80	44.3(305)	103.4(1100)	146.5(04.7)	<b>3.2</b> 3	103.3(2.9)
		143aE/HFC-2	245ea				
	20	5.0/95.0	8.2 (57)	42.7 (294)	163.0 (72.8)	3.90	47.7 (0.8)
		95.0/5.0	42.3 (292)	171.3 (1181)	169.5 (76.4)	3.45	179.6 (3.2)
		143aE/HFC-	245fa				
		-	12.5 (86)	59.4 (410)	155.0 (68.3)	3.74	65.0 (1.1)
	05	5.0/95.0	• •	175.4 (1209)	` '	3.48	186.2 (3.3)
	25	95.0/5.0	44.6 (308)	173.4 (1209)	107.5 (75.5)	3.40	100.2 (3.3)
		143aE/HFC-			·		
		5.0/95.0	7.8 (54)	40.1 (276)	161.5 (71.9)	3.90	45.1 (0.8)
		95.0/5.0	41.5 (286)	168.9 (1165)	169.6 (76.4)	3.45	177.1 (3.1)
	30	•					
		143aE/HFC-	-254cb				
		5.0/95.0	19.7 (136)	84.3 (581)	155.3 (68.5)	3.64	92.3 (1.6)
		95.0/5.0	45.9 (316)	177.8 (1226)	166.8 (74.9)	3.48	189.6 (3.3)
	35	143aE/HFC	-254eb				
	55	5.0/95.0	20.1 (139)	85.6 (590)	155.2 (68.4)	3.63	93.6 (1.6)
		95.0/5.0	45.9 (31.6)	177.9 (1227)		3.48	189.9 (3.3)
·		. 93.0/3.0	43.7 (31.0)	177.5 (1227)	100.7 (71.0)	5.10	103.5 (5.5)
· · · · ·		143aE/HFC	-263ca	• •	•	٠.	•
	40	5.0/95.0	10.3 (71)	48.9 (337)	162.6 (72.6)	3.83	55.6 (1.0)
		95.0/5.0	42.4 (292)	169.7 (1170)	•	3.48	179.9 (3.2)
		93.0/3.0	42.4 ( <i>L)L)</i>	105.7 (1170)	, 100.7 (12.7)	5.10	177.5 (0.2)
		143aE/HFC	C-263fb				
		5.0/95.0	31.3 (216)	122.9 (847)	155.4 (68.6)	3.53	132.5 (2.3)
•	45	95.0/5.0	46.9 (323)	180.3 (1243	) 166.4 (74.7)	3.48	192.4 (3.4)
		143aE/HFC	C-272ca				
•		5.0/95.0	19.9 (137)	81.6 (563)	160.9 (71.6)	3.71	93.1 (1.6)
		•	, , ,	` '	, ,		•
	<b></b>	95.0/5.0	44.9 (310)	174.3 (1202	2) 167.0 (75.0)	2.30	187.2 (3.3)
	50		2.050				
•		143aE/HF0	J-2/2ea				

5	5.0/95.0	11.5 (79)	54.3 (374)	171.0 (77.2)	3.84	62.3 (1.1)
	95.0/5.0	42.2 (291)	168.9 (1165)	169.0 (76.1)	3.49	179.8 (3.2)
	•	•		,		
	143aE/HFC-	272fb	•			
	5.0/95.0	14.8 (102)	66.7 (460)	168.9 (76.1)	3.78	76.1 (1.3)
10	95.0/5.0	43.5 (300)	171.7 (1184)	168.1 (75.6)	3.50	183.7 (3.2)
	•					
	143aE/HFC-	281ea				
	5.0/95.0	27.0 (186)	106.7 (736)	168.2 (75.7)	3.69	122.5 (2.2)
	95.0/5.0	45.3 (312)	175.2 (1208)	167.3 (75.2)	3.51	188.6 (3.3)
15						
	143aE/HFC-					
	5.0/95.0	21.3 (147)	89.0 (614)	169.5 (76.4)	3.73	101.9 (1.8)
	95.0/5.0	44.4 (306)	173.1 (1193)	167.6 (75.3)	3.51	186.0 (3.3)
••		. 22				
20	C216E/HFC		FOF 2 (2(02)	107 4 (01 0)	2 20	<i>EEC</i> 2 (0.0)
	5.0/95.0*	156.5 (1079)	525.3 (3622)	•	3.30	556.2 (9.8)
	95.0/5.0	76.7 (529)	238.9 (1647)	150.5 (65.8)	3.15	252.8 (4.4)
	* - 60	bcool temperati	re of 20 0°E			
25	- su	ocoor temperati	11C Of 20.0 1			
25	C216E/HFC	<b>1-125</b>				
	5.0/95.0*	62.6 (432)	230.8 (1591)	131.3 (55.2)	3.28	233.2 (4.1)
	95.0/95.0	58.8 (405)	` ,	141.0 (60.0)	2.95	182.0 (3.2)
	93.0/3.0	30.0 (403)	210.4 (1431)	141.0 (00.0)	2.75	102.0 (3.2)
30	* - 01/	aporator temper	rature of 10 0°	F condenser ten	nneratur	bac III 00 fo
30		urn gas of 30.0°F		r, condenser ten	претани	C OI 70.0 I and
	100	um bas or solo i			•	
•	C216E/HF0	C-134				
٠	99.0/1.0	60.2 (415)	217.4 (1499)	140.3 (61.2)	2.96	190.1 (3.3)
35	79.8/20.2	69.3 (478)	245.1 (1690)	• •	3.01	219.9 (3.9)
	1.0/99.0	43.1 (297)	174.9 (1206)	173.9 (78.8)	3.58	192.8 (3.4)
						,
	C216E/HF0	C-134a	•			
• • •	5.0/95.0	56.9 (392)	221.2 (1525)	,	3.41	229.8 (4.0)
40	95.0/5.0	59.5 (410)	212.8 (1467)	•	2.96	184.1 (3.2)
•	99/1	58.8(405)	196.4(1355)	•	3.24	189.3(3.3)
٠.	61.7/38.3	56.2(387)	202.3(1395)	•	2.93	•
	1/99	55.1(380)	215.3(1485)	170.5(76.9)	3.44	225.4(4.0)
		C 142		·		
45	C216E/HF		700/6/4	100 7 (07 1)	4 07	07 4 (4 7)
	5.0/95.0	18.2 (125)	• •	, ,	3.97	97.1 (1.7)
	95.0/5.0	54.8 (378)	196.7 (1356	) 141.2 (60.7)	3.01	174.1 (3.1)
	CO1 CO ITTO	C 1425				
50	C216E/HF		265 0 /0500	)\ 215 2 /101 0\	3.18	202 2 (6 7)
50	5.0/95.0*	110.9 (765)	303.8 (2322	2) 215.2 (101.8)	3.10	383.3 (6.7)

5	95.0/5.0	60.0 (414)	214.1 (1476)	143.2 (61.8)	2.99	188.0 (3.3)
	° = subc	ool temperatu	re of 20.0°F			
	C216E/HFC-1					
10	5.0/95.0	52.8 (364)	199.0 (1372)	201.0 (93.9)	3.61	230.2 (4.0)
	95.0/5.0	61.2 (422)	217.9 (1502)	143.5 (61.9)	2.98	190.9 (3.4)
	99/1	57.0(383)	203.5(1404)	193.0(59.4)	2.96	176.5(3.1)
	77.6/22.4	72.4(499)	250.0(1725)	155.0(68.3)	<b>3.0</b> 8	231.5(4.1)
	1/99	51.0(351)	195.0(1345)	204.3(95.7)	3.58	223.6(3.9)
15	•					
	C216E/HFC-1	161				
	5.0/95.0	81.6 (563)	284.8 (1964)	199.1 (92.8)	3.49	321.2 (5.6)
	95.0/5.0	66.8 (461)	237.7 (1639)	145.9 (63.3)	3.00	209.6 (3.7)
	99/1	58.4(403)	207.9(1434)	140.2(60.1)	2.99	182.2(3.2)
20	58.8/41.2	98.5(679)	325.5(2246)		3.13	315.7(5.6)
	1/99	80.2(553)	280.6(1936)	200.8(93.8)	3.50	318.0(5.6)
	C216E/HFC-2	22700				
	5.0/95.0	37.2 (256)	145 5 (1003)	142.5 (61.4)	3.19	136.5 (2.4)
25	95.0/5.0	54.3 (374)	•	139.2 (59.6)	2.95	169.6 (3.0)
2.5	75.075.0	31.0 (371)	170.0 (1881)		2.75	200.0 (0.0)
	C216E/HFC-	227ea				
	5.0/95.0	36.3 (250)	142.5 (983)	142.5 (61.4)	3.20	134.2 (2.4)
	95.0/5.0	54.1 (373)	195.6 (1349)	139.3 (59.6)	2.95	169.1 (3.0)
30	•	, ,	,			, ,
	C216E/HFC-	236ca				
	5.0/95.0	14.4 (99)	66.8 (461)	150.3 (65.7)	3.68	71.6 (1.3)
	95.0/5.0	51.3 (354)	189.2 (1304)	) 140.0 (60.0)	2.99	165.6 (2.9)
35	C216E/HFC	236ch			•	
33	5.0/95.0	19.4 (138)	84.3 (581)	145.2 (62.9)	3.52	87.3 (1.5)
	95.0/5.0	52.4 (361)	• • • • • • • • • • • • • • • • • • • •	) 139.5 (59.7)	2.98	167.0 (2.9)
	75.0/5.0	. (501)	2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2, 2	, 20,10 (0,11)		10/10 (21)
· 	C216E/HFC	-236fa				•
40	5.0/95.0	21.3 (147)	90.9 (627)	•	3.48	93.5 (1.6)
• • • •	95.0/5.0	52.5 (362)	191.7 (1322	2) 139.6 (59.8)	2.98	167.0 (2.9)
	CO16E /HEC	24500				•
	C216E/HFC 5.0/95.0	-243ca 8.4 (58)	42.2 (291)	156.5 (69.2)	3.96	48.1 (0.8)
45	95.0/5.0	48.0 (331)	• • •	` ,	2.99	159.9 (2.8)
70	<i>33.0/3.0</i>	40.0 (551)	105.5 (1200	), 111.5 (00.0)	2.,,,	107.7 (2.0)
`,	C216E/HFC	2-245cb				
	5.0/95.0	37.1 (256)	140.4 (968)	139.0 (59.4)	3.29	138.6 (2.4)
	95.0/5.0	54.8 (378)	` <i>,</i>	8) 139.0 (59.4)	2.95	170.5 (3.0)
50	•	55.5(382)	198.8(1371	139.0(59.4)	2.94	171.4(3.0)
	95.1/4.9	54.8(378)	197.0(1359	) 139.0(59.4)	2.95	170.6(3.0)
						•
	·		•			

PCT/US93/04614

5	1/99	36.3(253)	138(952)	139.0(59.4)	3.30	136.4(2.4)
	C216E/HFC-24	45ea				
	5.0/95.0	8.6 (59)	43.5 (300)	159.4 (70.8)	4.06	50.9 (0.9)
	95.0/5.0	49.2 (339)	185.9 (1282)	141.2 (60.7)	2.99	162.2 (2.9)
10	93.0/3.0	4722 (337)	105.7 (1202)	141.2 (00.7)	21,7,7	10212 (21)
10	C216E/HFC-2	45fa	•			•
	5.0/95.0	12.5 (86)	58.9 (406)	153.4 (67.4)	3.78	65.1 (1.1)
	95.0/5.0	50.6 (349)	187.8 (1295)	140.3 (60.2)	3.00	164.8 (2.9)
	33.0/3.0	50.0 (515)	107.0 (1255)	110.5 (00.2)	<b>D.100</b>	10 110 (21)
15	C216E/HFC-2	54ca				
	5.0/95.0	8.2 (57)	40.7 (281)	158.3 (70.2)	4.04	47.8 (0.8)
	95.0/5.0	47.7 (329)	182.5 (1258)	141.6 (60.9)	3.00	159.7 (2.8)
			•	,		
	C216E/HFC-2					
20	5.0/95.0	19.7 (136)	84.0 (579)	153.7 (67.6)	3.65	92.0 (1.6)
	95.0/5.0	52.4 (361)	190.9 (1316)	140.0 (60.0)	2.99	167.8 (2.9)
•	C216E/HFC-2	254eb				
	5.0/95.0	20.1 (139)	85.3 (588)	153.7 (67.6)	3.64	93.2 (1.6)
25	95.0/5.0	52.5 (362)	191.1 (1318)	•	3.00	168.3 (3.0)
25	22.0/2.0	02.0 (002)	->(->)	20000 (0000)		
	C216E/HFC-2	263ca				
	5.0/95.0	10.7 (74)	49.6 (342)	160.1 (71.2)	3.93	58.1 (1.0)
	95.0/5.0	49.1 (339)	183.8 (1267)	141.0 (60.6)	3.02	163.0 (2.9)
30						
	C216E/HFC-2		100 1 (051)	4540 (650)	2.50	120 5 (0.2)
	5.0/95.0	31.5 (217)	123.4 (851)	154.3 (67.9)	3.52	132.5 (2.3)
	95.0/5.0	54.4 (375)	195.5 (1348)	139.9 (59.9)	2.98	171.7 (3.0)
. 35	C216E/HFC-	272ca				
	5.0/95.0 (139)		82.2 (567)	159.6 (70.9)	3.74	94.4 (1.7)
	95.0/5.0 (361)		189.9 (1309)	140.2 (60.1)	3.02	169.1 (3.0)
• • •	C216E/HFC-			4650 (55.4)	4.00	(7 ( (1 0)
40	•	12.3 (85)	56.1 (387)	· · · · · · · · · · · · · · · · · · ·	4.00	67.6 (1.2)
	95.0/5.0	51.2 (353)	187.8 (1295)	) 140.8 (60.4)	3.03	167.4 (2.9)
	C216E/HFC	-272fb				
	5.0/95.0	15.5 (107)	68.4 (472)	166.5 (74.7)	3.89	80.6 (1.4)
45	•	52.6 (362)	190.9 (1316	•	3.02	169.7 (3.0)
	CO4 (T) // TTC	001				
	C216E/HFC		100 2 (747)	167.0 (75.0)	3.72	125.2 (2.2)
	5.0/95.0	27.6 (190)				
50	95.0/5.0	55.2 (381)	197.1 (1359	7 170.5 (00.3)	5.01	175.1 (5.1)
50						

5	C216E/HFC	7-281fa				
J	5.0/95.0	21.9 (151)	90.5 (624)	168.0 (75.6)	3.78	105.3 (1.9)
	95.0/5.0	54.2 (374)	194.5 (1341)	141.0 (60.6)	3.01	173.3 (3.1)
	33.073.0	5 (5 . 7)	( ( ( )	1.20 (00.0)		27010 (012)
	C-216E2/H	FC-32				
10	5.0/95.0	149.0 (1027)	508.2 (3504)	198.2 (92.3)	3.16	513.2 (9.0)
	36.0/64.0°	138.0 (951)	473.4 (3264)	184.7 (84.8)	3.21	475.3 (8.4)
	95.0/5.0	56.1 (387)	216.3 (1491)	141.9 (61.1)	3.25	204.7 (3.6)
•	·	·	·			
	* 20°F Subo	cool	,			
15	C 04 (T)0 /IX	TO 124				
	C-216E2/H		471 ( (4400)	100 0 (00 0)	2.50	100 ( (0.0)
	5.0/95.0	42.7 (294)	171.6 (1183)	180.0 (82.2)	3.58	189.6 (3.3)
	95.0/5.0	45.4 (313)	174.2 (1201)	136.2 (57.9)	3.11	159.2 (2.8)
	60.5/39.5	48.5 (334)	186.1 (1283)	152.3 (66.8)	3.34	186.6 (3.3)
20		70.404				
	C-216E2/H		0145 (1470)	1600 (760)	2.40	000 0 (0 0)
	5.0/95.0	54.8 (378)	214.5 (1479)	169.2 (76.2)	3.42	222.9 (3.9)
	20.7/79.4	55.5 (383)	214.9 (1482)	163.8 (73.2)	3.37	219.3 (3.9)
٥.	95.0/5.0	46.0 (317)	176.4 (1216)	135.9 (57.7)	3.11	160.9 (2.8)
25		DDC 142			•	
	C-216E2/H		740 (516)	100 0 (00 3)	2 02	001 (1 ()
	5.0/95.0	16.7 (115)	74.8 (516)	190.8 (88.2)	3.83	88.1 (1.6)
	87.1/12.9	36.4 (251)	146.7 (1011)	` ,	3.30	143.2 (2.5)
20	95.0/5.0	41.0 (283)	160.5 (1107)	137.0 (58.3)	3.18	149.8 (2.6)
30	C-216E2/H	IEC-152a				
	60.5/39.5	53.8 (371)	200.7 (1384)	164.6 (73.7)	3.42	210.7 (3.7)
	5.0/95.0	51.1 (352)	194.3 (1340)	` '	3.59	223.4 (3.9)
	95.0/5.0	46.7 (322)	178.4 (1230)	•	3.15	165.3 (2.9)
35	)3.0/ J.O <sub>.</sub>	10.7 (322)		130.2 (37.0)	5.15	105.5 (2.7)
	C-216E2/F	HFC-161	•			
	45.7/54.3	78.8 (543)	275.5 (1900)	178.6 (81.4)	3.39	294.1 (5.2)
	5.0/95.0	79.9 (551)	279.8 (1929)		3.49	315.6 (5.6)
	95.0/5.0	51.4 (354)	194.9 (1344)		3.17	182.1 (3.2)
40	33.073.0		=> .u> (== : ;)	, 2:0:: (00,2)	<b>3</b> ,12,	20212 (012)
	C-216E2/I	HFC-245cb				
	74.7/25.3	41.2 (284)	158.2 (1091)	135.3 (57.4)	3.16	147.4 (2.6)
	5.0/95.0	36.4 (251)	138.4 (954)		3.29	
	95.0/5.0	43.5 (300)	167.2 (1153)	•	3.09	151.5 (2.7)
45	,	· - /	<b>,</b> ,	, ( , , , , , , , , , , , , , , , , , ,		- (
	218E/HF0	C-32				•
	5.0/95.0*	155.2 (1070)	523.5 (3609	) 197.5 (91.9)	3.30	553.7 (9.7)
	95.0/5.0	69.2 (477)	•	,		227.1 (4.0)
				. ,		` '

\* = subcool temperature of 20.0°F

5	218E/HFC-1	.25				
	5.0/95.0	62.6 (432)	231.3 (1595)	131.4 (55.2)	3.28	233.0 (4.1)
	95.0/5.0	52.1 (359)	203.0 (1400)	140.0 (60.0)	2.83	162.4 (2.9)
	218E/HFC-1	134				
10	99.0/1.0	49.1 (339)	192.4 (1327)	138.2 (59.0)	2.80	152.6 (2.7)
	63.3/36.7	63.7 (439)	235.1 (1621)	153.2 (67.3)	3.04	211.5 (3.7)
	35.0/65.0	54.8 (378)	213.6 (1473)	167.0 (75.0)	3.34	215.8 (3.8)
	5.0/95.0	44.6 (308)	177.3 (1222)	179.4 (81.9)	3.62	198.5 (3.5)
15	218E/HFC-	134a				
	5.0/95.0	56.5 (390)	220.5 (1520)	169.5 (76.4)	3.41	228.9 (4.0)
	95.0/5.0	52.8 (364)	205.7 (1418)	140.4 (60.2)	2.82	164.4 (2.9)
	99/1	49.3(340)	192.8(1330)	138.0(53.3)	2.81	153.4(2.7)
	53.0/47.0	70.4(485)	258.8(1785)	154.2(67.9)	3.00	228.7(4.0)
20	1/99	55.0(379)	215.4(1486)	170.6(77.0)	3.43	225.2(4.0)
	218E/HFC-					
	5.0/95.0	17.9 (123)	78.1 (538)	189.2 (87.3)	3.95	95.3 (1.7)
25	95.0/5.0	48.1 (332)	187.0 (1289)	139.8 (60.0)	2.90	155.0 (2.7)
2.5	218E/HFC-	143a				
	5.0/95.0*	110.8 (764)	366.5 (2527)	215.4 (101.9)	3.18	383.2 (6.7)
	95.0/5.0	53.6 (370)	207.7 (1432)	· · · · · · · · · · · · · · · · · · ·	2.86	169.4 (3.0)
30	* = sı	ıbcool temperat	ure of 20.0°F			
	218E/HFC-	·152a				
	5.0/95.0	52.5 (362)	198.6 (1369)	201.1 (93.9)	3.61	229.5 (4.0)
	95.0/5.0	54.8 (378)	211.7 (1460)	` '	2.85	172.0 (3.0)
35	99/1	49.8(343)	194.4(1341)	•	2.82	155.5(2.7)
	68.2/31.8	69.8(481)	250.5(1728)	•	3.12	234.9(4.1)
	41/59	63.1(435)	232.3(1602)	•	3.42	247.4(4.4)
	218E/HFC	-161				
40	5.0/95.0	81.5 (562)	284.7 (1963)	199.2 (92.9)	3.49	321.1 (5.7)
•	95.0/5.0*	61.1 (421)	236.0 (1627)	146.0 (63.3)	3.05	204.6 (3.6)
	84/16*	88.3 (609)	275.7 (1907)	146.6 (63.7)	3.74	310.2 (5.5)
	62.6/37.4	97.7(674)	329.2(2271)	169.3(76.3)	3.04	307.5(5.4)
	39/61	92.2(636)	315.8(2179)	183.2(84.0)	3.30	329.2(5.8)
45	* = s	subcool tempera	ture of 20.0°F			
		<u>-</u>			-	
	218E/HFC		4447 (000)	140 4 (// 5)		488845
50	5.0/95.0	36.8 (254)	144.7 (998)	•	3.18	135.2 (2.4)
50	95.0/5.0	47.3 (326)	185.9 (1282	) 137.8 (58.8)	2.82	148.1 (2.6)

5	218E/HFC-2	227ea				
J	5.0/95.0	35.0 (248)	141.8 (978)	142.4 (61.3)	3.20	133.2 (2.3)
	95.0/5.0	47.3 (326)	` '	137.7 (58.7)	2.83	149.0 (2.6)
	93.0/3.0	47.5 (520)	105.7 (1200)	157.7 (56.7)	<b>4.</b> 03	147.0 (2.0)
	218E/HFC-2	236ca				-
10	5.0/95.0	14.0 (97)	65.7 (453)	150.3 (65.7)	3.65	69.8 (1.2)
	95.0/5.0	44.3 (305)	178.3 (1229)	138.3 (59.1)	2.88	145.4 (2.6)
	218E/HFC-	236cb				
	5.0/95.0	19.1 (132)	83.0 (572)	145.0 (62.8)	3.51	85.7 (1.5)
15	95.0/5.0	45.1 (311)	179.8 (1240)	138.0 (58.9)	2.87	146.2 (2.6)
	218E/HFC-	236fa				
	5.0/95.0	21.0 (145)	89.8 (619)	144.7 (626)	3.47	92.0 (1.6)
	95.0/5.0	45.4 (313)	180.8 (1247)	138.0 (58.9)	2.86	146.6 (2.6)
20	93.0/3.0	43.4 (313)	100.0 (1247)	130.0 (30.3)	2.00	140.0 (2.0)
	218E/HFC-	245ca				
·	5.0/95.0	8.1 (56)	41.2 (284)	156.0 (68.9)	3.91	56.8 (1.0)
	95.0/5.0	41.2 (284)	172.2 (1187)	139.5 (59.7)	2.90	140.4 (2.5)
25	218E/HFC-	-245cb				
	5.0/95.0	36.8 (254)	139.7 (963)	138.9 (59.3)	3.29	137.6 (2.4)
	95.0/5.0	47.9 (330)	187.1 (1290)	137.5 (58.6)	2.83	150.4 (2.6)
	218E/HFC	-245ea				
30	5.0/95.0	8.2 (57)	42.5 (293)	160.1 (71.2)	3.99	48.5 (0.9)
	95.0/5.0	42.3 (292)	174.7 (1205)	•	2.89	142.4 (2.5)
	218E/HFC	-245fa				
	5.0/95.0	12.2 (84)	58.0 (400)	153.6 (67.6)	3.74	63.2 (1.1)
35	95.0/5.0	43.8 (302)	176.8 (1219)	•	2.90	145.0 (2.6)
	218E/HFC	`-254ca		•		
· ···	5.0/95.0	7.9 (54)	39.8 (274)	159.0 (70.6)	3.97	45.6 (0.8)
	95.0/5.0	40.9 (282)	171.0 (1179)		2.91	140.4 (2.5)
40	75.075.0	10.5 (202)	27210 (2217)	20010 (0010)		2 (30) (20)
.40	218E/HFC	`-254cb				
	5.0/95.0	19.4 (134)	83.1 (573)	153.7 (67.6)	3.63	90.5 (1.6)
	95.0/5.0	45.4 (313)	180.1 (1242)	•	2.89	148.0 (2.6)
45	218E/HF(	3-254eh			•	
43	5.0/95.0	19.8 (137)	84.3 (581)	153.5 (67.5)	3.63	91.9 (1.6)
	95.0/5.0	45.5 (314)	180.2 (1242)	•	2.89	148.2 (2.6)
	218E/HF0	~-263ca	·			
50	5.0/95.0	10.4 (72)	48.9 (337)	160.5 (71.4)	3.89	56.4 (1.0)
JU	•	42.5 (293)	172.6 (1190	` '	2.94	144.0 (2.5)
	95.0/5.0	42.3 (293)	112.0 (1190	7 133.0 (33.4)	2.74	177.0 (2.3)

5						
	218E/HFC-26	3fb				
	5.0/95.0	31.2 (215)	122.8 (847)	154.2 (67.9)	3.52	131.5 (2.3)
	95.0/5.0	47.6 (328)	185.8 (1281)	138.4 (59.1)	2.87	151.8 (2.7)
	99/1	48.2(332)	188.7(1302)	137.7(58.7)	2.81	150.2(2.6)
10	96.3/3.7	47.8(329)	186.9(1289)	138.2(59.0)	2.85	151.3(2.7)
	1/99	27.9(192)	120.6(832)	155.5(68.6)	3.26	116.9(2.1)
		_,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	12010(002)	155.5(00.0)	5.20	110.5(2.1)
	218E/HFC-27	2ca				
	5.0/95.0	19.9 (137)	81.5 (562)	159.6 (70.9)	3.73	93.3 (1.6)
15	95.0/5.0	45.8 (316)	179.7 (1239)	138.7 (59.3)	2.92	150.1 (2.6)
	70.0700	.0.0 (0.20)	1,51, (125)	150.7 (55.5)	2.72	150.1 (2.0)
	218E/HFC-27	2ea				
	5.0/95.0	12.0 (83)	55.6 (383)	168.4 (75.8)	3.96	65.9 (1.2)
	95.0/5.0	44.5 (307)	177.2 (1222)	139.2 (59.6)	2.93	148.3 (2.6)
20	·	` ,	` ,	(= 1 1 1 )		
	218E/HFC-27	2fb				
	5.0/95.0	15.2(105)	67.7(467)	167.0(75.0)	3.86	78.9(1.4)
	95.0/5.0	45.9(316)	180.6(1245)	139.0(59.4)	2.91	150.5(2.6)
25	218E/HFC-28					
	5.0/95.0	27.4(189)	107.9(744)	167.0(75.0)	3.71	124.4(2.2)
	95.0/5.0	48.6(335)	187.8(1295)	139.6(59.8)	2.91	156.6(2.8)
	218E/HFC-28	l fo				
30	5.0/95.0	21.6(149)	90.0(621)	160 2/75 7\	2.76	1041/10)
30	95.0/5.0	47.7(329)	185.3(1278)	168.3(75.7)	3.76	104.1(1.8)
	75.075.0	41.7(323)	103.3(12/6)	139.6(59.8)	2.91	154.7(2.7)
	218E2/HFC-3	32				-
	5.0/95.0	151.9 (1047)	516.9 (3564)	198.0 (92.2)	2.93	484.2 (8.5)
35	95.0/5.0	48.6 (335)	211.8 (1460)	` '	3.43	197.4 (3.5)
		(332)		2.005 (00.5)	5.15	177.4 (3.3)
	218E2/HFC-1	125				
	5.0/95.0*	60.8 (419)	228.6 (1576)	131.8 (55.4)	3.26	228.5 (4.0)
•	95.0/5.0	34.1 (235)	150.5 (1038)	` ,	2.97	123.1 (2.2)
40				10113 (55.5)	2.,,	123.1 (2.2)
	* = evapor	ator temperati	ire of 10 0°F c	ondenser temp	arotura o	f 00 0°E and
•	return g	as of 30.0°F		ondenser temp	crature o	90.0 F, and
			·			
	218E2/HFC-	134				
45	95.0/5.0	33.1 (228)	145.8 (1005)	132.1 (55.6)	2.94	118.9 (2.1)
	79.0/21.0	40.1 (276)	169.2 (1167)	` '	3.06	147.0 (2.6)
	46.1/53.9	46.5 (321)	•	156.6 (69.2)	3.32	183.0 (3.2)
	1.0/99.0	42.2 (291)	170.2 (1173)	, ,	3.58	188.8 (3.3)
		•	,	<b>\</b>		(2.00)
50	218E2/HFC-	134a				

5	5.0/95.0 95.0/5.0 72/28	54.9 (379) 33.6 (232) 45.8(316)	215.4 (1485) 148.2 (1022) 189.8(1309)	169.0 (76.1) 132.0 (55.6) 143.0(61.7)	3.40 2.94 3.07	222.7 (3.9) 120.7 (2.1) 166.1(2.9)
	24.7/75.3 1/99	55.8(385) 54.6(376)	217.6(1501) 214.3(1478)	161.1(71.7) 170.6(77.0)	3.30 3.42	215.6(3.8) 223.5(3.9)
10	218E2/HFC-	-143		, ,		
	5.0/95.0 95.0/5.0	16.6 (114) 30.2 (208)	174.7 (515) 133.2 (918)	190.6 (88.1) 131.8 (55.4)	3.82 2.99	187.7 (1.5) 111.2 (2.0)
15	218E2/HFC	-143a				
	5.0/9 <b>5.</b> 0° 95.0/5.0	108.9 (751) 35.3 (243)	363.2 (1067) 154.7 (1344)	<b>,</b> ,	3.18 3.02	379.1 (2.3) 129.2 (3.9)
	* = su	bcool temperati	ure of 20.0°F			
20	219E2/UEC	1520				
	218E2/HFC 5.0/95.0	51.3 (354)	194.9 (1344)	200.9 (93.8)	3.59	223.9 (3.9)
	95.0/5.0	35.1 (242)	153.1 (1056)	134.5 (56.9)	2.99	127.5 (2.2)
	81/19	45.1(311)	183.9(1268)	146.7(63.7)	3.16	167.7(3.0)
25	51.0/49.0	53.4(368)	203.8(1406)	168.7(75.9)	3.38	210.6(3.7)
	1/99	50.9(351)	193.6(1335)	203.6(95.3)	3.60	223.5(3.9)
	218E2/HFC	2-161				
	5.0/95.0	80.2 (553)	281.3 (1940)	•	3.48	315.9 (5.6)
30	95.0/5.0	39.9 (275)	173.8 (1198)		3.05	147.2 (2.6)
	78/22	63.2(436)	246.7(1702)		3.11	224.5(4.0)
	46.4/53.6	81.0(558)	285.4(1969)	•	3.30	293.3(5.2)
•	1/99	79.9(551)	280.0(1932)	200.8(93.8)	3.49	316.7(5.6)
35	218E2/HFC					
	5.0/95.0	36.0 (248)	142.5 (983)	142.0 (61.1)	3.19	133.1 (2.3)
-	95.0/5.0°	30.6 (211)	135.4 (934)	134.3 (56.8)	2.85	107.3 (1.9)
	* = retur	n gas temperati	are = 70.0°F.			
40	01000 /115	2 227	-	•		
	218E2/HF0 5.0/95.0	35.2 (243)	139.7 (963)	142.0 (61.1)	3.20	131.1 (2.3)
	95.0/5.0°	• •	, ,	•		•
•	95.0/5.0	30.5 (210)	135.2 (932)	134.3 (56.8)	2.85	107.2 (1.9)
45	* = re	eturn gas tempe	rature = 70.0°	F.		
	218E2/HF	C-236ca				
	5.0/95.0	13.4 (92)	63.6 (439)	150.1 (65.6)	3.60	66.5 (1.2)
	95.0/5.0	28.2 (194)	128.0 (883)	129.9 (54.4)	2.96	104.5 (1.8)
50	,			•		•

5	218E2/HFC	-236cb				
	5.0/95.0	18.5 (128)	81.1 (559)	144.6 (62.6)	3.49	83.1 (1.5)
	95.0/5.0	28.9 (215)	129.8 (895)	129.6 (54.2)	2.94	105.6 (1.9)
	218E2/HFC	-236fa				
10	5.0/95.0	20.4 (141)	88.0 (607)	144.3 (62.4)	3.45	89.4 (1.6)
	95.0/5.0*	29.3 (202)	130.8 (902)	134.4 (56.9)	2.89	105.0 (1.8)
	99/1	30.1(207)	134.3(926)	133.7(56.5)	2.84	105.8(1.9)
	89.8/10.2	28.3(195)	126.7(874)	130.5(54.7)	2.98	105.1(1.8)
	1/99	20.3(140)	87.0(600)	145.0(62.8)	3.47	89.0(1.6)
15	•					
	= ret	turn gas tempera	$ature = 70.0^{\circ}F$	•		
	218E2/HFC	-245ca				
	5.0/95.0	7.4 (51)	38.9 (268)	156.6 (69.2)	3.77	41.7 (0.7)
20	95.0/5.0	26.2 (181)	122.8 (847)	130.9 (54.9)	3.00	100.9 (1.8)
	218E2/HFC	C-245cb				
	5.0/95.0	35.9 (248)	137.1 (945)	138.5 (59.2)	3.29	135.0 (2.4)
25	95.0/5.0*	30.7 (212)	135.4 (934)	134.2 (56.8)	2.87	108.0 (1.9)
23	* = re	eturn gas temper	tature of 70.0°I	3		
	218E2/HFC	C-245ea				
	5.0/95.0	7.4 (51)	39.7 (274)	161.2 (71.8)	3.81	42.8 (0.8)
30	95.0/5.0	26.6 (183)	123.9 (854)	130.9 (54.9)	2.99	102.0 (1.8)
•	218E2/HFC	C-245fa				
	5.0/95.0	11.5 (79)	55.8 (385)	153.6 (67.6)	3.67	59.4 (1.0)
•	95.0/5.0	27.7 (191)	126.6 (873)	130.3 (54.6)	2.97	103.7 (1.8)
35				•		•
	218E2/HFC					
 	5.0/95.0	7.2 (50)	37.4 (258)	•	3.81	40.8 (0.7)
	95.0/5.0	25.9 (179)	121.4 (837)	131.1 (55.1)	3.02	100.6 (1.8)
40	•	C-254cb				
	5.0/95.0	18.9 (130)	81.1 (897)	153.4 (54.6)	3.61	87.7 (1.9)
	95.0/5.0	29.1 (201)	130.1 (569)	130.2 (67.4)	2.96	106.5 (1.6)
	218E2/HF0	C-254eb				
45	5.0/95.0	19.2 (132)	82.5 (569)	153.3 (67.4)	3.60	88.9 (1.6)
•	95.0/5.0	29.1 (201)	130.0 (896)	•	2.96	106.8 (1.9)
		•				

5	218E2/HFC-2	263ca				
	5.0/95.0	9.7 (67)	46.6 (321)	161.0 (71.7)	3.78	52.1 (0.9)
	95.0/5.0	26.9 (185)	123.1 (849)	130.9 (54.9)	3.03	103.2 (1.8)
	218E2/HFC-	263fb				
10	5.0/95.0	30.6 (211)	120.7 (832)	153.8 (67.7)	3.52	129.1 (2.3)
	95.0/5.0	30.5 (210)	134.3 (926)	130.4 (54.7)	2.95	110.3 (1.9)
	99/1	30.6(211)	120.1(828)	154.0(67.8)	3.53	129.4(2.3)
	60.5/39.5	30.8(212.5)	128.0(883)	140.5(60.3)	3.28	122.5(2.2)
	1/99	30.6(211)	120.2(829)	154.6(68.1)	3.53	129.4(2.3)
15	<i>T</i> ·	• • •		, .		
	218E2/HFC-	272ca				
	5.0/95.0	19.3 (133)	79.8 (550)	159.6 (70.9)	3.69	90.2 (1.6)
	95.0/5.0	29.1 (201)	129.1 (890)	130.8 (54.9)	3.00	107.9 (1.9)
20	218E2/HFC	-272ea	•			
	5.0/95.0	11.2 (77)	52.9 (365)	169.5 (76.4)	3.82	60.2 (1.1)
	95.0/5.0	27.9 (192)	125.7 (867)	131.3 (55.2)	3.02	106.0 (1.9)
	218E2/HFC			•		
25	5.0/95.0	14.4 (99)	65.4 (451)	167.3 (75.2)	3.77	34.2 (1.3)
	95.0/5.0	29.0 (200)	129.1 (890)	131.0 (55.0)	3.01	108.1 (1.9)
	218E2/HFC					
	5.0/95.0	26.8 (185)	105.9 (730)	166.8 (74.9)	3.69	121.5 (2.1)
30	95.0/5.0	31.0 (214)	135.2 (932)	131.9 (55.5)	2.99	113.5 (2.0)
	218E2/HFC					
	5.0/95.0	21.0 (145)	87.9 (606)	168.3 (75.7)	3.72	100.4 (1.8)
	95.0/5.0	30.1 (208)	132.3 (912)	131.9 (55.5)	3.00	111.4 (2.0)
35	C-225eEαβ	/HFC-143			·	
	55.9/44.1	16.9 (117)	75.2 (518)	167.9 (75.5)	3.73	84.6 (1.5)
	5.0/95.0	16.1 (111)	72.6 (501)	191.7 (88.7)	3.80	84.8 (1.5)
	95.0/5.0	16.8 (116)	74.4 (513)	148.8 (64.9)	3.60	79.6 (1.4)
40						,
	$C-225eE\alpha\beta$	/HFC-236cb				•
•	16.7/83.3	18.4 (127)	80.2 (553)	145.4 (63.0)	3.51	83.1 (1.5)
	5.0/95.0	18.3 (126)	79.9 (551)	145.5 (63.1)	3.50	82.5 (1.5)
	95.0/5.0	16.9 (117)	74.8 (516)	146.3 (63.5)	3.57	79.0 (1.4)
45	·					
	•	/HFC-236ea	50 0 (540)	146 6 (60 7)	2.50	70.0 (1.4)
	91.5/8.5	16.6 (114)	73.9 (510)		3.58	78.2 (1.4)
	5.0/95.0	15.4 (106)	70.5 (486)		3.57	73.7 (1.3)
	95.0/5.0	16.7 (115)	73.9 (510)	146.4 (63.6)	3.58	78.3 (1.4)
50		ATTEC 245-b				
	C-225eEap	3/HFC-245cb				

5	22.4/77.6	30.8 (212)	122.2 (843)	140.9 (60.5)	3.38	123.6 (2.2)
	5.0/95.0	34.9 (241)	133.9 (923)	139.4 (59.7)	3.32	133.2 (2.3)
	95.0/5.0	17.5 (121)	76.9 (530)	145.9 (63.3)	3.59	81.7 (1.4)
	227caEαβ/H	IFC-32*				
10	61/39	55.4(382)	257.2(1774)	149.6(65.3)	3.05	230.4(4.1)
	17.9/82.1	84.3(581)	312.6(2156)	158.1(70.1)	3.43	342.4(6.0)
	1/99	79.4(547.9)	511.6(3530)	225.3(107.4)	1.90	262.3(4.6)
	*Condenser	temp. 90°F, Eva	porator temp.	10°F, and Retur	rn gas Te	mp. 30°F
15	227caΕαβ/H	JEC-125				
	5.0/95.0		384.0(2648)	170.5(76.9)	2.75	318.0(5.6)
	95.0/5.0	26.0(179)	113.8(785)	135.3(57.4)	3.28	106.6(1.9)
20	227caΕαβ/I	HFC-134				
20	5.0/95.0	42.4(292)	170.3(1174)	179.7(82.1)	3.57	188.0(3.3)
•	95.0/5.0	24.7(170)	109.4(754)	136.1(57.8)	3.25	101.5(1.8)
	227caΕαβ/I	HFC-134a				
25	5.0/95.0	54.3(374)	212.9(1468)	169.2(76.2)	3.41	220.8(3.9)
	95.0/5.0	25.1(173)	111.2(767)	135.7(57.6)	3.25	103.0(1.8)
	227caEαβ/]					
	•	16.4(113)	73.8(509)	190.7(88.2)	3.10	86.4(1.5)
30	95.0/5.0	22.6(156)	101.0(696)	136.4(58.0)	3.27	94.5(1.7)
	227caEαβ/	HFC-143a				
	5.0/95.0	107.2(739)	359.0(2475)	216.0(102.2)	2.30	270.8(4.8)
35	95.0/5.0	27.1(187)	117.8(812)	137.6(58.7)	3.31	111.8(2.0)
33	227caEαβ/	HFC-152a				
	5.0/95.0	50.9(351)	193.4(1333)	201.1(93.9)	3.60	222.4(3.9)
	95.0/5.0	26.4(182)	115.4(796)	138.0(58.9)	3.28	108.5(1.9)
40	227caEαβ/	HFC-161				•
	5.0/95.0	79.7(550)	279.4(1926)	199.0(92.8)	3.48	314.7(5.5)
	95.0/5.0	30.8(212)	131.4(906)	139.8(59.9)	3.34	126.1(2.2)
	•	HFC-227ca	·			
45	5.0/95.0	35.5(245)	141.0(972)	142.5(61.4)	3.19	131.7(2.3)
	95.0/5.0	22.8(157)	102.7(708)	134.2(56.8)	3.20	93.1(1.6)
	•	HFC-227ea				
	5.0/95.0	34.7(239)	138.3(954)	142.4(61.3)	3.20	129.8(2.3)
50	95.0/5.0	22.8(157)	102.6(707)	134.8(57.1)	3.20	93.1(1.6)

5	227caΕαβ/H	FC-236ca				
	5.0/95.0	13.3(92)	62.9(433)	150.2(65.7)	3.60	65.8(1.2)
	95.0/5.0	21.5(148)	97.3(671)	134.3(56.8)	3.24	89.6(1.6)
	227caΕαβ/H	FC-236cb				
10	5.0/95.0	18.4(127)	80.3(554)	144.9(62.7)	3.49	82.4(1.4)
	95.0/5.0	21.9(151)	99.0(682)	134.2(56.8	3.22	90.7(1.6)
	227caΕαβ/H	IFC-236fa				
*	5.0/95.0	20.1(140)	87.1(600)	144.5(62.5)	3.46	88.9(1.6)
15	95.0/5.0	22.1(152)	99.4(685)	134.1(56.7)	3.23	91.2(1.6)
	227caΕαβ/H	IFC-245ca				
	5.0/95.0	7.4(51)	38.4(265)	156.6(69.2)	3.76	41.0(0.7)
	95.0/5.0	20.4(141)	94.1(649)	134.9(57.2)	3.25	86.5(1.5)
20	•	, ,	·			
	227caEαβ/F	IFC-245cb				
	5.0/95.0	35.4(244)	135,7(936)	139.0(59.4)	3.28	133.4(2.3)
	95.0/5.0	22.9(158)	102.8(709)	134.1(56.7)	3.20	93.5(1.6)
	1/99	36.0(248.4)	•	139.0(59.4)	3.30	135.6(2.4)
25	8.1/91.9	35.0(241.5)	•	138.8(59.3)	3.29	132.7(2.3)
	82/18	24.8(171)	107.8(1743)	134.8(57.1)	3.25	100.6(1.8)
	227caEαβ/I				. ===	44.0(0.77)
	5.0/95.0	• •	39.1(269)	161.3(71.8)	3.78	41.9(0.7)
30	95.0/5.0	20.6(142)	94.7(653)	135.1(57.3)	3.24	87.0(1.5)
	227caEαβ/1					
	5.0/95.0	11.5(79)	54.7(377)	153.2(67.3)	3.68	58.7(1.0)
35	95.0/5.0	21.5(148)	96.4(664)	134.0(56.7)	3.29	90.2(1.6)
33	227caEαβ/	HFC-254ca				
	5.0/95.0	7.1(49)	36.9(254)	160.0(71.1)	3.78	40.0(0.7)
•	95.0/5.0	20.3(140)	93.3(643)	135.1(57.3)	3.26	86.2(1.5)
40	227caFo8 /	HFC-254cb				-14
	5.0/95.0	18.7(129)	80.5(555)	153.6(67.6)	3.61	87.0(1.5)
	95.0/5.0	22.0(152)	98.9(682)	134.7(57.1	3.24	91.3(1.6)
	227caEαβ /	HFC-254eb				
45	5.0/95.0	19.0(131)	81.7(563)	153.5(67.5)	3.60	88.3(1.6)
	95.0/5.0	22.0(152)	99.0(683)	134.7(57.1)	3.24	91.4(1.6)
	227caΕαβ /	/HFC-263ca				
	5.0/95.0	9.7(67)	46.2(318)	161.1(71.7)	3.77	51.4(0.9)
50	95.0/5.0	20.8(143)	94.5(651)	135.1(57.3)	3.27	88.0(1.5)

5	227caEαβ/HF	FC-263fb					
	5.0/95.0	30.3(209)	119.6(825)	154.1(67.8)	3.52	128.1(2.3)	
	95.0/5.0	22.9(158)	102.3(706)	135.0(57.2)	3.23	94.2(1.7)	
	227caΕαβ/HF	FC-272ca					
10	5.0/95.0	19.2(132)	79.3(54.7)	159.8(71.0)	3.69	89.6(1.6)	
	95.0/5.0·	22.2(153)	98.9(682)	135.4(57.4)	3.26	92.4(1.6)	
	99/1	22.3(153)	100.2(691)	133.8(56.6)	3.23	91.8(1.6)	
	94.3/5.7	22.1(152)	98.5(679)	135.5(57.5)	3.28	92.5(1.6)	
	1/99	19.1(131)	78.6(542)	160.4(71.3)	3.70	89.4(1.6)	
15	-1		,				
	227caΕαβ/HI	FC-272ea					
	5.0/95.0	11.1(76)	51.5(355)	168.6(75.9)	3.84	59.2(1.0)	
	95.0/5.0	21.4(148)	96.5(665)	135.7(57.6)	3.28	90.4(1.6)	
20	227caΕαβ/H	FC-272fb					
20	5.0/95.0	14.3(98)	64.6(445)	167.4(75.2)	3.76	73.2(1.3)	
	95.0/5.0	21.9(151)	98.5(679)	135.7(51.6)	3.27	91.8(1.6)	
	227caΕαβ/H	FC-281ea					
25	5.0/95.0	26.6(184)	105.3(726)	167.0(75.0)	3.69	120.7(2.1)	
23	95.0/5.0	23.4(162)	103.3(712)	136.3(57.9)	3.28	97.2(1.7)	
	99/1	22.5(155)	101.2(698)	134.1(56.7)	3.22	92.6(1.6)	
	31.5/68.5	26.8(184)	107.4(741)	160.6(71.4)	3.63	119.7(2.1)	
	1/99	26.6(183)	104.9(723)	167.8(75.4)	3.70	120.7(2.1)	
30	-1, >>		,	,		,	
50	$227 ca E \alpha \beta / H$	IFC-281fa					
	5.0/95.0	20.8(144)	87.5(604)	168.6(75.9)	3.71	99.6(1.8)	
•	95.0/5.0	22.8(157)	101.4(699)	136.3(57.9)	3.28	95.2(1.7)	
	99/1	22.4(154)	100.7(694)	134.0(56.7)	3.20	92.4(1.6)	
35	84.3/15.7	23.4(161)	101.3(699)	141.8(61.0)	3.39	100.2(1.8)	
	1/99	20.7(142)	86.8(598)	169.3(76.3)	3.72	99.4(1.7)	
	227caΕβγ/H	TFC-32					
	5.0/95.0	152.1(1049)	517.0(3565)	198.4(924)	2.92	483.9(8.5)	
40	95.0/5.0*	42.9(296)	190.1(1311)	•	3.77	200.3(3.5)	
70	67/33	98.9(682)	360.0(2484)	•	3.35	365.6(6.4)	
	28.4/71.6*	159.9(1103)		•	3.61	550.1(9.7)	
	1/99	150.1(1035)			3.16	519.7(9.1)	
45	* = \$1	ubcool tempera	ture of 20.0°F				
73	* = subcool temperature of 20.0°F						
	227caΕβγ/Ι		226 0/1550	\ 120.0/E4.0\	2 27	226 274 0	
	5.0/95.0*	59.7(412)	226.0(1558	,	3.27	226.3(4.0)	
	95.0/5.0	30.3(209)	130.7(901)	141.8(61.0)	3.31	124.1(2.2)	
50							

	227caΕβγ/H	FC-134				
	95.0/5.0	29.2 (201)	126.5 (872)	142.3 (61.3)	3.27	118.7 (2.1)
10	76.0/24.0	37.1 (256)	152.2 (1049)	149.9 (65.5)	3.38	151.3 (2.7)
20	34.8/65.2	44.2 (305)	175.3 (1209)	166.9 (74.9)	3.46	184.2 (3.2)
	1.0/99.0	42.2 (291)	170.0 (1172)	182.0 (83.3)	3.59	188.7 (3.3)
	2.07 22.0	v <b>=</b> v= (*** =)	<b>(/</b>			(-·-)
	227caΕβγ/H	FC-134a	-			
15	5.0/95.0	54.7(377)	214.0(1475)	169.5(76.4)	3.41	222.2(3.9)
	95.0/5.0	29.6(204)	128.5(886)	142.0(61.1)	3.27	120.7(2.1)
	67/33	42.7(294)	175.0(1207)	152.2(66.8)	3.31	169.4(3.0)
	1.9/98.1	54.6(376)	214.0(1476)	170.3(76.8)	3.43	223.2(3.9)
	1/99	54.6(376)	214.0)1476)	170.7(77.1)	3.43	223.4(3.9)
20		•				
٠.	$227 \text{caE}\beta\gamma/\text{H}$					
	5.0/95.0	16.5(114)	74.4(513)	191.4(88.6)	3.81	87.2(1.5)
	95.0/5.0	26.9(185)	116.6(804)	142.2(61.2)	3.29	110.9(2.0)
25	227an E8a. /IU	TEC 1/20				
23	227caEβγ/H 5.0/95.0*	107.8(743)	360.6(2486)	216.6(102.6)	3.18	377.2(6.6)
	95.0/5.0	31.3(216)	134.3(926)	144.3(62.4)	3.35	129,6(2.3)
	75.0/5.0	31.5(210)	154.5(720)	144.5(02.4)	J.JJ	125,0(2.5)
	* = su	bcool temperat	ure of 20.0°F			
30						
	$227 ca E \beta \gamma / F$					
	5.0/95.0	51.0(352)	194.2(1339)	201.5(94.2)	3.59	223.1(3.9)
	95.0/5.0	30.9(213)	132.6(914)	144.4(62.4)	3.31	126.6(2.2)
	78/22	41.4(285)	167.0(1152)	157.6(69.8)	3.39	168.3(3.0)
35	38.3/61.7	51.4(354)	195.1(1346)	182.2(83.4)	3.50	213.6(3.8)
	1/99	50.8(350)	193.4(1334)	203.6(95.3)	3.6	223.5(3.9)
:	227caΕβγ/I	JEC-161				
	5.0/95.0	80.0(552)	280.1(1931)	199.3(92.9)	3.48	315.6(5.6)
40	95.0/5.0	35.1(242)	149.6(1031)	` '	3.39	146.2(2.6)
70	72/28	60.9(420)	233.8(1613)	•	3.32	234.0(4.1)
	34.4/65.6	54.1(373)	247.5(1707)		2.73	194.7(3.4)
•	1/99	79.8(550)	279.8(1930)	` '	3.49	316.7(5.6)
	-1//	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	275.0(1550)	200.0(75.0)		220.7(3.0)
45	227caEβγ/]	HFC-227ca				
	5.0/95.0	35.8(247)	141.8(978)	142.6(61.4)	3.20	133.1(2.3)
	95.0/5.0	27.2(188)	118.5(817)	139.8(59.9)	3.23	109.8(1.9)

5	227caEβγ/HF 5.0/95.0 95.0/5.0	FC-227ea 35.0(241) 27.2(188)	139.0(958) 118.3(816)	142.6(61.4) 139.7(59.8)	3.21 3.23	131.0(2.3) 109.7(1.9)
10	227caEβγ/HF 5.0/95.0 95.0/5.0	FC-236ca 13.4(92) 25.5(176)	63.9(441) 112.6(776)	150.7(65.9) 140.3(60.2)	3.60 3.27	66.4(1.2) 105.5(1.9)
15	227caΕβγ/ΗΙ 5.0/95.0 95.0/5.0	FC-236cb 18.5 (129) 26.1 (180)	80.9 (578) 114.3 (788)	145.3 (62.9) 139.9 (59.9)	3.49 3.25	82.9 (1.5) 106.7 (1.9)
	227caEβγ/HI 5.0/95.0 95.0/5.0	FC-236fa 20.4(141) 26.3(181)	87.6(604) 114.9(792)	144.9(62.7) 139.8(59.9)	3.46 3.26	89.5(1.6) 107.3(1.9)
20	227caΕβγ/HI 5.0/95.0 95.0/5.0	FC-245ca 7.4 (51) 24.0 (165)	38.8 (268) 108.6 (749)	157.1 (69.5) 141.2 (60.7)	3.78 3.29	41.7 (0.7) 102.0 (1.8)
25	227caEβγ/HI 5.0/95.0 95.0/5.0		136.4 (940) 118.4 (816)	139.1 (59.5) 139.6 (59.8)	3.30 3.24	134.7 (2.4) 110.1 (1.9)
30	227caΕβγ/H 5.0/95.0 95.0/5.0	FC-245ea 7.4 (51) 24.3 (168)	39.6 (273) 109.5 (755)	161.8 (72.1) 141.2 (60.7)	3.81 3.29	42.7 (0.8) 102.8 (1.8)
35	227caΕβγ/H 5.0/95.0 95.0/5.0	FC-245fa 11.5 (79) 25.2 (174)	55.7 (384) 111.5 (769)	153.2 (67.3) 139.5 (59.7)	3.68 3.29	59.5 (1.0) 105.1 (1.8)
	227caEβγ/H 5.0/95.0 95.0/5.0	FC-254ca 7.2 (50) 23.8 (164)	37.3 (257) 107.7 (743)	160.5 (71.4) 141.4 (60.8)	3.81 3.31	40.6 (0.7) 101.6 (1.8)
40	227caΕβγ/H 5.0/95.0 95.0/5.0	FC-254cb 18.8 (130) 26.1 (180)	81.0 (558) 114.1 (787)	153.9 (67.7) 142.4 (60.2)	3.61 3.27	87.7 (1.5) 107.4 (1.9)
45	227caEβγ/H 5.0/95.0 95.0/5.0	IFC-254eb 19.2(132) 26.2(181)	82.2(567) 114.4(789)	153.8(67.7) 140.3(60.2)	3.61 3.28	89.0(1.6) 107.8(1.9)
50	227caEβγ/E 5.0/95.0	IFC-263ca 9.7 (67)	46.5 (321)	161.5 (71.9)	3.78	52.0 (0.9)

5	95.0/5.0	24.5 (169)	109.1 (752)	141.2 (60.7)	3.31	103.4 (1.8)
	227caΕβγ/ΗΓ	C-263fb				
	5.0/95.0	30.5 (210)	120.1 (828)	154.3 (67.9)	3.52	120 0 (2 2)
	95.0/5.0	27.2 (188)	117.8 (812)	•		128.9 (2.3)
10	99/1	26.9(185)	` ,	140.6 (60.3)	3.26	110.6 (1.9)
10	•	` ,	117.3(809)	139.7(59.8)	3.24	109.1(1.9)
	32.9/67.1	29.9(206)	120.2(829)	150.9(66.1)	3.47	125.4(2.2)
	1/99	30.6(211)	120.1(828)	154.7(68.2)	3.53	129.3(2.3)
	227caEβγ/HF	C-272ca				
15	5.0/95.0	19.3 (133)	79.5 (548)	159.9 (71.1)	3.70	90.2 (1.6)
	95.0/5.0	26.2 (181)	113.7 (784)	140.9 (60.5)	3.30	108.2 (1.9)
	99/1	26.7(184)	116.6(204)	139.8(159)	3.25	108.6(1.9)
	89.0/11.0	25.5(176)	109.7(756)	142.6(61.4)	3.36	107.3(1.9)
	1/99	19.1(131)	78.7(543)	160.5(71.4)	3.70	89.5(1.6)
20	, , ,	_, _,	7011 (0.10)	100.5(71.4)	3.70	03.3(1.0)
	227caEβγ/HF	C-272ea				
	5.0/95.0	11.1 (77)	52.7 (363)	169.9 (76.6)	3.82	60.0 (1.1)
•	95.0/5.0	25.3 (174)	111.1 (766)	141.4 (60.8)	3.32	106.1 (1.9)
	·			(000)		100.1 (1.5)
25	$227 \text{caE}\beta\gamma/\text{HF}$					
	5.0/95.0	14.4 (99)	65.1 (449)	167.8 (75.4)	3.77	73.9 (1.3)
	95.0/5.0	26.0 (179)	113.4 (782)	141.3 (60.7)	3.30	107.9 (1.9)
	227caΕβγ/ΗΓ	C-281ea				
30	5.0/95.0	26.7 (184)	105.7 (729)	167.3 (75.2)	3.69	121.1 (2.1)
	95.0/5.0	27.7 (191)	118.8 (819)	142.0 (61.1)	3.28	113.0 (2.0)
	99/1	27.0(186)	117.6(811)	140.0(60.0)	3.25	109.6(1.9)
	73.1/26.9	28.9(199)	118.6(818)	150.6(65.9)	3.46	122.7(2.2)
	1/99	26.6(183)	105.0(724)	167.9(75.5)	3.69	120.8(2.1)
35	•	()		10/15(7515)	5.07	120.0(2.1)
	227caΕβγ/ΗΓ	C-281fa	•			
	5.0/95.0	20.9 (144)	87.8 (605)	168.7 (75.9)	3.72	100.2 (1.8)
	95.0/5.0	27.0 (186)	116.5 (803)	141.9 (61.1)	3.30	111.1 (2.0)
	99/1	26.9(185)	117.2(808)	140.0(60.0)	3.25	109.3(1.9)
40	85.9/14.1	26.8(184)	113.6(783)	145.9(63.2)	3.40	113.3(2.0)
• •	1/99	20.7(142)	86.9(599)	169.4(76.3)	3.72	99.4(1.7)
	227eaE/HFC-	-32				
	5.0/95.0	152.1 (1049)	516 0 (3564)	100 2 702 41	2.02	404 1 (0.5)
45	95.0/5.0*	45.3 (312)	516.9 (3564)	198.3 (92.4)	2.93	484.1 (8.5)
TJ.		• •	196.1 (1352)	151.3 (66.3)	3.77	208.1 (3.7)
	68/32**	51.2(353)	240.8(1661)	144.4(62.4)	3.26	228.0(4.0)
	30.0/70.0	160.9(1110)	479.0(3305)	175.8(79.9)	3.60	549.5(9.7)
	1/99	150.1(1035)	512.3(3534)	199.8(93.2)	3.16	519.7(9.1)

<sup>50</sup> 

<sup>\*</sup>Subcool temp. 20.0°F \*\*Subcool temp. 20°F, Return gas temp. 30°F

5						•				
	227eaE/HFC-125									
	5.0/95.0*	60.0 (414)	226.5 (1562)	132.6 (55.9)	3.27	227.1 (4.0)				
	95.0/5.0	31.8 (219)	135.8 (936)	141.8 (61.0)	3.29	128.0 (2.3)				
	<i>73.075.</i> 0	<b>21</b> (21)		(0)		, ,				
10	* = A379T	oorator tempera	ature of 10 0°F	condenser tem	nerature	of 90.0°F, and				
10	-	n gas temperat		, condoinor to	Pozuo	, , , , , , , , , , , , , , , , , , , ,				
	· Ictur	n gas tomporat	dr 0 0 50.0 1			•				
	227eaE/HFC	-134								
	95.0/5.0	30.7 (211)	131.9 (909)	142.3 (61.3)	3.24	122.9 (2.2)				
15	78.0/22.0	37.2 (256)	154.6 (1066)	149.9 (65.5)	3.29	148.8 (2.6)				
10	38.2/61.8	44.8 (309)	177.0 (1220)	165.5 (74.2)	3.44	184.5 (3.2)				
	1.0/99.0	42.2 (291)	170.0 (1172)	182.0 (83.3)	3.59	188.8 (3.3)				
	210,7710			` ,						
	227eaE/HFC	C-134a								
20	5.0/95.0	54.7 (377)	214.3 (1478)	169.5 (76.4)	3.41	222.5 (3.9)				
	95.0/5.0	31.1 (214)	134.0 (924)	142.1 (61.2)	3.24	124.6 (2.2)				
	70/30	43.0(296)	175.6(1211)	151.0(66.1)	3.29	168.8(3.0)				
	9.3/90.7	54.8(378)	214.3(1478)	168.2(75.7)	3.40	221.1(3.9)				
	1/99	54.6(376)	214.1(1477)	170.6(77.0)	3.43	223.5(3.9)				
25			•							
	227eaE/HFC					OM 4 44 M				
	5.0/95.0	16.6 (114)	74.6 (514)	191.3 (88.5)	3.81	87.4 (1.5)				
	95.0/5.0	28.3 (195)	121.7 (839)	142.2 (61.2)	3.27	115.0 (2.0)				
20	227-aB/UE	7 1/20								
30	227eaE/HF0		361.2 (2490)	216.5 (102.5)	3.18	377.9 (6.7)				
	5.0/95.0* 95.0/5.0	108.1 (745) 32.8 (226)	139.6 (963)		3.32	133.4 (2.3)				
	93.0/3.0	32.0 (220)	159.0 (905)	144.4 (02.4)	3.32	2001. (2.0)				
	* = S11	bcool tempera	ture of 20.0°F	•						
35		· ·								
Ŏ, Ď	227eaE/HF	C-152a								
	5.0/95.0	51.1 (352)	194.5 (1341	) 201.6 (94.2)	3.59	223.3(3.9)				
	95.0/5.0	32.5 (224)	138.1 (952)	144.5 (62.5)	3.28	130.8 (2.3)				
	80/20	42.1(290)	169.3(1168)	156.1(68.9)	3.36	168.9(3.0)				
40	42.1/57.9	52.1(359)	197.3(1361)	•	3.48	213.7(3.8)				
	1/99	50.8(350)	193.5(1335	203.7(95.4)	3.60	223.5(3.9)				
	227eaE/HF				0.40	015.0 (5.6)				
	5.0/95.0	80.0 (552)	280.3 (193.		3.48	•				
45	95.0/5.0	36.7 (253)	155.1 (1069		3.36	150.1 (2.6)				
	73/27	61.8(426)	236.3(1630	•	3.30	235.0(4.1)				
	37.5/62.5	79.3(547)	278.3(1920	•	3.38	` '				
	1/99	79.8(550)	279.8(1930	)) 200.8(93.8)	3.49	316.7(5.6)				
50	22712/11	FC 22700								
50	227eaE/HI	rC-22/Ca								

5	5.0/95.0	35.9 (248)	142.0 (979)	142.6 (61.4)	3.20	133.3 (2.3)
	95.0/5.0	28.7 (198)	123.6 (852)	139.7 (59.8)	3.21	113.9 (2.0)
	227eaE/HFC	.227en				
	5.0/95.0	35.1 (242)	139.1 (959)	142.6 (61.4)	3.21	131.1 (2.3)
10	95.0/5.0	28.6 (197)	123.3 (850)	139.7 (59.8)	3.21	113.7 (2.0)
	·		, ,			• •
	227eaE/HFC		(0.5 (100)	450 = 444 0		<b>**</b> * * * * * * * * * * * * * * * * * *
	5.0/95.0	13.4 (92)	63.5 (438)	150.7 (65.9)	3.60	66.5 (1.2)
15	95.0/5.0	26.7 (184)	117.4 (809)	140.3 (60.2)	3.25	109.3 (1.9)
1.0	227eaE/HFC	236cb				
	5.0/95.0	18.5 (128)	81.0 (558)	145.2 (62.9)	3.49	83.3 (1.5)
	95.0/5.0	27.5 (190)	119.3 (823)	139.8 (59.9)	3.24	111.0 (2.0)
20	227eaE/HFC	2-236fa				
20	5.0/95.0	20.4 (141)	87.8 (605)	144.9 (62.7)	3.46	89.6 (1.6)
	95.0/5.0	27.6 (190)	119.9 (827)	139.8 (59.9)	3.24	111.3 (2.0)
	227eaE/HFC	2-245ca		٠ .	• ·	
25	5.0/95.0	7.5 (52)	38.9 (268)	157.1 (69.5)	3.78	41.9 (0.7)
	95.0/5.0	25.2 (174)	113.4 (782)	141.3 (60.7)	3.27	105.6 (1.9)
	227eaE/HFC	`-245ch				•
	5.0/95.0		136.6 (942)	139.0 (59.4)	3.30	134.9 (2.4)
30	95.0/5.0	28.7 (198)	123.5 (852)	139.6 (59.8)	3.22	114.2 (2.0)
	227eaE/HFC	~245ea				
	5.0/95.0	7.4 (51)	39.7 (274)	161.9 (72.2)	3.81	42.9 (0.8)
	95.0/5.0	25.6 (177)	114.3 (788)	141.2 (60.7)	3.27	106.7 (1.9)
35	•					
	227eaE/HFC					
	5.0/95.0	11.6 (80)	55.8 (385)	154.2 (67.9)	3.67	59.6 (1.0)
	95.0/5.0	26.4 (182)	116.4 (803)	140.6 (60.3)	3.26	108.6 (1.9)
40	227eaE/HF0	C-254ca				·
	5.0/95.0	7.2 (50)	37.4 (258)	160.4 (71.3)	3.81	40.9 (0.7)
	95.0/5.0	25.0 (172)	112.4 (775)	141.4 (60.8)	3.28	105.3 (1.9)
	227eaE/HF	C-254cb			•	
45	5.0/95.0	18.9 (130)	81.1 (559)	153.9 (67.7)	3.61	87.8 (1.5)
	95.0/5.0	27.5 (190)	119.4 (823)	140.5 (60.3)	3.25	111.2 (2.0)
	227eaE/HF	C-254eb				
	5.0/95.0	19.2 (132)	82.3 (567)	153.8 (67.7)	3.61	89.1 (1.6)
50	95.0/5.0	27.5 (190)	119.2 (822)	140.4 (60.2)	3.25	111.4 (2.0)

5	227eaE/HFC	2-263ca				. •
_	5.0/95.Ó	9.8 (68)	46.7 (322)	161.5 (71.9)	3.78	52.2 (0.9)
	95.0/5.0	25.7 (177)	113.8 (785)	141.2 (60.7)	3.29	107.3 (1.9)
	227eaE/HFC	C-263fb				
10	5.0/95.0	30.5 (210)	120.3 (829)	154.3 (67.9)	3.52	129.0 (2.3)
	95.0/5.0	28.6 (197)	122.7 (846)	140.6 (60.3)	3.24	114.6 (2.0)
	99/1	28.4(194)	122.7(846)	139.7(59.8)	3.22	113.4(2.0)
	49.3/50.7	30.0(207)	121.8(840)	148.5(64.7)	3.42	124.4(2.2)
	1/99	30.6(211)	120.1(828)	154.7(68.2)	3.53	129.3(2.3)
15	-122	5 515 (=25)		25 (00.1)		
10	227eaE/HFC	-272ca				
	5.0/95.0	19.3 (133)	79.5 (548)	159.9 (71.1)	3.70	90.2 (1.6)
	95.0/5.0	27.4 (189)	118.1 (814)	141.0 (60.6)	3.27	111.6 (2.0)
	99/1	28.2(194)	121.8(840)	139.9(59.9)	3.22	112.6(2.0)
20	90.7/9.3	26.7(184)	114.4(789)	142.1(61.2)	3.33	110.8(2.0)
20	29/71	20.6(142)	85.4(589)	156.1(68.9)	3.66	95.0(1.7)
	->/		0011(005)	10011(0015)	•••	70.0(2.7)
	227eaE/HF0	C-272ea	•			
	5.0/95.0	11.2 (77)	52.8 (364)	169.9 (76.6)	3.82	60.2 (1.0)
25	95.0/5.0	26.6 (183)	116.1 (800)	141.6 (60.9)	3.29	109.8 (1.9)
	227eaE/HF0	C-272fb				
	5.0/95.0	14.4 (99)	65.2 (450)	167.8 (75.4)	3.77	73.9 (1.3)
	95.0/5.0	27.3 (188)	118.3 (816)	141.3 (60.7)	3.28	111.9 (2.0)
30				()		()
	227eaE/HF	C-281ea				
	5.0/95.0	26.7 (184)	105.8 (729)	167.3 (75.2)	3.68	121.2 (2.1)
	95.0/5.0	29.1 (201)	123.7 (853)	141.9 (61.0)	3.27	117.1 (2.1)
	99/1	28.5(196)	123.0(848)	140.0(60.0)	3.23	113.9(2.0)
. 35	76.8/23.2	29.8(205)	122.1(842)	149.2(65.1)	3.43	124.9(2.2)
	1/99	26.6(183)	105.1(725)	167.9(75.5)	3.59	120.8(2.1)
		()				120.0(2.1)
	227eaE/HF	C-281fa				
	5.0/95.0	21.0 (145)	87.9 (606)	168.6 (75.9)	3.72	100.5 (1.8)
40	95.0/5.0	28.4 (196)	121.5 (838)	141.9 (61.0)	3.28	115.3 (2.0)
	99/1	28.4(196)	122.5(845)	140.0(60.0)	3.23	113.6(2.0)
	87.6/12.4	20.7(142)	86.7(598)	169.2(76.2)	3.73	99.6(1.8)
	1/99	20.7(142)	87.0(600)	169.4(76.3)	3.72	99.5(1.8)
45	C-234fEαβ/	HFC-245cb	• ,			
	13.5/86.5	29.3 (202)	119.3 (823)	142.1 (61.2)	3.38	119.8 (2.1)
	5.0/95.0	33.5 (231)		140.1 (60.1)	3.33	130.0 (2.3)
	95.0/5.0	9.4 (65)	` ,	151.4 (66.3)	3.76	50.0 (0.9)
50	C-234fF~R	/HFC-245eb				
50	49.1/50.9	11.6 (80)	55.7 (384)	152.3 (66.8)	3.67	59.5 (1.0)
	77.1/30.7	11.0 (00)	23.7 (2 <del>01</del> )	152.5 (00.0)	J.01	JJ.J (1.0)

PCT/US93/04614

			75			
5	5.0/95.0	8.6 (59)	43.2 (298)	156.3 (69.1)	3.71	46.2 (0.8)
	95.0/5.0	8.6 (59)	41.9 (289)	152.6 (67.0)	3.73	45.5 (0.8)
	C-234fEαβ/H	FC-356mff				
	59.0/41.0	9.1 (63)	44.6 (308)	145.3 (62.9)	3.64	46.9 (0.8)
10	5.0/95.0	7.6 (52)	39.4 (272)	138.4 (59.1)	3.55	39.1 (0.7)
	95.0/5.0	8.6 (59)	42.2 (291)	151.5 (66.4)	3.72	45.7 (0.8)
	C-234fEαβ/H	FC-356mmz		•		
	50.1/49.9	9.9 (68)	47.1 (325) 1	43.4 (61.9)	3.62	49.5 (0.9)
15	5.0/95.0	8.7 (60)	43.2 (298) 1	37.5 (58.6)	3.54	43.4 (0.8)
	95.0/5.0	8.7 (60)	42.5 (293) 1	51.4 (66.3)	3.73	46.2 (0.8)
	C-234fEβγ/H	IFC-245ca				
	33.6/66.4	7.2 (50)	37.0 (255)	156.3 (69.1)	3.74	39.7 (0.7)
20	5.0/95.0	7. 0 (48)	36.7 (253)	157.8 (69.9)	3.74	39.2 (0.7)
	95.0/5.0	6.6 (46)	33.9 (234)	154.5 (68.1)	3.76	36.7 (0.6)
	C-234fEβγ/H	IFC-245cb	•			
	10.2/89.8	29.5 (203)	120.8 (833)	142.3 (61.3)	3.36	120.3 (2.1)
25	5.0/95.0	32.8 (226)	129.0 (889)	140.5 (60.3)	3.33	128.5 (2.3)
	95.0/5.0	7.5 (52)	37.7 (260)	153.0 (67.2)	3.89	42.4 (0.7)
	C-234fE $\beta\gamma$ /I					40 ( (0.5)
	36.0/64.0	7.0 (48)	36.9 (254)	159.5 (70.8)	3.76	39.6 (0.7)
30	5.0/95.0	6.9 (48)	37.2 (256)	162.6 (72.6)	3.77	39.7 (0.7)
	95.0/5.0	6.6 (46)	33.9 (234)	154.8 (68.2)	3.76	36.7 (0.6)
	C-234fE $\beta\gamma$ /I				· ·	
	36.0/64.0	6.9 (48)	35.6 (245)	158.6 (70.3)	3.77	38.6 (0.7)
35	5.0/95.0	6.8 (47)	35.3 (243)	161.1 (71.7)	3.77	38.1 (0.7)
	95.0/5.0	6.6 (46)	33.8 (233)	154.7 (68.2)	3.76	36.7 (0.6)
		HFC-356mff				
	43.1/56.9	7.8 (54)	39.7 (274)	143.9 (62.2		41.1 (0.7)
40	5.0/95.0	7.4 (51)	38.8 (268)	138.5 (59.	•	38.4 (0.7)
	95.0/5.0	6.7 (46)	34.3 (236)	153.4 (67.	.4) 3.76	37.1 (0.7)
•.		HFC-356mmz				10000
	35.8/64.2	8.4 (58)	41.5 (286)		3.61	43.0 (0.8)
45	5.0/95.0	8.5 (59)	42.2 (291)	· · · · · · · · · · · · · · · · · · ·	3.54	42.4 (0.7)
	95.0/5.0	6.7 (46)	34.3 (236)	153.3 (67.4)	3.76	37.2 (0.7)
	22600E /LIE	C-245co				
<b>5</b> 0	236caE/HF 5.0/95.0	7.0 (48)	36.6 (252)	157.7 (69.8)	3.74	39.0 (0.7)
50	50.0/50.0	6.7 (46)	36.5 (252)		3.71	37.8 (0.7)
	20.0/20.0	0.7 ( <del>1</del> 0)	JU.J (LJL)	127.7 (00.0)	J./ I	27.0 (0.7)

5	95.0/5.0	6.2 (43)	35.7 (246)	150.9 (66.1)	3.67	35.7 (0.6)
	236caE/HFC-	-254ca				
	99/1	6.2(42)	35.5(245)	150.6(65.9)	3.67	35.5(2.0)
	17.6/82.4	6.7(46)	35.4(244)	159.9(71.1)	3.76	37.9(1.8)
10	1/99	6.7(46)	35.2(242)	161.4(71.9)	3.77	38.0(1.8)
		70.00				
	$236eaE\beta\gamma/HI$		10 7/000	440.0467.0		
	99/1	7.7(53)	42.5(293)	149.3(65.2)	3.64	42.6(0.7)
1.5	4.1/95.9	9.3(64)	44.8(309)	162.0(72.2)	3.77	49.8(0.9)
15	1/99	9.4(64)	44.8(309)	162.3(72.4)	3.77	49.9(0.9)
	236eaΕβγ/HI	FC-338mf				
	99/1	7.7(53)	42.7(294)	148.9(64.9)	3.64	42.7(0.8)
	92.6/7.4	8.0(55)	43.8(302)	147.5(64.2)	3.63	43.9(0.8)
20	1/99	9.7(66)	48.3(333)	131.1(55.1)	3.39	45.8(0.8)
	236eaΕβγ/H	FC-356mmz		•		
	99/1	7.7(53)	42.5(293)	149.0(65.0)	3.64	42.6(0.7)
	15.1/84.9	8.6(59)	43.2(298)	138.3(59.1)	3.53	43.1(0.8)
25	1/99	8.4(58)	42.0(289)	136.9(58.3)	3.53	42.2(0.7)
	236faE/HFC	-32				
	55/45*	80.8(557)	320.8(2213)	181.3(82.9)	3.62	352.9(6.2)
	8.5/91.5	149.2(1029)	506.5(3494)	`	2.96	479.3(8.4)
30	1/99	149.6(1032)	510.4(3521)	199.8(93.2)	3.16	518.3(9.1)
	*Subcool tem	ър. 25°F				
	` 22 <i>C</i> E-E /IJEC	070				
25	236faE/HFC 99/1		74 5/514\	140 2/(1 2)	2.46	70 7/4 0
35		15.7(108)	74.5(514)	142.3(61.3)	3.46	73.7(1.3)
	27.8/72.2 1/99	18.6(128)	78.2(539)	156.9(69.4)	3.67	87.1(1.5)
	1/33	19.1(131)	78.5(541)	160.5(71.4)	3.70	89.3(1.6)
	236faE/HFC	2-272fb		•		
40	99/1	15.6(107)	74.3(512)	142.4(61.3)	3.47	73.6(1.3)
	82.3/17.7	15.7(108)	73.2(505)	148.1(64.5)	3.55	75.4(1.3)
•	1/99	14.0(96)	63.5(438)	168.7 <u>(</u> 75.9)	3.76	72.0(1.3)
	236faE/HFC	C-281fa				
45	99/1	15.8(109)	75.1(517)	142.5(61.4)	3.47	74.3(1.3)
	9.3/90.7	20.6(142)	86.7(598)	167.9(75.5)	3.72	98.9(1.7)
	1/99	20.7(142)	86.7(598)	169.3(76.3)	3.73	99.3(1.7)
	•	` '	` /	` '		(, )

## **EXAMPLE 4**

The following table shows the refrigerant performance of various compositions. The data are based on the following conditions.

Evaporator temperature

40.0°F (4.4°C)

Condenser temperature

100.0°F (37.8°C)

10

Compressor efficiency is 75%.

Return gas temperature

60.0°F

## TABLE 5

15	Refrig.	Evap. Press.	Cond. Press.	Comp. Dis.		Capacity BTU/min
	Comp.	Psia (kPa)	Psia (kPa)	Temp. °F (°C)	<u>CC</u>	<u> (kw)</u>
20	CFC-11	7.1 (49)	23.5 (162)	130.0 (54.4)	5.68	44.2 (0.8)
20	134E/HFC-32					400 0 (0 ()
	5.0/95.0	135.9 (937)	•		3.17	490.0 (8.6)
	95.0/5.0	21.1 (145)	95.6 (659)	175.8 (79.9)	4.08	116.8 (2.1)
25	134E/HFC-125*					
	5.0/95.0	107.4(741)	387.9(2675)	154.0(67.8)	2.13	244.0(4.3)
	95.0/5.0	23.7(163)	63.5(438)	126.4(42.4)	7.10	146.9(2.6)
	* = Condenser to	emp. of 130°F	, evaporator te	mp. of 45°F, and	l return	gas temp. of 65°F
30		•	· •			
	134E/HFC-134	060(050)	4040(700)	107 1(50.0)	£ 20	104.0/2.0)
	5.0/95.0	36.3(250)	104.9(723)	127.1(52.8)	5.38	184.8(3.2)
	95.0/5.0	15.2(105)	50.5(348)	119.5(48.6)	5.53	90.5(1.6)
<b>3</b> 5	134E/HFC-134a					
	5.0/95.0	46.8(323)	132.8(916)	118.5(48.1)	5.20	222.8(3.9)
	95.0/5.0	15.7(108)	51.8(357)	119.9(48.8)	5.57	93.5(1.6)
	134E/HFC-143					
40	5.0/95.0	14.5 (100)	45.2 (312)	134.5 (56.9)	5.60	84.0 (1.5)
	37.9/62.1	14.7 (101)	46.7 (322)	128.9 (53.8)	5.57	85.7 (1.5)
	95.0/5.0	14.4 (99)	48.0 (331)	119.0 (48.3)	5.51	85.7 (1.5)
	134E/HFC-143a	a ·				
45	5.0/95.0	101.0(696)	247.9(1709)	149.7(65.4)	4.84	•
	95.0/5.0	23.9(165)	69.4(479)	133.2(56.2)	6.54	148.0(2.6)

5	134E/HFC-152	a				
	5.0/95.0	44.5(307)	122.9(847)	142.8(61.6	5.39	220.3(3.9)
	95.0/5.0	16.1(111)	52.8(364)	121.7(49.8)	5.57	95.4(1.7)
				` ;		, ,
	134E/HFC-161					
10	5.0/95.0	70.2(484)	181.9(1254)	141.2(60.7)	5.28	317.3(5.6)
	95.0/5.0	18.1(125)	58.3(402)	125.4(51.9)	5.69	108.0(1.9)
	134E/HFC-227	loo				
	5.0/95.0	35.1 (242)	97.7 (674)	102.2 (39.0)	4.88	140 7 (2.6)
15	13.6/86.4	37.4 (258)	103.4 (713)	99.6 (37.6)	4.92	149.7 (2.6) 160.1 (2.8)
1.7	15.0/ 60.4	37.4 (230)	103.4 (713)	99.0 (37.0)	4.92	100.1 (2.8)
	134E/HFC-227	lea				
	5.0/95.0	34.3(237)	95.8(661)	102.3(39.1)	4.89	147.5(2.6)
	95.0/5.0	18.9(130)	57.1(394)	122.6(50.3)	6.16	114.7(2.0)
20	7.3/92.7*	36.0 (248)	141.7 (977)		3.2	•
	_					
	= Condense	$er = 130^{\circ}F$ , eva	$porator = 45^{\circ}F$	, and return gas	$s = 65^{\circ}$ H	<b>.</b>
	124E /UEC 224	(an				
25	134E/HFC-236 5.0/95.0	12.7(87)	40.6(280)	105 9/41 0\	<i>5 A</i> 1	70 5/1 0)
.23	95.0/5.0	15.0(103)	49.8(343)	105.8(41.0) 117.8(47.7)	5.41 5.52	70.5(1.2)
	99/1	13.5(93)	44.8(309)	142.3(61.3)	5.52 5.50	88.9(1.6)
	78.0/22.0	14.2(98)	46.2(318)	` ,	5.59	81.5(1.4)
	1/99	11.8(81)	62.1(428)	137.7(58.7) 152.1(66.7)	5.57 3.33	83.5(1.5)
30	1/37	11.0(01)	02.1(426)	132.1(00.7)	3.33	58.0(1.0)
50	134E/HFC-23	6ch				
	5.0/95.0	17.7 (122)	53.5 (369)	101.2 (38.4)	5.28	90.4 (1.6)
	36.3/63.7	22.3 (154)	66.2 (456)	104.1 (40.1)	5.26	111.8 (2.0)
	95.0/5.0	15.8 (109)	51.6 (356)	118.0 (47.8)	5.61	93.8 (1.7)
35	30.070.0	15.6 (10)	31.0 (330)	110.0 (47.0)	2.01	95.0 (1.7)
	134E/HFC-23	беа				
· · · ·	5.0/95.0	14.7 (101)	46.2 (319)	104.9 (40.5)	5.36	79.4 (1.4)
	52.8/47.2	19.1 (132)	59.2 (408)	108.9 (42.7)	5.35	102.2 (1.8)
	95.0/5.0	15.2 (105)	50.2 (346)	118.0 (47.8)	5.54	90.0 (1.6)
40	•		(* -7			7 010 (210)
	134E/HFC-23	6fa				
	5.0/95.0	19.5(135)	58.3(402)	100.7(38.2)	5.25	97.7(1.7)
	95.0/5.0	16.1(111)	52.0(359)	119.1(48.4)	5.65	95.3(1.7)
	14.2/85.8*	21.2 (146)	91.1 (628)	148.6 (64.8)	3.50	94.3 (1.7)
45	11.27 00.0	21.2 (1.0)	71.1 (020)	140.0 (04.0)	5.50	77.3 (1.7)
	* = Condens	er = 130°F, eva	aporator = $45^{\circ}$	F, and return ga	s = 65°	T.
	Condons		-p	-, una rotuin ga	ພ — <b>ບ</b> ລ	<b>4</b> •
	134E/HFC-24					
	5.0/95.0	6.9(47)	23.9(164)	111.7(44.3)	5.58	42.7(0.8)
50	95.0/5.0	14.4(99)	47.9(331)	117.2(47.3)	5.50	85.2(1.5)

5						
	134E/HFC-	245cb				
	5.0/95.0	33.5 (231)	91.5 (631)	104.4 (40.2)	4.90	142.1 (2.5)
	28.5/71.5	32.8 (226)	91.8 (633)	103.6 (39.8)	5.03	147.3 (2.6)
10	95.0/5.0	16.5 (114)	53.1 (366)	119.5 (48.6)	5.69	97.9 (1.7)
10	134E/HFC-	245ea				
	5.0/95.0	6.7(46)	23.7(164)	115.2(46.2)	5.59	42.5(0.7)
	95.0/5.0	14.2(98)	47.6(328)	117.6(47.6)	5.49	84.5(1.5)
15	134E/HFC-					
	5.0/95.0	10.7(74)	35.0(241)	108.2(42.3)	5.46	61.5(1.1)
	95.0/5.0	14.6(101)	49.2(339)	117.8(47.7)	5.44	86.4(1.5)
	134E/HFC-			,		
20	5.0/95.0	6.5(45)	22.5(155)	113.5(45.3)	5.59	40.5(0.7)
	95.0/5.0	14.1(97)	47.4(327)	117.6(47.6)	5.48	84.1(1.5)
	134E/HFC-		50.0 (0.50)	105 1 (11 5)	<b>5.00</b>	20.044.6
25	5.0/95.0	17.4 (120)	52.0 (359)	107.1 (41.7)	5.39	90.8 (1.6)
25	29.7/70.3	19.4 (134) 15.2 (105)	58.0 (400) 50.4 (347)	108.5 (42.5)	5.39	101.2 (1.8)
	95.0/5.0	13.2 (103)	50.4 (347)	118.1 (47.8)	5.53	90.1 (1.6)
	134E/HFC		00.0 (570)	150 0 (50 5)	2.4	00.444.6
30	28.6/71.4	19.0 (131)	82.9 (572)	159.2 (70.7)	3.64	90.4 (1.6)
50	* = Conde	enser = 130°F, eva	porator = 45°	F, and return ga	$as = 65^{\circ}I$	₹.
	·				•	
35	134E/HFC					
	5.0/95.0	8.8(61)	28.6(197)	113.5(45.3)	5.57	51.9(0.9)
	95.0/5.0	14.4(99)	47.8(330)	117.4(47.4)	5.50	85.1(1.5)
	134E/HFC				• _	
40	5.0/95.0	28.0(193)	78.8(543)	106.5(41.4)	5.28	134.1(2.4)
·	95.0/5.0	16.1(111)	52.5(362)	119.4(48.6)	5.60	95.2(1.7)
	134E/HFC	•				
مع و	5.0/95.0	17.5(121)	51.2(353)	111.7(44.3)	5.44	91.0(1.6)
45	95.0/5.0	15.2(105)	50.0(345)	118.0(47.8)	5.51	89.3(1.6)
-	134E/HFC		00.4/004	440.0440.01	<b></b>	
	5.0/95.0	9.8(67)	32.1(221)	119.8(48.8)	5.52	57.7(1.0)
50	95.0/5.0	14.1(97)	47.3(326)	118.1(47.8)	5.50	84.1(1.5)

5	134E/HFC-	272fb				
-	5.0/95.0	12.7(88)	40.1(276)	117.5(47.5)	5.51	72.3(1.3)
	95.0/5.0	14.4(100)	48.2(332)	117.9(47.7)	5.50	85.8(1.5)
	2010/010	2111(200)	10.2(332)	111.5(41.1)	2.50	05.0(1.5)
	134E/HFC-	281ea				
10	5.0/95.0	24.0(166)	67.9(468)	116.7(47.1)	5.47	121.8(2.1)
10	95.0/5.0	15.5(107)	51.0(351)	118.8(48.2)	5.52	91.3(1.6)
	, , , , , , , , , , , , , , , , , , , ,	13.5(107)	31.0(331)	110.0(40.2)	عرب.د	91.5(1.0)
	134E/HFC-	281fa			•	
	5.0/95.0	18.7(129)	55.3(381)	117.1(47.3)	5.50	99.8(1.8)
15	95.0/5.0	15.2(105)	49.6(342)	118.0(47.8)	5.57	89.7(1.6)
	22.072.0	25.2(205)	13.0(3.12)	110.0(47.0)	J.J 1	05.7(1.0)
	134E/HFC-	338mf				
	5.0/95.0	10.5 (72)	34.7 (239)	95.3 (35.2)	5.35	58.5 (1.0)
	65.5/34.5	18.8 (130)	59.8 (412)	108.2 (42.3)	5.21	99.7 (1.8)
20	95.0/5.0	15.7 (108)	51.6 (356)	118.1 (47.8)	5.62	93.1 (1.6)
				11011 (1710)	5.02	75.1 (1.0)
	236caE/HF	C-125		·		
	5.0/95.0	90.0(621)	242.9(1675)	127.5(53.1)	4.33	330.6(5.8)
	95.0/5.0	9.0(62)	30.8(212)	119.3(48.5)	6.26	61.3(1.1)
25	·	, ,	` ,			
	236caE/HF	C-134				
	5.0/95.0	35.3(243)	103.9(716)	129.2(54.0)	<b>5.2</b> 8	179.7(3.2)
	95.0/5.0	6.9(48)	25.0(172)	110.7(43.7)	5.68	44.9(0.8)
			. ,			` ,
30	236caE/HF	C-134a				
	5.0/95.0	44.5(307)	129.1(890)	121.1(49.5)	5.13	213.3(3.7)
	95.0/5.0	7.2(50)	26.0(179)	111.8(44.3)	5.74	47.3(0.8)
	236caE/HF		•			•
35	5.0/95.0	14.1(97)	44.2(305)	134.3(56.8)	5.60	82.1(1.4)
	95.0/5.0	6.1(42)	22.5(155)	107.2(41.8)	5.49	38.9(0.7)
• •	236caE/HF	_				
	5.0/95.0	90.0(621)	232.8(1605)	160.3(71.3)	4.68	361.3(6.3)
40	95.0/5.0	9.6(66)	33.1(228)	123.6(50.9)	6.18	64.9(1.1)
	00 C T /TT	20.450				
	236caE/HF		404040			
	5.0/95.0	43.5(300)	121.3(836)	143.5(61.9)	5.34	215.6(3.8)
45	95.0/5.0	7.9(54)	28.2(194)	115.9(46.6)	5.82	51.9(0.9)
45	006 - T /III	20.161				
	236caE/HF		100 ((10.15)	440 F//4 A		
	5.0/95.0	69.0(476)	180.6(1245)	142.5(61.4)	5.22	311.7(5.5)
	95.0/5.0	10.1(70)	36.1(249)	126.8(52.7)	5.90	67.4(1.2
50	226anT2 /TTT	CC 227an				
50	236caE/HF		07 5/603\	00 0/27 0\	4.00	105.000.00
	5.0/95.0	30.5(210)	87.5(603)	99.0(37.2)	4.93	135.8(2.4)

				81			
5	95.0/5	.0	6.6(46)	23.8(164)	107.9(42.2)	5.67	42.7(0.8)
	236caT	E/HFC-22	27ea				
	5.0/95		29.8(205)	95.7(591)	98.9(37.2)	4.95	133.6(2.3)
	95.0/5		6.6(46)	23.7(163)	107.6(42.0)	5.67	42.5(0.7)
10	•	.0	0.0(40)	25.7(105)	107.0(42.0)	3.07	42.5(0.1)
10		E/HFC-23	36ca				
	5.0/95	•	11.3(78)	36.9(254)	104.4(40.2)	5.37	63.5(1.1)
			5.7(39)	21.4(147)	104.2(40.1)	5.44	•
	95.0/5	0.0	3.7(39)	21.4(147)	104.2(40.1)	J.44	36.5(0.6)
15	23600]	E/HFC-2	36ch				
13	5.0/95	•	15.5(107)	47.9(330)	100.9(38.3)	5.25	80.4(1.4)
	•		5.8(40)	` '	104.4(40.2)		•
	95.0/5	0.0	3.6(40)	21.7(149)	104.4(40.2)	5.46	37.2(0.7)
	236ca	E/HFC-2	36fa				
20		•	17.3(119)	52.8(364)	100.2(37.9)	5.21	87.9(1.5)
	95.0/5		6.0(41)	22.2(153)	105.1(40.6)	5.50	38.3(0.7)
	236ca	E/HFC-2	45cb				
	5.0/95	5.0	29.8(205)	84.4(582)	100.1(37.8)	4.96	132.8(2.3)
25	95.0/5	5.0	6.4(44)	23.4(161)	106.8(41.6)	5.59	41.2(0.7)
	006	T // TO 0	4.5				
		E/HFC-2		01 0/151)	110 0/// 0)	<i>5.5</i> 0	20.0(0.5)
	5.0/95		6.1(42)	21.9(151)	112.9(44.9)	5.53	38.8(0.7)
24	95.0/	5.0	5.5(38)	20.7(143)	104.1(40.1)	5.42	35.2(0.6)
30			AFF-				
		E/HFC-2		20.2(222)	107.0/41.7\	. 530	55 O(1 O)
	5.0/9		9.7(67)	32.3(223)	107.0(41.7)	5.38	55.9(1.0)
	95.0/	<b>5.</b> 0 .	5.7(39)	21.2(146)	104.1(40.1)	5.43	36.2(0.6)
3:	5 236ca	E/HFC-2	254ca				
<b>.</b>	5.0/9	•	6.0(41)	21.0(145)	111.3(44.1)	5.54	37.3(0.7)
	95.0/		5.5(38)	20.6(142)	104.1(40.1)	5.43	35.2(0.6)
							()
	236ca	aE/HFC-2	254cb	·	•	•	
4	0 5.0/9	5.0	16.0(111)	48.8(336)	107.5(41.9)	5.37	84.8(1.5)
	95.0/	<b>'5.0</b>	6.0(41)	22.1(152)	105.3(40.7)	5.47	38.0(0.7)
			;_				
		aE/HFC-					
	5.0/9		16.3(113)	49.6(342)	107.5(41.9)	5.37	86.1(1.5)
4	5 95.0/	/5.0	6.0(41)	22.1(153)	105.3(40.7)	5.47	38.2(0.7)
	236c	aE/HFC-	263ca				
•	5.0/9	•	8.3(57)	27.8(187)	112.4(44.7)	5.53	48 8(0 0)
	95.0		5.7(39)	21.1(145)	•	5.44	48.8(0.9)
5	93.0 <sub>/</sub> 50	73.0	3.7(39)	21.1(143)	104.4(40.2)	. J. <del>44</del>	36.1(0.6)
~		aE/HFC	263fb				
				•			
•				,			
		·			·		
	•					•	
	٠.				•		

_		24.244.72				10000
5	5.0/95.0	26.0(179)	74.5(514)	108.5(42.5)	5.26	126.3(2.2)
	95.0/5.0	6.5(45)	23.6(163)	107.5(41.9)	5.57	41.5(0.7)
	236caE/HF0	C-272ca				
	5.0/95.0	16.7(115)	49.0(338)	112.2(44.6)	5.46	87.3(1.5)
10	95.0/5.0	6.1(42)	22.5(155)	106.1(41.2)	5.49	39.0(0.7)
	00 ( D (III)	C 070				
	236caE/HF0		20.7/211)	117 0/17 7	5.60	<i>57 1/1 0</i> )
	5.0/95.0	9.6(66) 5.8(40)	30.7(211)	117.9(47.7)	5.68	57.1(1.0)
15	95.0/5.0	3.6(40)	21.6(149)	105.4(40.8)	5.44	37.0(0.7)
15	236caE/HF	C-272fb				
	5.0/95.0	12.2(84)	38.9(268)	117.5(47.5)	5.48	69.7(1.2)
	95.0/5.0	6.0(41)	22.1(152)	105.8(41.0)	5.46	38.0(0.7)
20	236caE/HF	C-281ea			•	
20	5.0/95.0	23.2(160)	66.2(456)	117.8(47.7)	5.46	118.4(2.1)
	95.0/5.0	6.8(47)	24.4(169)	109.1(42.8)	5.58	43.2(0.8)
	226 co E /UE	C 2016a				
25	236caE/HF 5.0/95.0	18.2(125)	54.5(376)	117.5(47.5)	5.51	97.4(1.7)
<b>4</b> .7	95.0/5.0	6.5(45)	23.4(163)	107.9(42.2)	5.53	41.3(0.7)
	•		` ,	, ,		
	236eaEβγ/I		- 4 T O (4 T O T)			
20	•	93.0(641)	245.9(1695)	125.0(51.7)	4.39	338.5(5.9)
30	95.0/5.0	10.4(72)	35.5(245)	116.6(47.0)	6.00	67.6(1.2)
	236eaΕβγ/	HFC-134				
	5.0/95.0	36.1(249)	104.5(721)	127.2(52.9)	5.35	183.1(3.2)
25	95.0/5.0	8.3(58)	29.5(204)	108.7(42.6)	5.60	52.3(0.9)
35	236eaΕβγ/	HEC-134a				
	5.0/95.0	45.5(314)	130.6(900)	119.7(48.7)	5.16	217.2(3.8)
	95.0/5.0	8.6(59)	30.6(211)	109.5(43.1)	5.65	54.3(1.0)
	· .		` ,			
40	236eaΕβγ/					
	5.0/95.0	14.3(97)	44.6(307)	134.4(56.9)	5.56	82.2(1.4)
	95.0/5.0	7.4(51)	26.6(1840	105.5(40.8)	5.43	45.8(0.8)
	236eaEβγ/	HFC-143a	•			
45	5.0/95.0	90.0(621)	232.8(1605)	160.3(71.3)	4.68	361.3(6.3)
	95.0/5.0	9.6(66)	32.8(226)	123.3(50.7)	6.23	65.1(1.1)
	236eaΕβγ/	/HFC-152a				•
	5.0/95.0	44.3(305)	122.5(844)	142.1(61.2)	5.38	219.0(3.8)
50	95.0/5.0	9.5(65)	32.8(226)	113.6(45.3)	5.72	59.7(1.0)
						• •

5	236eaΕβγ/H	IFC-161				
	5.0/95.0	69.6(480)	181.5(1251)	141.7(60.9)	5.23	313.9(5.5)
	95.0/5.0	11.7(81)	39.8(274)	121.8(49.9)	5.91	75.0(1.3)
	236eaΕβγ/H	IFC-227ca				
10	5.0/95.0	30.9(213)	88.3(609)	102.1(38.9)	4.88	135.9(2.4)
	95.0/5.0	7.9(54)	27.9(193)	105.6(40.9)	5.57	49.2(0.9)
	236eaΕβγ/I	HFC-227ea				
	5.0/95.0	30.3(209)	86.5(596)	102.0(38.9)	4.90	133.7(2.3)
15	95.0/5.0	7.9(54)	27.9(192)	105.5(40.8)	5.50	48.9(0.9)
	236eaΕβγ/I	HFC-236ca				
	5.0/95.0	11.4(79)	37.3(257)	104.3(40.2)	5.32	63.6(1.1)
20	95.0/5.0	7.0(48)	25.7(177)	103.2(39.6)	5.32	42.9(0.8)
20	236eaΕβγ/]	HFC-236cb				
•	5.0/95.0	15.9(110)	48.9(337)	100.0(37.8)	5.24	81.8(1.4)
	95.0/5.0	7.2(50)	26.1(180)	103.2(39.6)	5.42	44.7(0.8)
25	236eaEβγ/	HFC-236fa				
	5.0/95.0	17.6(121)	53.3(368)	104.1(40.1)	5.16	88.1(1.6)
	95.0/5.0	7.3(51)	26.4(182)	103.6(39.8)	5.42	45.3(0.8)
	236eaEβγ/	HFC-245ca				,
30	5.0/95.0	6.2(43)	21.9(151)	109.0(42.8)	5.50	38.6(0.7)
	95.0/5.0	6.8(47)	24.7(170)	102.8(39.3)	5.39	41.9(0.7)
,		HFC-245cb	•			
	5.0/95.0	30.3(209)	85.2(587)	99.8(37.7)	4.96	134.3(2.4)
35	95.0/5.0	7.7(53)	27.5(190)	104.7(40.4)	5.50	47.9(0.8)
· ·	236eaΕβγ/	HFC-245ea				
	5.0/95.0	6.2(42)	22.1(152)	112.9(44.9)	5.53	39.0(0.7)
	95.0/5.0	6.8(47)	24.7(170)	103.0(39.4)	5.39	41.9(0.7)
40						-
		/HFC-245fa		400000	P 14	5'2 5'4 O
	5.0/95.0	9.8(68)	32.5(224)	106.6(41.4)	5.41	56.5(1.0)
	95.0/5.0	6.9(48)	25.3(175)	103.0(39.4)	5.36	42.8(0.8)
45		/HFC-254ca		444 8814 48		
	5.0/95.0	6.0(41)	21.1(146)		5.53	37.5(0.7)
	95.0/5.0	6.8(47)	24.6(170)	103.0(39.4)	5.39	41.9(0.7)

5	236eaΕβγ/H	FC-254cb				
	5.0/95.0		49.1(338)	107.0(41.7)	5.38	85.6(1.5)
	95.0/5.0	8.2(57)	26.2(181)	103.0(39.4)	6.04	50.9(0.9)
	236ea <b>Ε</b> βγ/Η	IFC-254eb				
10	5.0/95.0	16.5(114)	49.9(344)	106.9(41.6)	5.38	86.8(1.5)
	95.0/5.0	7.3(50)	26.3(181)	103.8(39.9)	5.42	45.0(0.8)
	236eaΕβγ/H	IFC-263ca				
	5.0/95.0	8.3(57)	27.3(188)	112.2(44.6)	5.54	49.1(0.9)
15	95.0/5.0	6.9(48)	25.1(173)	103.2(39.6)	5.39	42.7(0.8)
	236eaΕβγ/H	IFC-263fb				
	5.0/95.0	26.3(181)	75.0(517)	107.8(42.1)	5.27	127.6(2.2)
	95.0/5.0	7.8(54)	27.8(192)	105.5(40.8)	5.49	48.2(0.8)
20	236ea <b>Ε</b> βγ/Η	JFC-272ca				
	5.0/95.0	•	49.3(340)	111.6(44.2)	5.47	88.2(1.5)
	95.0/5.0	• • • • • • • • • • • • • • • • • • • •	26.8(184)	104.6(40.3)	5.43	46.0(0.8)
25	236eaΕβγ/I	IFC-272ea				
	5.0/95.0		31.1(214)	118.6(48.1)	5.57	56.6(1.0)
	95.0/5.0	7.1(49)	25.6(176)	103.9(39.9)	5.41	43.8(0.8)
	236eaΕβγ/I	HFC-272fb				
30	5.0/95.0	12.4(85)	39.1(269)	117.1(47.3)	5.51	70.4(1.2)
	95.0/5.0	7.3(50)	26.2(181)	104.3(40.2)	5.41	44.8(0.8)
	236eaEβγ/I	HFC-281ea			·	
	5.0/95.0	23.4(162)	66.6(459)	117.3(47.4)	5.46	119.2(2.1)
35	95.0/5.0	8.1(56)	28.6(197)	107.0(41.7)	5.50	49.9(0.9)
	236eaΕβγ/]	HFC-281fa				
. ,	5.0/95.0	18.3(126)	54.3(375)	117.4(47.4)	5.49	98.0(1.7)
	95.0/5.0	7.8(54)	27.8(192)	106.0(41.1)	<b>5.4</b> 6	48.0(0.8)
40	2266012 /1310	C 125				
	236faE/HF		252 0/17/2\	110 0/40 0\	4.40	254 1/6 2)
	5.0/95.0 95.0/5.0	99.6(687) 17.4(120)	252.9(1743) 54.6(377)	119.9(48.8) 103.8(39.9)	4.49 5.51	354.1(6.2) 95.4(1.7)
45	236faE/HF	C-134				
43	5.0/95.0	37.6(259)	108.1(745)	125.3(51.8)	5.33	100 //2 2\
	•	15.8(109)	50.6(349)	•	5.29	188.4(3.3)
	95.0/5.0	12.0(103)	30.0(349)	100.6(38.1)	J.4 <del>y</del>	85.0(1.5)

5	236faE/HFC	C-134a			٠:	•
	5.0/95.0	48.2(332)	135.5(934)	116.5 (46.9)	5.19	226.2(4.0)
	95.0/5.0	16.2(112)	51.7(356)	101.1 (38.4)	5.33	87.4(1.5)
	236faE/HFC					
10	5.0/95.0	14.5(100)	45.5(314)	133.6 (56.4)	5.58	84.1(1.5)
	95.0/5.0	14.5(100)	46.6(321)	103.5 (39.7)	5.17	76.7(1.3)
	236faE/HF0					
	5.0/95.0	96.7(667)	241.0(1662)	152.6 (67.0)	4.81	382.2(6.7)
15	95.0/5.0	18.3(126)	56.9(392)	106.6 (41.4)	5.58	101.1(1.8)
	236faE/HF					
	5.0/95.0	45.7(315)	125.1(863)	140.1 (60.1)	5.39	224.3(3.9)
	95.0/5.0	17.1(118)	54.2(374)	103.9 (39.9)	5.37	- 92.6(1.6)
20						
	236faE/HF					
	5.0/95.0	72.2(498)	185.7(1280)	138.9 (59.4)	5.27	322.7(5.7)
	95.0/5.0	20.6(142)	63.3(436)	110.6 (43.7)	5.65	113.9(2.0)
25	236faE/HF					
	5.0/95.0	31.9(220)	90.1(621)	101.5 (30.6)	4.87	138.3(2.4)
	95.0/5.0	14.8(1020	47.7(329)	101.5 (38.6)	5.16	78.0(1.4)
	236faE/HF					
30	5.0/95.0	31.1(215)	88.3(609)	101.6 (38.7)	4.88	135.8(2.4)
	95.0/5.0	14.7(101)	47.6(328)	101.5 (38.6)	5.16	77.8(1.4)
	236faE/HF					
	5.0/95.0	11.8(81)	38.1(263)	103.7 (39.8)	5.35	65.4(1.1)
35	95.0/5.0	13.8(95)	45.0(310)	102.1 (38.9)	5.12	73.1(1.3)
	236faE/HI					
	5.0/95.0	16.3(112)	49.8(343)	104.2 (40.1)	5.17	82.5(1.4)
,	95.0/5.0	14.1(97)	45.8(316)	101.8 (38.8)	5.12	74.3(1.3)
40						
** ** ,	236faE/HI	•			- 10	00.444.6
	5.0/95.0	18.0(124)	54.3(375)	•	5.13	` '
	95.0/5.0	14.2(98)	46.0(317)	101.8 (38.8)	5.12	74.6(1.3)
45	236faE/H					
	5.0/95.0	6.4(44)	22.5(155)	•	5.51	39.7(0.7)
	95.0/5.0	13.2(91)	43.3(299)	102.3 (39.1)	5.18	71.1(1.2)

PCT/US93/04614

86

			50			
5	236faE/HFC	C-245cb				
	5.0/95.0	31.6(218)	87.4(603)	109.0 (42.8)	4.84	134.4(2.4)
	95.0/5.0	14.8(102)	47.5(328)	106.5 (41.4)	5.09	76.9(1.4)
	236faE/HFC	C-245ea				•
10	5.0/95.0	6.4(44)	22.7(157)	113.1 (45.1)	5.54	40.3(0.7)
	95.0/5.0	13.3(92)	43.6(301)	102.4 (39.1)	5.17	71.6(1.3)
	236faE/HFC	C-245fa				
•	5.0/95.0	10.1(70)	33.3(230)	106.3 (41.3)	<b>5.40</b>	57.9(1.0)
15	95.0/5.0	13.7(94)	44.6(308)	102.0 (38.9)	5.16	72.9(1.3)
	236faE/HFC	C-254ca				
	5.0/95.0	6.2(43)	21.6(149)	111.5 (44.2)	5.55	38.6(0.7)
	95.0/5.0	13.2(91)	43.3(299)	102.6 (39.2)	5.17	70.9(1.2)
20	00 CE TI /ETT	0.054.1				
	236faE/HF0		50.2(246)	106 1 (41 2)	5 27	07 1/1 5\
	5.0/95.0	16.6(114)	50.2(346)	106.1 (41.2)	5.37 5.14	87.1(1.5)
	95.0/5.0	14.1(97)	45.8(316)	102.2 (39.0)	2.14	74.6(1.3)
25	236faE/HF			•		
	5.0/95.0	16.9(117)	51.0(352)	106.0 (41.1)	5.36	88.4(1.6)
	95.0/5.0	14.1(97)	45.9(316)	102.3 (39.1)	5.13	74.7(1.3)
	236faE/HF	C-263ca				
30	5.0/95.0	8.5(59)	28.0(193)	112.5 (44.7)	5.49	49.9(0.9)
	95.0/5.0	13.5(93)	43.9(303)	102.6 (39.2)	5.17	72.0(1.3)
· 	236faE/HF	C-263fb				
	5.0/95.0	27.0(186)	76.9(530)	106.6 (41.4)	5.22	129.2(2.3)
35	95.0/5.0	14.8(102)	47.6(328)	102.3 (39.1)	5.16	77.8(1.4)
	236faE/HF	C-272ca				
	5.0/95.0	17.2(119)	50.1(345)	110.8 (43.8)	5.47	89.6(1.6)
-	95.0/5.0	14.3(99)	46.1(318)	102.8 (39.3)	5.14	75.3(1.3)
40	00 CC TO IT	000				
	236faE/HF		24.0/040\	1100 (400)	5 50	57 4/1 (1)
•	5.0/95.0	9.7(67)	31.8(219)	118.9 (48.3)	5.52	57.4(1.0)
	95.0/5.0	13.8(95)	44.8(309)	103.2 (39.6)	5.15	73.3(1.3)
45						
	5.0/95.0	12.6(87)	39.8(274)		5.52	71.8(1.3)
	95.0/5.0	14.1(97)	45.5(314)	103.0 (39.4)	5.15	74.6(1.3)

	5.0/95.0 95.0/5.0	23.9(165) 15.2(105)	67.6(466) 48.4(334)	116.3 (48.0) 103.3 (39.6)	5.45 5.19	120.9(2.1) 79.9(1.4)
	•	. ,	` /	( · · · · · · /		` '
10	236faE/HFC		55 4/000\	44664470	<i>5</i>	00 4/4 5\
	5.0/95.0	18.7(129)	55.1(380)	116.6 (47.0)	5.50	99.4(1.7)
	95.0/5.0	14.8(102)	47.4(327)	103.3 (39.6)	5.18	78.0(1.4)
	245faEβγ/H					
15	5.0/95.0	88.9(613)	240.9(1661)	128.2 (53.4)	4.33	328.4(5.8)
	95.0/5.0	8.9(61)	30.1(208)	121.1 (49.5)	6.35	60.9(1.1)
	245faEβγ/H				•	
	5.0/95.0	34.6(239)	101.7(701)	129.6 (54.2)	5.32	177.2(3.1)
20	95.0/5.0	6.6(46)	23.9(165)	111.6 (44.2)	5.68	43.0(0.8)
	245faΕβγ/H				_	
	5.0/95.0	43.4(299)	127.2(877)	122.3 (50.2)	5.11	209.7(3.7)
25	95.0/5.0	6.9(48)	24.8(171)	112.7 (44.8)	5.75	45.2(0.8)
	$245 \text{faE}\beta\gamma/\text{H}$	IFC-143				
	5.0/95.0	13.9(96)	44.3(305)	135.4 (57.4)	<b>5.50</b>	80.7(1.4)
	95.0/5.0	5.9(41)	21.7(150)	108.6 (42.6)	5.51	37.9(0.7)
30	245faΕβγ/H					
	5.0/95.0	89.2(615)	231.5(1596)	161.1 (71.7)	4.66	359.0(6.3)
•	95.0/5.0	9.4(65)	31.9(220)	124.7 (51.5)	6.31	64.2(1.1)
	245faEβγ/H					·
<b>35</b> .	5.0/95.0	42.8(295)	120.1(828)	144.4 (62.4)	5.33	213.0(3.7)
	95.0/5.0	7.5(52)	26.7(184)	116.5 (46.9)	5.81	49.2(0.9)
	245faEβγ/I		,			
	5.0/95.0	67.9(468)	178.9(1233)	` '	5.20	307.8(5.4)
40	95.0/5.0	9.6(66)	33.1(228)	126.0 (52.2)	6.06	64.3(1.1)
	$245$ fa $E\beta\gamma/I$					·
•	5.0/95.0	30.5(210)	87.6(604)	98.9 (37.2)	4.93	136.0(2.4)
45	95.0/5.0	6.5(45)	23.4(161)	109.9 (43.3)	5.76	42.7(0.8)
43	245faE8~/	HFC-227ea				
	5.0/95.0	29.9(206)	85.8(592)	98.8 (37.1)	4.95	133.9(2.4)
	95.0/5.0	6.5(45)	23.3(161)	109.8 (43.2)	5.74	42.5(0.7)
50	245faEβγ/	HFC-236ca				
	5.0/95.0	11.2(77)	37.1(256)	104.8 (40.4)	5.29	62.9(1.1)
			•			

5	95.0/5.0	5.6(39)	20.9(144)	106.0 (41.1)	5.47	36.1(0.6)
	245faΕβγ/H	FC-236cb				
	5.0/95.0	15.7(108)	48.4(334)	100.2 (37.9)	5.25	81.3(1.4)
	95.0/5.0	5.8(40)	21.5(148)	106.7 (41.5)	5.52	37.4(0.7)
10	33.070.0	210(10)	22.0(2.0)	10017 (1210)	0.02	
10	245faEβγ/H	FC-236fa				
	5.0/95.0	17.3(119)	52.6(363)	100.3 (37.9)	5.22	87.7(1.5)
	95.0/5.0	5.8(40)	21.6(149)	106.9 (41.6)	5.52	37.6(0.7)
	33.0/3.0	5.6(10)	21.0(115)	100.5 (11.0)		<i>57.15</i> (517)
15	245faΕβγ/H	FC-245ca	•			
	5.0/95.0	6.2(43)	21.8(150)	109.0 (42.8)	5.51	38.4(0.7)
	95.0/5.0	5.4(37)	20.2(139)	105.7 (40.9)	5.45	34.7(0.6)
	2210,210			(1117)		
	$245 \text{faE} \beta \gamma / \text{H}$	IFC-245cb				
20	5.0/95.0	29.7(205)	84.0(579)	100.1 (37.8)	4.97	132.6(2.3)
	95.0/5.0	6.3(43)	22.8(157)	108.5 (42.5)	5.64	40.7(0.7)
•	•	, ,				•
	$245 \text{faE} \beta \gamma / H$	IFC-245ea				
	5.0/95.0	6.1(42)	21.9(151)	112.9 (44.9)	5.53	38.8(0.7)
25	95.0/5.0	5.4(37)	20.2(139)	105.8 (41.0)	5.45	34.7(0.6)
	0455-700 (7)	TEO 0456-				
	$245$ faE $\beta\gamma$ /H		22.2/222	107.0 (41.7)	£ 20	55 O(1 O)
	5.0/95.0	9.7(67)	32.3(223)	107.0 (41.7)	5.38 5.37	55.9(1.0)
30	95.0/5.0	5.5(38)	20.9(144)	106.4 (41.3)	5.37	35.2(0.6)
30	245faΕβγ/H	IFC-254ca				
	5.0/95.0	6.0(41)	21.0(1450	111.3 (44.1)	5.54	37.3(0.7)
	95.0/5.0	5.4(37)	20.2(139)	105.7 (40.9)	5.46	34.7(0.6)
	33.073.0	. 3.1(31)	20.2(13)	105.7 (10.2)	5.40	34.7(0.0)
35	245faEβγ/I	HFC-254cb				
	5.0/95.0	16.0(110)	48.7(336)	107.6 (42.0)	5.37	84.6(1.5)
	95.0/5.0	5.8(40)	21.5(148)	107.0 (41.7)	5.51	37.5(0.7)
						<b>,</b>
• • • •	245faEβγ/I	HFC-254eb		•		
40	5.0/95.0	16.3(112)	49.4(341)	107.4 (41.9)	5.38	86.0(1.5)
	95.0/5.0	5.8(40)	21.6(149)	107.1 (41.7)	5.51	37.6(0.7)
					•	
	$245 \text{faE}\beta\gamma/1$			440 # 444 #1	# #A	40.5%
. :-	5.0/95.0	8.3(57)	27.2(188)	112.5 (44.7)	5.50	48.7(0.9)
45	95.0/5.0	5.5(38)	20.7(143)	106.4 (41.3)	5.41	35.2(0.6)
	245faF8~ /	HFC-263fb				
	5.0/95.0	25.9(179)	74.2(512)	108.7 (42.6)	5.26	126.0(2.2)
	95.0/5.0	6.3(43)	22.9(158)	109.1 (42.8)	5.62	40.8(0.7)
50	22.0/2.0	0.0 ( 1.0 )	, (200)		J.0 <b>_</b>	. 5.5(5.7)
	245faFβ~ /	HFC-272ca				
	J. Lune / /					

5	5.0/95.0 95.0/5.0	16.4(113) 6.0(41)	49.4(341) 22.0(152)	113.0 (45.0) 107.9 (42.2)	5.31 5.53	85.7(1.5) 38.5(0.7)			
	$245$ fa $E\beta\gamma/H$	IFC-272ea							
•	5.0/95.0	9.4(65)	30.9(213)	118.9 (48.3)	<b>5.5</b> 5	56.0(1.0)			
10	95.0/5.0	5.6(39)	21.2(146)	107.5 (41.9)	5.40	35.7(0.6)			
	245faEβγ/HFC-272fb								
	5.0/95.0	12.2(84)	38.9(268)	117.8 (47.7)	5.46	69.4(1.2)			
	95.0/5.0	5.8(40)	21.5(148)	107.3 (41.8)	5.50	37.2(0.7)			
15	•	•				-			
	245faEβγ/H	IFC-281ea							
	5.0/95.0	23.1(159)	65.9(454)	118.1 (47.8)	5.45	117.8(2.1)			
	95.0/5.0	6.5(45)	23.6(163)	110.5 (43.6)	<b>5.60</b>	42.0(0.7)			
20	245faEβγ/F	IFC-281fa							
	5.0/95.0	18.1(125)	53.9(372)	117.9 (47.7)	5.48	97.0(1.7)			
	95.0/5.0	6.3(43)	22.9(158)	109.3 (42.9)	5.55	40.2(0.7)			
	•		<b>\</b>	- 30 10 (1-10)		.0.2(0.7)			

#### **EXAMPLE 5**

25

30

The following table shows the refrigerant performance of various compositions. The data are based on the following conditions.

Evaporator temperature 10.0°F (-12.2°C)

Condenser temperature 90.0°F (32.2°C)

Return gas temperature 30.0°F (-1.1°C)

Compressor efficiency is 75%.

#### TABLE 6

35		Evap.	Cond.			(	Capacity
	Refrig.	Press.	Press.	Comp. Dis.	•		BTU/min
. •	Comp.	Psia (kPa)	Psia (kPa)	Temp. °F (°C	C)	COP	(kw)
40	HCFC-22	47.9(330)	183.6(1266)	179.1(81.7)	3.62	217.7	(3.8)
	116E/HFC-32				-		
	88/12	85.4(589)	312.7(2157)	127.7(53.2)	3.01	283.6	(5.0)
	75.2/24.8	79.4(547)	296.6(2046)	135.7(57.6)	3.24	294.9	•
45	50/50	76.2(525)	289.2(1995)	149.0(65.0)	3.39	308.3	•
45	116E/HFC-41°	•					
	84/16	39.6(273)	206.2(1422)	127.4(53.0)	3.05	182.9	(3.2)

5	58.6/41.4	52.8(364)	219.6(1515)	149.6(65.3)	3.32	237.7(4.2)
-	30/70	68.9(475)	274.0(1890)	179.7(82.1)	3.15	294.4(5.2)
				20.00E and Da	co	s tamp = 10 0°F
	*Condenser	temp. 50.0°F, Ev	aporator temp.	30.0°F, and Re	turn ga	s temp10.0 r
10	116E/HFC-:	125				
	99/1*	82.2(567)	304.0(2097)	101.4(38.6)	2.87	254.9(4.5)
	86.0/14.0	96.5(665)	338.9(2338)	121.4(49.7)	2.73	273.5(4.8)
	1/99	64.8(447)	237.2(750)	132.5(55.8)	3.28	240.1(4.2)
	5.0/95.0	66.5(458)	242.1(1669)	131.7(55.4)	3.27	243.8(4.3)
15	95.0/5.0	98.5(679)	319.1(2200)	113.8(45.4)	2.21	211.7(3.7)
1.5	•	, ,	•	, ,		, ,
	*Condenser	temp. 80.0°F, E	vaporator temp.	0.0°F, and Reti	urn gas	temp. 10.0°F
	116E/HFC-	134				
20	90.2/9.8	103.9 (716)	319.9 (2206)	112.1 (44.5)	3.24	314.2 (5.5)
	116E/HFC-		20( 1/2112)	110 2/42 4)	275	217 2(1 1)
	99/1*	82.8(571)	306.1(2112)	110.2(43.4)	2.75	247.3(4.4) 299.7(5.3)
	90.0/10.0	103.0(710)	332.4(2293)	115.0(46.1)	3.00	• •
<b>2</b> 5	53/47	63.1(435)	265.2(1829)	121.2(49.6)	2.78	215.4(3.8)
	5.0/95.0	34.9(241)	138.2(953)	129.7(54.3)	4.04	172.6(3.0)
	95.0/5.0	101.9(702)	356.2(2456)	120.7(49.3)	2.62	274.5(4.8)
	*Condense	r temp. 80°F, Ev	aporator temp. 0	0.0°F, and Retu	rn gas t	emp. 20.0°F
30			•	·		_
-	116E/HFC	-143				
	99/1	98.2(677)	345.7(2385)	120.2(49.0)	2.66	270.3(4.8)
	94.9/5.1	43.3(298)	241.2(1664)	139.7(59.8)	2.38	155.0(2.7)
	60/40	27.3(188)	112.9(779)	131.0(55.0)	4.28	169.5(3.0)
35	• .					
	116E/HFC	C-143a				
	99/1*	82.2(567)	304.1(2098)	110.5(43.6)	2.76	247.5(4.4)
	94.8/5.2*	81.8(564)	301.6(2081)	112.8(44.9)	2.81	250.8(4.4)
	40/60	75.9(523)	270.0(1863)	155.6(68.7)	3.29	283.4(5.0)
40		62.4(430)	226.2(1559)	182.0(83.3)	3.42	255.2(4.5)
	95.0/5.0	98.7(681)	318.9(2199)	115.6(46.4)	2.32	223.7(3.9)
	*Condense	er temp. 80.0°F,	Evaporator temp	o. 0.0°F, and Re	eturn ga	s temp. 20.0°F
			•	•	-	
45	•		A = 0 (A < = 0)	444 //44 ^\	0.40	202 5/5 2
	99/1	100.2(691)	315.8(2179)	111.6(44.2)		` '
	92.1/7.9	102.9(710)	320.1(2208)	114.7(45.9)	<b>1</b>	
	60/40	60.0(414)	250.1(1725)	148.5(64.7)	/	
	5.0/95.0	32.4(224)		161.5(71.9)	•	` '
50	95.0/5.0	102.6(707)	335.9(2316)	117.4(47.4	) 2.76	278.2(4.9)

99/1 57/4(396) 243.5(1680) 102.4(39.1) 2.92 206.7(3.6) 87.3/12.7 32.4(223) 149.6(1032) 91.5(33.1) 3.79 166.8(2.9) 166.8(2.9) 125.1(152) 126.1(870) 151.7(66.5) 3.33 119.3(2.1)  10 °Condenser temp. 70.0°F, Evaporator temp10.0°F, and Return gas temp. 10.0°F 116E/HFC-227ca 5.0/95.0 20.9(143) 89.9(620) 108.0(42.2) 3.69 97.7(3.5) 95.0/5.0 92.3(636) 331.4(2285) 119.9(48.8) 2.67 259.8(4.6)  15 16E/HFC-227ea 5.0/95.0 16.7(115) 78.3(540) 104.4(40.2) 3.67 82.2(1.4) 95.0/5.0 92.3(636) 333.0(2296) 119.9(48.8) 2.66 259.2(4.6)  20 116E/HFC-236ca 5.0/95.0 16.2 (112) 72.9 (503) 149.7 (65.4) 3.93 84.2 (1.5) 95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F 116E/HFC-236ca 5.0/95.0 13.5(7) 85.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ca 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236ca 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.67 251.6(4.4)  116E/HFC-245ca 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 495.0/5.0 95.0/5.0 84.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 95.0/5.0 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ca 5.0/95.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ca 5.0/95.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)	5	116E/HFC-16	1°					
87.3/12.7 32.4(223) 149.6(1032) 91.5(33.1) 3.79 166.8(2.9) 60/40 22.1(152) 126.1(870) 151.7(66.5) 3.33 119.3(2.1)  10 °Condenser temp. 70.0°F, Evaporator temp10.0°F, and Return gas temp. 10.0°F  116E/HFC-227ea 5.0/95.0 20.9(143) 89.9(620) 108.0(42.2) 3.69 97.7(3.5) 95.0/5.0 92.3(636) 331.4(2285) 119.9(48.8) 2.67 259.8(4.6)  15  116E/HFC-227ea 5.0/95.0 16.7(115) 78.3(540) 104.4(40.2) 3.67 82.2(1.4) 95.0/5.0 92.3(636) 333.0(2296) 119.9(48.8) 2.66 259.2(4.6)  20 116E/HFC-236ca 5.0/95.0° 16.2 (112) 72.9 (503) 149.7 (65.4) 3.93 84.2 (1.5) 95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-236ca 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ca 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236ca 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245ca 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)	_	•		243.5(1680)	102.4(39.1)	2.92	206.7(3.6)	
60/40 22.1(152) 126.1(870) 151.7(66.5) 3.33 119.3(2.1)  **Condenser temp. 70.0°F, Evaporator temp10.0°F, and Return gas temp. 10.0°F  116E/HFC-227ca 5.0/95.0 20.9(143) 89.9(620) 108.0(42.2) 3.69 97.7(3.5) 95.0/5.0 92.3(636) 331.4(2285) 119.9(48.8) 2.67 259.8(4.6)  15  116E/HFC-227ca 5.0/95.0 16.7(115) 78.3(540) 104.4(40.2) 3.67 82.2(1.4) 95.0/5.0 92.3(636) 333.0(2296) 119.9(48.8) 2.66 259.2(4.6)  20 116E/HFC-236ca 5.0/95.0° 16.2 (112) 72.9 (503) 149.7 (65.4) 3.93 84.2 (1.5) 95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  ** = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-236cb 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 85.4(589) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ca 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 430 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 1363 (57.9) 2.58 195.5 (3.4)  ** = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 430 59.1 (1.0) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ca 5.0/95.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)				149.6(1032)	91.5(33.1)	3.79	166.8(2.9)	
10 °Condenser temp. 70.0°F, Evaporator temp10.0°F, and Return gas temp. 10.0°F  116E/HFC-227ca 5.0/95.0 20.9(143) 89.9(620) 108.0(42.2) 3.69 97.7(3.5) 95.0/5.0 92.3(636) 331.4(2285) 119.9(48.8) 2.67 259.8(4.6)  15  116E/HFC-227ca 5.0/95.0 16.7(115) 78.3(540) 104.4(40.2) 3.67 82.2(1.4) 95.0/5.0 92.3(636) 333.0(2296) 119.9(48.8) 2.66 259.2(4.6)  20 116E/HFC-236ca 5.0/95.0° 16.2 (112) 72.9 (503) 149.7 (65.4) 3.93 84.2 (1.5) 95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  ** = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-236cb 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ca 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 95.0/5.0 95.0/5.0 84.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  ** = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ca 5.0/95.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)		•	•	•	•	3.33	119.3(2.1)	
116E/HFC-227ca 5.0/95.0 20.9(143) 89.9(620) 108.0(42.2) 3.69 97.7(3.5) 95.0/5.0 92.3(636) 331.4(2285) 119.9(48.8) 2.67 259.8(4.6)  15  116E/HFC-227ca 5.0/95.0 16.7(115) 78.3(540) 104.4(40.2) 3.67 82.2(1.4) 95.0/5.0 92.3(636) 333.0(2296) 119.9(48.8) 2.66 259.2(4.6)  20 116E/HFC-236ca 5.0/95.0° 16.2 (112) 72.9 (503) 149.7 (65.4) 3.93 84.2 (1.5) 95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-236cb 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ea 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  316E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F			, ,	, ,	, ,			
5.0/95.0 20.9(143) 89.9(620) 108.0(42.2) 3.69 97.7(3.5) 95.0/5.0 92.3(636) 331.4(2285) 119.9(48.8) 2.67 259.8(4.6)  116E/HFC-227ea 5.0/95.0 16.7(115) 78.3(540) 104.4(40.2) 3.67 82.2(1.4) 95.0/5.0 92.3(636) 333.0(2296) 119.9(48.8) 2.66 259.2(4.6)  20 116E/HFC-236ca 5.0/95.0° 16.2 (112) 72.9 (503) 149.7 (65.4) 3.93 84.2 (1.5) 95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  a = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-236cb 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ea 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  a = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F	10	*Condenser te	emp. 70.0°F, Ev	aporator temp	10.0°F, and Re	turn ga	s temp. 10.0°F	
5.0/95.0 20.9(143) 89.9(620) 108.0(42.2) 3.69 97.7(3.5) 95.0/5.0 92.3(636) 331.4(2285) 119.9(48.8) 2.67 259.8(4.6)  116E/HFC-227ea 5.0/95.0 16.7(115) 78.3(540) 104.4(40.2) 3.67 82.2(1.4) 95.0/5.0 92.3(636) 333.0(2296) 119.9(48.8) 2.66 259.2(4.6)  20 116E/HFC-236ca 5.0/95.0° 16.2 (112) 72.9 (503) 149.7 (65.4) 3.93 84.2 (1.5) 95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  a = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-236cb 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ea 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  a = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F		44677 (\$4770.00	27			•		
95.0/5.0 92.3(636) 331.4(2285) 119.9(48.8) 2.67 259.8(4.6)  116E/HFC-227ea 5.0/95.0 16.7(115) 78.3(540) 104.4(40.2) 3.67 82.2(1.4) 95.0/5.0 92.3(636) 333.0(2296) 119.9(48.8) 2.66 259.2(4.6)  20 116E/HFC-236ca 5.0/95.0° 16.2 (112) 72.9 (503) 149.7 (65.4) 3.93 84.2 (1.5) 95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-236cb 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ca 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 95.0/5.0 95.0/5.0 84.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F		•		00.0/600\	100 0/40 0)	2 (0	07 7/2 5\	
15  116E/HFC-227ea 5.0/95.0 16.7(115) 78.3(540) 104.4(40.2) 3.67 82.2(1.4) 95.0/5.0 92.3(636) 333.0(2296) 119.9(48.8) 2.66 259.2(4.6)  20  116E/HFC-236ca 5.0/95.0° 16.2 (112) 72.9 (503) 149.7 (65.4) 3.93 84.2 (1.5) 95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-236cb 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30  116E/HFC-236ca 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)		•	` '		•		•	
116E/HFC-227ea 5.0/95.0 16.7(115) 78.3(540) 104.4(40.2) 3.67 82.2(1.4) 95.0/5.0 92.3(636) 333.0(2296) 119.9(48.8) 2.66 259.2(4.6)  20 116E/HFC-236ea 5.0/95.0° 16.2 (112) 72.9 (503) 149.7 (65.4) 3.93 84.2 (1.5) 95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-236eb 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ea 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F	4.5	95.0/5.0	94.3(030)	331.4(2283)	119.9(46.6)	2.07	239.6(4.0)	
5.0/95.0 16.7(115) 78.3(540) 104.4(40.2) 3.67 82.2(1.4) 95.0/5.0 92.3(636) 333.0(2296) 119.9(48.8) 2.66 259.2(4.6)  20 116E/HFC-236ca 5.0/95.0° 16.2 (112) 72.9 (503) 149.7 (65.4) 3.93 84.2 (1.5) 95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  ** = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  25 116E/HFC-236cb 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ca 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  ** = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)	15	1160 /100 0	2700					
95.0/5.0 92.3(636) 333.0(2296) 119.9(48.8) 2.66 259.2(4.6)  20 116E/HFC-236ca 5.0/95.0° 16.2 (112) 72.9 (503) 149.7 (65.4) 3.93 84.2 (1.5) 95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  ** = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-236cb 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ea 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca° 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  ** = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)		•		78 3/5/0)	104 4(40 2)	3 67	82 2(1 4)	
20 116E/HFC-236ca 5.0/95.0° 16.2 (112) 72.9 (503) 149.7 (65.4) 3.93 84.2 (1.5) 95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-236cb 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ca 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)		•			•		•	
5.0/95.0° 16.2 (112) 72.9 (503) 149.7 (65.4) 3.93 84.2 (1.5) 95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-236cb 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ea 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca° 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)		93.0/3.0	92.3(030)	333.0(2290)	119.9(40.0)	2.00	239.2(4.0)	
95.0/5.0 70.9 (489) 301.7 (2080) 127.3 (52.9) 2.71 233.8 (4.1)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-236cb 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ea 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)	20	116E/HFC-2	36ca					
* = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-236cb 5.0/95.0 11.5(79) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ea 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)		5.0/95.0°	16.2 (112)	72.9 (503)	149.7 (65.4)	3.93	84.2 (1.5)	
25		95.0/5.0	70.9 (489)	301.7 (2080)	127.3 (52.9)	2.71	233.8 (4.1)	
25		* 0	4amm af 120	9E		-d -o+v	m gas tomm of 65°E	
116E/HFC-236cb 5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ea 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  a = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 5.0/95.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0* 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)	25	" = Condens	er temp. of 130	r, evaporator te	emp. or 45 F, an	na retu	in gas temp. of 65 r	
5.0/95.0 11.5(79) 53.1(366) 110.8(43.8) 3.97 62.0(1.1) 95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ea 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0* 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)	23	116F/HFC-2	36ch	•				
95.0/5.0 86.0(593) 321.4(2216) 121.4(49.7) 2.66 249.2(4.4)  30 116E/HFC-236ea 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  31 116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)		•		53.1(366)	110.8(43.8)	3.97	62.0(1.1)	
30 116E/HFC-236ea 5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)			• •		•		• ,	
5.0/95.0 10.4(72) 48.7(335) 114.0(45.6) 4.20 60.1(1.1) 95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0* 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)		22,0,000						
95.0/5.0 85.4(589) 321.7(2218) 122.1(50.1) 2.64 247.8(4.4)  116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  a = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0* 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)	30	116E/HFC-2	236ea	•				
116E/HFC-236fa 35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0* 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)		5.0/95.0	10.4(72)	48.7(335)	114.0(45.6)	4.20	60.1(1.1)	
35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)		95.0/5.0	85.4(589)	321.7(2218)	122.1(50.1)	2.64	247.8(4.4)	
35 5.0/95.0 12.5(86) 57.1(394) 110.5(43.6) 3.92 65.8(1.2) 95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)		116E/HEC-2	)36fa	•				
95.0/5.0 87.2(601) 322.8(2226) 121.0(49.4) 2.67 251.6(4.4)  116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0* 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)	35	•	•	57.1(394)	110.5(43.6)	3.92	65.8(1.2)	
116E/HFC-245ca* 5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0* 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)	55	•	• •	*	` ,		•	
5.0/95.0 9.9 (68) 47.0 (324) 153.9 (67.7) 4.30 59.1 (1.0) 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  a = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)			0.12(002)					
40 95.0/5.0 54.0 (372) 279.2 (1925) 136.3 (57.9) 2.58 195.5 (3.4)  * = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb  45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7)  95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea  5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)	:	116E/HFC-2	245ca*	· .				
* = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F  116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)		5.0/95.0	9.9 (68)	•	153.9 (67.7)	4.30	- ,	
116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6) 116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)	40	95.0/5.0	54.0 (372)	279.2 (1925)	136.3 (57.9)	2.58	195.5 (3.4)	
116E/HFC-245cb 45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6) 116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)	•	° = Conden	ser temp, of 13	0°F, evaporator	temp. of 45°F.	and ret	urn gas temp, of 65°F	ì
45 5.0/95.0 21.3(146) 88.3(609) 104.3(40.2) 3.63 96.0(1.7) 95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)   116E/HFC-245ea 5.0/95.0* 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)								
95.0/5.0 93.2(642) 331.4(2285) 119.1(48.4) 2.69 262.0(4.6)  116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)	·	•						
116E/HFC-245ea 5.0/95.0° 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)	45	•	•		•		•	
5.0/95.0* 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)		95.0/5.0	93.2(642)	331.4(2285)	119.1(48.4)	2.69	262.0(4.6)	
5.0/95.0* 9.9 (68) 47.8 (330) 157.9 (69.9) 4.35 60.8 (1.1)		116E/HFC	-245ea					
		•		47.8 (330)	157.9 (69.9	) 4.35	60.8 (1.1)	
	50	•	• •		•	•		

\* = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F

116E/HFC-245fa 5.0/95.0\* 14.1 (97) 64.1 (442) 152.5 (66.9) 4.03 76.2 (1.3) 95.0/5.0 65.4 (451) 292.5 (2017) 129.6 (54.2) 2.70 223.6 (3.9)

10

\* = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F

116E/HFC-254ca 5.0/95.0\* 9.4 (65) 44.7 (308) 156.9 (69.4) 4.32 56.8 (1.0) 15 95.0/5.0 50.1 (345) 273.7 (1887) 139.2 (59.6) 2.54 185.1 (3.3)

\* = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F

	116E/HFC-2	254cb <sup>*</sup>				
20	5.0/95.0	12.1(83)	53.7(370)	118.9(48.3)	4.14	67.0(1.2)
•	95.0/5.0	86.1(594)	318.7(2197)	121.2(49.6)	2.68	250.5(4.4)
	116E/HFC-2	263ca				
	5.0/95.0	9.4(65)	44.8(309)	114.8(46.0)	4.28	56.0(1.0)
25	95.0/5.0	83.1(573)	317.9(2192)	122.6(50.3)	2.62	242.9(4.3)
	116E/HFC-	263fb				
	5.0/95.0	18.1(125)	76.3(526)	120.3(49.1)	3.89	90.4(1.6)
	95.0/5.0	91.0(628)	326.1(2248)	120.0(48.9	2.71	260.4(4.6)
30	•	•	, ,	•		•
	116E/HFC-	272ca				
	5.0/95.0*	21.2 (146)	85.6 (590)	159.4 (70.8)	3.85	101.7 (1.8)
	95.0/5.0	68.7 (474)	284.5 (1962)	125.8 (52.1)	2.89	237.4 (4.2)

\* = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F

116E/HFC-272ea 5.0/95.0\* 13.0 (90) 58.3 (402) 167.4 (75.2) 4.11 72.6 (1.3) 95.0/5.0 54.7 (377) 222.1 (1531) 120.4 (49.1) 3.46 228.0 (4.0)

40

\* = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F

116E/HFC-272fb 5.0/95.0\* 16.2 (112) 70.8 (488) 166.3 (74.6) 3.99 85.8 (1.5) 45 95.0/5.0+ 49.8 (343) 236.8 (1633) 120.5 (49.2) 2.90 193.4 (3.4)

- \* = Condenser temp. of 130°F, evaporator temp. of 45°F, and return gas temp. of 65°F + = Return gas temp. 20°F
- 50 116E/HFC-281ea

5	5.0/95.0	16.7(115)	68.0(469)	132.1(55.6)	4.17	88.8(1.6)
	95.0/5.0	89.7(618)	287.7(1983)	103.1(39.5)	3.08	266.6(4.7)
	116E/HFC-	281fa				
10	5.0/95.0	14.0(96)	57.7(398)	129.9(54.4)	4.39	78.9(1.4)
	95.0/5.0	85.8(591)	273.8(1887)	110.5(43.6)	2.99	249.5(4.4)

## **EXAMPLE 6**

## Refrigerant Performance

The following table shows the refrigerant performance of various compositions. Except where indicated, the data are based on the following conditions.

Evaporator temperature	40.0°F (4.4°C)
Condenser temperature	100.0°F (37.8°C)
Subcool temperature	0°F (-17.8°C)
Return gas temperature	40.0°F (12.8°C)
Compressor efficiency is	75%

#### TABLE 7

25	
4	,

45

20

	Refrig.	Evap. Press. <u>Psia (kPa)</u>	Cond. Press. Psia (kPa	Comp. Di  Temp. °F (		Capacity BTU/min OP (kw)
30	236eaΕβγ/H	IFC-245ca				
	69.1/30.9	6.8 (47)	25.2 (174)	101.5 (38.6)	5.32	42.1 (0.7)
	236caE/HF	C-245ca	-			
.35 ·.	16.1/83.9	6.1 (42)	23.3 (161)	108.3 (42.3)	5.41	39.6 (0.7)
	236eaΕβγ/F	IFC-356mff <sup>*</sup>				
	96.9/3.1	6.8 (47)	25.2 (174)	113.4 (45.2)	5.11	40.4 (0.7)
,		*return gas tem	$p. = 55.0^{\circ}F$ (	12.8°C)		
40	245faΕβγ/H	IFC-356mff*				·
	4.4/95.6	6.5 (45)	23.2 (160)	108.5 (42.5)	5.04	36.8 (0.6)
		*return gas tem	$p. = 55.0^{\circ}F$	12.8°C)		` '

The following compounds have the indicated HGWPs (all HGWP values are relative to CFC-11 = 1.0). The HGWPs were estimated relative

5 to the HGWP of CFC-11 as follows:

HGWP = (IR abs (A) / IR abs. (CFC-11)) x

(t(A)/t(CFC-11))x

(mass (CFC-11) / mass (A))

where A is the gas being analyzed;

IR abs. is the to

IR abs. is the total infrared absorption cross section in the region of interest, that is, where H<sub>2</sub>O and CO<sub>2</sub> do not absorb;

t = atmospheric lifetime; and mass = atomic mass.

15

	•	
	COMPOUND	<u>HGWP</u>
	HFC-125	0.84
	HFC-134	<b>≈</b> 0.28
	HFC-134a	0.28
20	HFC-143a	1.1
	FC-218	>10
	134E	<b>≈</b> 0.1
	143aE	<b>≈</b> 0.2

A composition of a fluoroether and an HFC are prepared, and have the indicated HGWPs.

•	COMPOSITION	<u>HGWP</u>
	(wt.%/wt/%)	
30	134E/HFC-125	0.25
	(80.0/20.0)	
•	134E/HFC-125	0.5
	(46.0/54.0)	
	134E/HFC-134	0.14
35	(80.0/20.0)	
	134E/HFC-134a	0.14
	(80.0/20.0)	
	134E/HFC-143a	0.3
	(80.0/20.0)	
40	143aE/HFC-125	0.33
	(80.0/20.0)	

5	143aE/HFC-143a	0.38
	(80.0/20.0)	
	143aE/HFC-125	0.5
	(53.0/47.0)	
	143aE/HFC-134	0.22
10	(80.0/20.0)	
	143aE/HFC-134a	0.22
	(80.0/20.0)	

The novel compositions of this invention, including the azeotropic or azeotrope-like compositions, may be used to produce refrigeration by condensing the compositions and thereafter evaporating the condensate in the vicinity of a body to be cooled. The novel compositions may also be used to produce heat by condensing the refrigerant in the vicinity of the body to be heated and thereafter evaporating the refrigerant.

In addition to refrigeration applications, the novel constant boiling or substantially constant boiling compositions of the invention are also useful as aerosol propellants, heat transfer media, gaseous dielectrics, fire extinguishing agents, expansion agents for polyolefins and polyurethanes and power cycle working fluids.

Additives such as lubricants, corrosion inhibitors, stabilizers, dyes and other appropriate materials may be added to the novel compositions of the invention for a variety of purposes provided they do not have an adverse influence on the composition for its intended application. Preferred lubricants include esters having a molecular weight of greater than 250.

#### **CLAIMS**

1. A refrigerant composition comprising

10

(a) a cyclic or acyclic hydrofluoroether of the formula  $C_aF_bH_{2a+2-b}O$  wherein a=2 or 3 and b=3,4,6,7 or 8 and b=5 when a=3,

or CF3OCF2OCF3 and

15

- (b) a hydrofluorocarbon of the formula  $C_nF_mH_{2n+2-m}$  wherein  $1 \le n \le 4$  and  $1 \le m \le 8$ .
- A refrigerant composition comprising 1 to 49 weight percent
   CHF<sub>2</sub>OCF<sub>3</sub> and 51 to 99 weight percent of a hydrofluorocarbon of the formula
   C<sub>n</sub>F<sub>m</sub>H<sub>2n+2-m</sub> wherein 1≤ n≤ 4 and 1≤ m≤ 8.
- 3. An azeotropic or azeotrope-like composition comprising effective amounts of: 116E and HFC-32, HFC-41, HFC-125, HFC-134, HFC-134a, HFC-143, HFC-143a, HFC-152a or HFC-161; 125E and HFC-32, HFC-134, HFC-134a, HFC-25 143, HFC-152a or HFC-161; 134E and HFC-143, HFC-227ca, HFC-227ea, HFC-236ca, HFC-236cb, HFC-236ea, HFC-236fa, HFC-245cb, HFC-254cb, HFC-254eb, HFC-338mf or HFC-356mff; 134aE and HFC-143, HFC-227ca, HFC-227ea or HFC-245cb; 143aE and HFC-32, HFC-134, HFC-143a, HFC-152a, HFC-227ca, HFC-227ea or HFC-245cb; C216E and HFC-134, HFC-134a, HFC-143, HFC-152a, 30 HFC-161or HFC-245cb; C-216E2 and HFC-32, HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161, and HFC-245cb; 218E and HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161 or HFC-263fb; 218E2 and HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161, HFC-236fa or HFC-263fb; C-225eEαβ and HFC-143, HFC-236cb, HFC-236ea, and HFC-245cb;  $227caE\alpha\beta$  and HFC-32, HFC-143, HFC-245cb, 35 HFC-272ca, HFC-281ea or HFC-281fa; 227caEβγ and HFC-32, HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161, HFC-263fb, HFC-272ca, HFC-281ea or HFC-281fa; 227eaE and HFC-32, HFC-134, HFC-134a, HFC-143, HFC-152a, HFC-161, HFC-263fb, HFC-272ca, HFC-281ea or HFC-281fa; 236caE and HFC-143, HFC-245ca or HFC-254ca; C-234fE $\alpha\beta$  and HFC-245cb, HFC-245eb, HFC-356mff and 40

HFC-356mmz; C-234fE $\beta\gamma$  and HFC-245ca, HFC-245cb, HFC-245ea, HFC-254ca or

- HFC-356mmz; 236eaEβγ and HFC-143, HFC-245ca, HFC-263ca, HFC-338mf, HFC-356mff or HFC-356mmz; 236faE and HFC-32, HFC-143, HFC-272ca, HFC-272fb or HFC-281fa; or 245faEβγ and HFC-356mff or HFC-356mmz to form an azeotropic or azeotrope-like composition.
- 4. A composition comprising effective amounts of a first component and a second component, where the first component comprises a hydrofluorocarbon, and the second component comprises a hydrofluoroether and has a halocarbon global warming potential less than the halocarbon global warming potential of the first component, such that the composition has a halocarbon global warming potential lower than the halocarbon global warming potential of the first component.

International Application No

I. CLASSIFI	CATION OF SUBJE	CT MATTER (if several classification sy	mbols apply, indicate all) <sup>6</sup>	
According to	o International Patent	Classification (IPC) or to both National Classification	assification and IPC	
Int.C1.	5 C09K5/04	; C09K3/30;	C08J9/14	·
II. FIELDS	SEARCHED			
		Minimum Docume	ntation Searched?	
Classification	on System		Classification Symbols	
			Separation Symbols	
Int.Cl.	5	соэк		i
1110.01.	J			·
				ŀ
		Documentation Searched other	than Minimum Documentation	
		to the Extent that such Documents a	re Included in the Fields Searched®	i
<del></del>	<del></del>			
				<u> </u>
III. DOCUM	ENTS CONSIDER	ED TO BE RELEVANT 9		
Category o	Citation of D	ocument, 11 with indication, where appropris	ate, of the relevant nassages 12	Relevant to Claim No.13
		,	and and seed the seed and	account to Claim 1401-
	En 4 0 ·	20E 727 (M D 0040E 8 00	CON I	1
X		385 737 (W.R.GRACE & CO	cunn.)	1,3
		mber 1990	·	
		e 2, line 1 - line 2		
		e 4, line 18 - line 24		
	see cla	ims 3-5,7 <b>-</b> 9		1
Х	DATABAS			1-3
	Week 91			
	Derwent	Publications Ltd., Lon	idon, GB;	
		3 093 890 (DAIKIN KOGYO	) KK) 18	Į į
1	April 1			
1	see abs	tract		
				1
X	DATABAS	E WPI		1-3
	Week 91	.22,	•	
	Derwent	Publications Ltd., Lor	ndon, GB;	]
1	& JP,A.	3 093 889 (DAIKIN KOGYO	) KK) 18	
1	April 1		·•	
İ	see abs	•		
l. · · · ·		<b>→</b>		
1		· .	-/	
1			/	
	al categories of cited d		"I" later document published after the interior priority date and not in confilet with	the application but
	cument defining the g axidered to be of parti	eneral state of the art which is not cular relevance	cited to understand the principle or theo	ry underlying the
"E" ea	rlier document but pul	blished on or after the international	invention "X" document of particular relevance; the cl	timed investing
	ing date	Low doubte as substitut allefactors	cannot be considered povel or cannot be	considered to
wh	ich is cited to establis	row doubts on priority claim(s) or th the publication date of another	involve an inventive step	simal investice
cit	ation or other special	reason (as specified)	"Y" document of particular relevance; the ci	ntive step when the
05 do	ocument referring to a her means	n oral disclosure, use, exhibition or	document is combined with one or more ments, such combination being obvious	other such docu-
P do	cument published pric	or to the international filing date but	in the art.	•
la la	ter than the priority d	ate daimed	"&" document member of the same patent for	umily
IV. CERT	TEICATION			
		f the International Secret	T Book and the second	
אדוני מו נו)	·	f the International Search	Date of Mailing of this International Se	earch Report
]	11 AU	GUST 1993	2 5. 08. 93	
			. 2 3, 40, 33	
Internation	nal Searching Authori	ty	Signature of Authorized Officer	
1	EUROP	EAN PATENT OFFICE	PUETZ C.	
Para PCT//S	A /210 (second shoul) ( Inn	1005		

III. DOCUM	ENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)	
Category o	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.
x	DATABASE WPI Week 9122, Derwent Publications Ltd., London, GB; & JP,A,3 093 883 (DAIKIN KOGYO KK) 18 April 1991 see abstract	1-3
E	WO,A,9 311 201 (UNITED STATES ENVIRONMENTAL PROTECTION AGENCY) 10 June 1993 see page 3, line 2 - line 16; tables 3,4 see claims 1,3-7	1-3
X	DATABASE WPI Week 9122, Derwent Publications Ltd., London, GB; & JP,A,3 093 882 (DAIKIN KOGYO KK) 18 April 1991 see abstract	1,3
A	EP,A,O 127 365 (IMPERIAL CHEMICAL INDUSTRIES) 5 December 1984 see page 2, line 15 - page 6, line 2 see examples 1,4,5,7	1,3
<b>A</b>	DATABASE WPI Week 9221, Derwent Publications Ltd., London, GB; & JP,A,4 110 386 (DAIKIN KOGYO KK) 10 April 1992 see abstract	1
	•	
·		
<u>.</u>		

# ANNEX TO THE INTERNATIONAL SEARCH REPORT ON INTERNATIONAL PATENT APPLICATION NO.

US 9304614 SA 74292

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report. The members are as contained in the European Patent Office EDP file on

08/93

Patent document cited in search report	Publication date		nt family mber(s)	Publicatio date
EP-A-0385737	05-09-90	US-A- AU-B- AU-A- CA-A- JP-A-	4961321 614215 4929990 2008862 2248490	09-10-90 22-08-91 06-09-90 31-08-90 04-10-90
WO-A-9311201	10-06-93	None		1 <b></b>
EP-A-0127365	05-12-84	AU-A- JP-A- US-A-	2839284 60004582 4541943	22-11-84 11-01-85 17-09-85
				· ~ ~ ~ ~ ~ ~ ~ ~ ~ .